

SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

SECTION 1. IDENTIFICATION

Product name : Ti-Pure™ R-706 Titanium Dioxide Pigment

SDS-Identcode : 130000030872

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Coloring agent
Pigment

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H361 Suspected of damaging fertility or the unborn child.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version 5.0 Revision Date: 07/01/2020 SDS Number: 1560892-00011 Date of last issue: 04/14/2020
Date of first issue: 04/21/2017

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Titanium dioxide	13463-67-7	$\geq 90 - \leq 100$
Silicon dioxide	7631-86-9	$\geq 1 - \leq 5$
Aluminium hydroxide	21645-51-2	$\geq 1 - \leq 5$
Trimethylolpropane	77-99-6	$\geq 0.1 - \leq 1$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : irritant effects
Suspected of damaging fertility or the unborn child.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment

SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

||| when the potential for exposure exists (see section 8).
Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Not applicable
Will not burn

Unsuitable extinguishing media : Not applicable
Will not burn

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Metal oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

||| Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

||| Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version 5.0 Revision Date: 07/01/2020 SDS Number: 1560892-00011 Date of last issue: 04/14/2020
Date of first issue: 04/21/2017

- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not swallow.
Avoid contact with eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³ (Silica)	NIOSH REL
Aluminium hydroxide	21645-51-2	TWA (Respirable particulate matter)	1 mg/m ³ (Aluminum)	ACGIH

- Engineering measures** : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

- Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazard.

SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version 5.0	Revision Date: 07/01/2020	SDS Number: 1560892-00011	Date of last issue: 04/14/2020 Date of first issue: 04/21/2017
----------------	------------------------------	------------------------------	---

dous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

- | | | | |
|--|----------|---|---|
| | Material | : | Chemical-resistant gloves |
| | Remarks | : | Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. |

	Eye protection	:	Wear the following personal protective equipment: Safety glasses
--	----------------	---	---

- | | | | |
|--|--------------------------|---|---|
| | Skin and body protection | : | Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc). |
|--|--------------------------|---|---|

	Hygiene measures	:	If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.
--	------------------	---	--

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	solid, crystalline
Color	:	white
Odor	:	odorless
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	3,349 °F / 1,843 °C
Initial boiling point and boiling range	:	5,432 °F / 3,000 °C

SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Will not burn
		Not expected to form explosive dust-air mixtures.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	3.4 - 4.3
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	The substance or mixture is not classified self-reactive.
Viscosity		
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	None known.
Conditions to avoid	:	None known.
Incompatible materials	:	None.

Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Ingestion
Eye contact

Acute toxicity

|| Not classified based on available information.

Components:**Titanium dioxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 10,000 mg/kg

Silicon dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Aluminium hydroxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.09 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Trimethylolpropane:

SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 0.85 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Titanium dioxide:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Silicon dioxide:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Aluminium hydroxide:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Trimethylolpropane:

Species	: Rabbit
Result	: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Titanium dioxide:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Silicon dioxide:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Aluminium hydroxide:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

Trimethylolpropane:

Species	: Rabbit
Result	: No eye irritation

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Titanium dioxide:**

Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Aluminium hydroxide:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Trimethylolpropane:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Titanium dioxide:**

Germ cell mutagenicity - Assessment	: Weight of evidence does not support classification as a germ cell mutagen.
-------------------------------------	--

Silicon dioxide:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
Genotoxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat

Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue:
5.0	07/01/2020	1560892-00011	04/14/2020
			Date of first issue: 04/21/2017

Application Route: Ingestion

Result: negative

Aluminium hydroxide:

Genotoxicity in vitro

: Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: positive
Remarks: Based on data from similar materials

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: equivocal
Remarks: Based on data from similar materials

Test Type: in vitro micronucleus test
Result: positive
Remarks: Based on data from similar materials

Genotoxicity in vivo

: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Trimethylolpropane:

Genotoxicity in vitro

: Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Carcinogenicity

Not classified based on available information.

Product:

Remarks

: In lifetime inhalation studies rats were exposed for 2 years to respectively 10, 50 and 250 mg/m³ of respirable TiO₂. Slight lung fibrosis was observed at 50 and 250 mg/m³ levels. Microscopic lung tumours were also observed in 13 percent of the rats exposed to 250 mg/m³, an exposure level that caused lung overloading and impairment of rat lungs clearance mechanisms.

In further studies, these tumours were found to occur only under particle overload conditions in a uniquely sensitive species, the rat, and have little or no relevance for humans. The pulmonary inflammatory response to TiO₂ particles exposure was also found to be much more severe in rats than in other rodent species.

In February 2006, IARC has re-evaluated Titanium dioxide as pertaining to Group 2B: "possibly carcinogenic to humans", based upon inadequate evidence in humans and sufficient

Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

evidence in experimental animals for the carcinogenicity of titanium dioxide. IARC evaluation guidelines consider the generation of tumours, in 2 different studies within the same animal species, to be adequate criteria for an assessment of sufficient evidence.

The conclusions of several epidemiology studies on more than 20000 TiO₂ industry workers in Europe and the USA did not suggest a carcinogenic effect of TiO₂ dust on the human lung. Mortality from other chronic diseases, including other respiratory diseases, was also not associated with exposure to TiO₂ dust.

Based upon all available study results, Chemours scientists conclude that titanium dioxide will not cause lung cancer or chronic respiratory diseases in humans at concentrations experienced in the workplace.

Components:**Titanium dioxide:**

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Silicon dioxide:

Species : Rat
 Application Route : Ingestion
 Exposure time : 103 weeks
 Result : negative

Aluminium hydroxide:

Species : Rat
 Application Route : inhalation (dust/mist/fume)
 Exposure time : 86 weeks
 Result : negative
 Remarks : Based on data from similar materials

IARC

Group 2B: Possibly carcinogenic to humans
 Titanium dioxide

13463-67-7

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:**Titanium dioxide:**

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

Silicon dioxide:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Aluminium hydroxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Trimethylolpropane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: positive

Effects on fetal development : Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:

Titanium dioxide:

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Titanium dioxide:

Species : Rat
NOAEL : 24,000 mg/kg

SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

LOAEL	: > 24,000 mg/kg
Application Route	: Ingestion
Exposure time	: 28 d
Remarks	: No significant adverse effects were reported

Species	: Rat
NOAEL	: 0.01 mg/l
LOAEL	: 0.05 mg/l
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 730 d

Silicon dioxide:

Species	: Rat
NOAEL	: 1.3 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 13 Weeks

Aluminium hydroxide:

Species	: Rat
NOAEL	: > 100 mg/kg
Application Route	: Ingestion
Exposure time	: 364 Days
Method	: OECD Test Guideline 426
Remarks	: Based on data from similar materials

Species	: Rat
NOAEL	: > 0.2 mg/kg
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 12 Months
Remarks	: Based on data from similar materials

Trimethylolpropane:

Species	: Rat
NOAEL	: 67 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Titanium dioxide:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h

Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (*Pseudokirchneriella subcapitata* (green algae)): > 100 mg/l
Exposure time: 72 h

NOEC (algae): 5,600 mg/l
Exposure time: 72 h

Silicon dioxide:

Toxicity to fish : LC50 (*Danio rerio* (zebra fish)): > 10,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 1,000 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (*Desmodesmus subspicatus* (green algae)): > 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (*Desmodesmus subspicatus* (green algae)): 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Aluminium hydroxide:

Toxicity to fish : LL50 (*Salmo trutta* (brown trout)): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (*Daphnia magna* (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EL50 (*Selenastrum capricornutum* (green algae)): > 100 mg/l
Exposure time: 96 h

Trimethylolpropane:

Toxicity to fish : LC50 (*Oryzias latipes* (Orange-red killifish)): > 1,000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 13,000 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (*Pseudokirchneriella subcapitata* (green algae)): > 1,000 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chron- : NOEC (*Daphnia magna* (Water flea)): > 1,000 mg/l
Exposure time: 21 d

SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

ic toxicity)

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h

Persistence and degradability

Components:

Trimethylolpropane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 6 %
Exposure time: 28 d

Bioaccumulative potential

Components:

Trimethylolpropane:

Partition coefficient: n-octanol/water : log Pow: -0.47

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Reproductive toxicity

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Titanium dioxide	13463-67-7
Silicon dioxide	7631-86-9
Inorganic metal oxide	Trade secret

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Silicon dioxide	7631-86-9
-----------------	-----------

California Permissible Exposure Limits for Chemical Contaminants

Titanium dioxide	13463-67-7
Silicon dioxide	7631-86-9

SECTION 16. OTHER INFORMATION

Further information


SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version 5.0 Revision Date: 07/01/2020 SDS Number: 1560892-00011 Date of last issue: 04/14/2020
Date of first issue: 04/21/2017

NFPA 704:



HMIS® IV:

HEALTH	*	0
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Ti-Pure™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

These products may not be directly added to food, pharmaceuticals, cosmetics, or cigarette papers/filters for tobacco products.

Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

In the manufacture of titanium dioxide, product is packaged at temperatures of approximately 100 to 120°C (212 to 248°F). When pigment is shipped shortly after manufacture, it may stay hot for a very long time depending on ambient temperatures and inventory storage practices. Use caution while handling hot pigment to prevent burns to personnel. Use caution in solvent applications to prevent ignition of solvent.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Sub-

SAFETY DATA SHEET



Ti-Pure™ R-706 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2020
5.0	07/01/2020	1560892-00011	Date of first issue: 04/21/2017

stances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 07/01/2020

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8