

TECHNICAL DATA SHEET

H.B. Fuller® CASEMATE WB 8921 P

| Type of Product | Water-based adhesive. | |
|-------------------------|--|--|
| Product Characteristics | very good lay-flat properties very good machinability excellent adhesion on difficult to bond surfaces high wet tack easy to clean | |
| Typical Applications | Developed for the casing-in of book blocks into covers. | |
| Suitable Substrates | Leather, acetate- and PP foils, as well as lacquered cardboards and plasticized PVC - and PP-foils as covers. It is important to ensure that the desired level of adhesion is obtained on the necessary substrates, including long-term tests. | |

Typical Properties *

| Property | Value |
|---|---------------------|
| Colour | white |
| Film | soft, elastic |
| рН | approx. 5 |
| Solids content | approx. 54% |
| Viscosity (Brookfield; ASTM D 3236-88; at 20°C) | approx. 3 100 mPa.s |
| Shelf life | 6 months |

* Typical values only, slight variations may occur but will not affect product's meeting the standard technical parameters as stated; please consult our CoA for more details (available on request).



.

| Application Instructions | Apply with roller. Application temperature should be between $15^{\circ}C - 25^{\circ}C$. |
|--------------------------|--|
| Cleaning Instructions | Adhesive residues may be washed off with warm water. |
| Typical Packaging | Please contact your local Sales Office for available packaging options. |
| Storage Conditions | In original sealed packaging protected from sun, dust, moisture and high temperatures. Clean and dry conditions above +15°C and below +25°C. |
| Disposal Advice | Please refer to the MSDS for disposal instructions. |
| Safety Advice | Please refer to the MSDS for safety advice. |

. .

. .

IMPORTANT: Information, specifications, procedures, and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid bases or damages or give desired results. It is user's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. The user is advised to review the specific context of the intended use to determine whether the user's intended use violates any law or infringes upon any patent(s). No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.



NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, (1) the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. (2) H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply. (3) Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence, or for breach of any mandatory implied terms unless period by law.