

SINGLE-PLY RESTORATION

Millennium Water Block Mastic (BP-300)



DESCRIPTION

Millennium Water Block Mastic is a gray colored, high performance, low VOC, non-curing, permanently flexible gun grade mastic. It maintains a positive seal by remaining flexible and adhered to all approved substrates.

BASIC USE

Millennium Water Block Mastic is a non-curing, non-skinning secondary sealant designed for unexposed waterproofing applications. Millennium Water Block Mastic can be used:

- Behind termination bar
- Under roof drains
- Acoustical sealant
- Roof panel rib sealant
- Vapor barrier sealant

SURFACE PREPARATION

All work surfaces should be clean, dry, free of dirt, dust, debris, oils, un-adhered coatings, deteriorated membrane and other contaminants that may result in a surface that is not sound or is uneven. If necessary, clean the surface to receive the Millennium Water Block Mastic with an approved surface cleaner.

LIMITATIONS

- Talc, dust, oil, ice, snow, or wet conditions inhibit good adhesion. Clean and dry surfaces are necessary for proper installation of this product.
- Not recommended for direct contact with insulating glass sealants.
- Not to be used in locations exposed to direct UV light.
- Not to be painted.
- Use only in unexposed areas.

SAFETY

Prior to working with this or any adhesive product consult product label and Safety Data Sheet (SDS) for necessary health and safety precautions.

STORAGE

Store material in original unopened packaging at temperatures between 40°F-110°F (4°C-43°C). Shelf life is 24 months when stored as recommended.

PACKAGING AND COVERAGE

Millennium Water Block Mastic is available in the following package:

Cartridge Size	Part #	Cartridges/Case
10.3 fl. oz. (305 mL)	CT-0304-GR	30

Coverage rate will be approximately 10-12 lineal feet (3.0 - 3.7m) for a 1/2" (1.3cm) bead.

FEATURES

BENEFITS

Low VOC formula (<150 g/L)	Suitable for use in VOC regulated markets
Excellent adhesion to clean and dry substrates. No primer required	Adheres to concrete, masonry, gypsum, metal, glass, plastic and wood surfaces
Excellent gunnability at low temperatures	Wide application temperature range
Water resistant, even under immersion conditions	Long term moisture barrier
Non-skinning and non-curing	Permanently flexible even at low temperatures

APPLICATION

1. Cut nozzle on cartridge to allow proper bead installation.
2. Apply an approximately 1/2" (1.3cm) size bead (or appropriate size bead to completely seal void) of Millennium Water Block Mastic between the objects to be sealed.
3. Install product and fasten accordingly. Note: Millennium Water Block Mastic is not intended to be used as a structural sealant or to replace mechanical fastening. It is intended for waterproofing only.
4. For drain applications, install a continuous bead of Millennium Water Block Mastic in between roof membrane and drain bowl. Install drain clamping ring according to drain manufacturers recommendations.
5. Note: This is a non-skinning, non-curing sealant and is intended for unexposed applications only.

TECHNICAL DATA

Typical Physical Properties and Characteristics		
	Typical Values	Test Method
Base Polymer	Synthetic Rubber	FTIR
Adhesion	Excellent to most clean, dry surfaces	ASTM C 794
Water Resistance	No adhesion loss, no shrinkage, no chalking	
Flash Point	105°F (40°C)	ASTM D 56
VOC Content	<150 g/L	ASTM D 3960
Solids content	85% Minimum	ASTM C 681
Weight/Gal	10.5 lbs.	ASTM D 1475
Application Properties		
Service temperature	-40°F to 200°F (-40°C to 93°C)	ASTM D 3359
Application temperature	20°F to 120°F (-6°C to 49°C)	ASTM C 603

NOTE:

The foregoing information is published as general information only. The listed properties and performance characteristics are typical values and are not to be interpreted as manufacturing specifications.



For more information about our company, visit www.hbfuller.com/construction.



Join the Conversation | www.hbfuller.com/connect

WARRANTY: H.B. Fuller warrants its products to conform to H.B. Fuller's specifications at the time of sale when tested according to H.B. Fuller standards. If a product is proven to be defective when tested according to H.B. Fuller standards, H.B. Fuller will, at its option, refund the purchase price or replace or repair the defective product. THIS LIMITED WARRANTY IS THE BUYER'S SOLE AND EXCLUSIVE REMEDY AGAINST H.B. FULLER AND IS IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event shall H.B. Fuller be liable for any special, incidental, consequential, or punitive damages arising out of any claims whether based on negligence, contract, warranty, strict liability or otherwise.