

TECHNICAL DATA SHEET

Swift®tak 5020

Type of Product Water-based adhesive.

Product Characteristics - fast setting

very good machinability

easy cleaning

Typical Applications To produce folding boxes in the "glue-line method" (Longitudinal

seam). Tube forming bags & sacks (side seam).

Suitable Substrates Paper and cartons, natural or with different coatings.

Typical Properties

Property	Value
Colour	white
Dry Film	clear, flexible
рН	approx. 5
Solids content	approx. 43%
Density	approx. 1,05 g/cm ³
Viscosity (Brookfield RTV, Sp3, 20rpm, at 20°C)	approx. 1 800 mPa.s
Shelf life	6 months

Application Instructions Application: nozzle, roller, wheel or hand.

Application temperature: between +15°C and +25°C

Amount of adhesive can vary due to different materials and the different

requirements for the bonding.

Tests on the different materials are necessary.



TECHNICAL DATA SHEET

Cleaning Instructions Fresh adhesive, cleaning with water.

Typical Packaging Please contact your local Sales Office for available packaging options.

Storage Conditions In original sealed packaging in clean and dry conditions above +5°C and

below +35°C.

Disposal Advice Please refer to the MSDS for disposal instructions.

Safety Advice Please refer to the MSDS for safety advice.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is user's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. The user is advised to review the specific context of the intended use to determine whether the user's intended use violates any law or infringes upon any patent(s). No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

H.B. Fuller

©H.B. Fuller Company

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of itness for a particular purpose) and limits of liability. All other terms are rejected. In any event, (1) the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. (2) H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply. (3) Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence, or for breach of any mandatory implied terms unless permitted by law.