

Adecol[®] C-1029

Type of Adhesive	The adhesive is an emulsion of polymers, whose diluent is water based, with strong tack.
Product Characteristics	High performance adhesive, with excellent performance on metallized labels and with varnish, presenting strong initial tack and great results.
Typical Applications	The adhesive used for gluing wrap-around paper labels in dry or wet glass, PET and PVC bottle. Also used for placing tax seal in aluminum, plastic or glass structure, in high-speed Krones automatic machines, with adhesive pumping. Consumption of 15g/m ² , with good refrigerator resistance.
Substrates	Aluminum, glass or plastic (PVC and PET) surfaces, with paper or wrap around label and tax stamp.

Typical Properties

Property	Value
Aspect	Liquid
Color	Beige
Film	Translucent
Brookfield RVT viscosity (sp 7/20 rpm at 25 ° C)	50,000 – 60,000 mPas
Solid content (%)	40.0 – 55.0%
pH. at 25 ° C	7.0 – 9.0
Shelflife	6 months

Application Instructions	Surfaces must be free of dust, grease or oil. For manual gluing, be careful to keep the brush in water after use, thus avoiding dryness and supposed lumps for the gluing area. The application must be verified for each specific case according to the following factors: Characteristics of the substrates, equipment, speed, amount of adhesive and the ambient temperature must be above 15° C.
Cleaning Instructions	Request information about cleaning options available to the Technical department.
Typical Packaging	Please contact your local Sales Office for available packaging options.
Storage Conditions	In the original packaging, well closed and protected from the sun, dust, humidity and high temperatures. Clean and dry place, temperature between 15 ° C and 35 ° C is advisable.
Disposal Advice	Consult the Safety Data Sheet (SDS).
Safety Advice	Consult the Safety Data Sheet (SDS).

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

© and ™ are trademarks of H.B. Fuller Company ("H.B. Fuller") or one of its affiliated entities.

NOTE TO USER: *by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, (1) the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. (2) H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising* ©H.B. Fuller Company out of or in connection with product supply.

**H.B. Fuller**www.hbfuller.com