

## Adecol<sup>®</sup> C-1091

**Type of Adhesive** The **ADECOL<sup>®</sup> C-1091** adhesive is a polyvinyl acetate homopolymer in aqueous dispersion, modified with special additives.

**Product Characteristics** The **ADECOL<sup>®</sup> C-1091** adhesive presents good fluidity with good initial grip for good application performance.

**Typical Applications** This adhesive is intended for palletizing various types of boxes without treatment, applied by nozzle or manual.

**Substrates** Untreated cardboard boxes, untreated boxes in general.

### Typical Properties

Property	Value
Aspect	Liquid
Color	White
Film	Colorless and translucent
Brookfield RVT viscosity (sp 3/20 rpm at 25°C)	1,500 – 2,000 mPas
Solid content (%)	49.0 – 52.0%
pH. at 25 ° C	4.0 – 5.5
Shelflife	6 months

**Application Instructions** Surfaces must be free of dust, grease or oil.  
For manual gluing, be careful to keep the brush in water after use, thus avoiding dryness and supposed lumps for the gluing area.  
The application must be verified for each specific case according to the following factors: Characteristics of the substrates, equipment, speed, amount of adhesive and the ambient temperature must be above 15° C.

<b>Cleaning Instructions</b>	Request information about cleaning options available to the Technical department.
<b>Typical Packaging</b>	Please contact your local Sales Office for available packaging options.
<b>Storage Conditions</b>	In the original packaging, well closed and protected from the sun, dust, humidity and high temperatures. Clean and dry place, temperature between 15 ° C and 35 ° C is advisable.
<b>Disposal Advice</b>	Consult the Safety Data Sheet (SDS).
<b>Safety Advice</b>	Consult the Safety Data Sheet (SDS).

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

© and ™ are trademarks of H.B. Fuller Company ("H.B. Fuller") or one of its affiliated entities.

**NOTE TO USER:** *by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, (1) the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. (2) H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.*