



Printing Date 07/22/2021 Revision Number 2 Revision Date 07/22/2021

1 Identification

- · Product identifier
- · Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 1
- · Article number: 730698
- · Relevant identified uses of the substance or mixture. Adhesive
- · Application of the substance / the mixture Adhesive
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Royal Adhesives & Sealants, LLC

17340 Munn Road

Chagrin Falls, OH 44023

Information Phone Number: 517-764-0334

- · Information department: Global Regulatory Department.
- Emergency telephone number:

ChemTrec: Day or Night within USA and Canada: 1-800-424-9300. Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

· Signal word Danger

(Contd. on page 2)

Printing Date 07/22/2021 Revision Number 2 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 1

(Contd. of page 1)

· Hazard statements

Combustible liquid.

Harmful if inhaled.

Causes skin irritation.

Causes serious eve irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause respiratory irritation.

· Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 1 Reactivity = 1

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Aromatic Isocyanates

(Contd. on page 3)

Printing Date 07/22/2021 Revision Number 2 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 1

(Contd. of page 2)

· Hazardous d	components:	
39420-98-9	Isocyanates, Reaction product of polyol with Methylenediphenyl diisocyanate	50-100%
101-68-8	4,4'-methylenediphenyl diisocyanate (MDI)	5-20%
26447-40-5	methylenediphenyl diisocyanate	2.5-10%

· Additional information:

All concentrations are in percent by weight unless the ingredient is a gas. Gas concentrations are in percent by volume. Any pigments or fillers in this product which may be considered "Hazardous" are potentially hazardous only if inhaled as an airborne dust. Exposure by these ingredients as used in sealants, putties, bedding compounds and non-sprayable products is highly unlikely. For the wording of the listed risk phrases refer to section 15.

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Overexposure, remove to fresh air and seek medical attention.
- · After skin contact:

If skin becomes irritated seek medical attention.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, sand, extinguishing powder. Do not use water.

Extinguishing powder. Do not use water.

- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

Dried solids can burn and release toxic fumes and vapors.

- · Advice for firefighters
- · **Protective equipment:** Protective clothing and respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Keep away from ignition sources
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Cover spilled material with neutralization solution (see below) and mix Wait 15 minutes. Collect material in open-head metal containers. Repeat neutralization and cleaning process until surface is decontaminated. Apply drum lid but DO NOT secure. Allow containers to vent for 72 hours to let carbon dioxide escape.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

Printing Date 07/22/2021 Revision Number 2 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 1

(Contd. of page 3)

Dispose of contaminated material as waste in accordance with federal state and local regulations. Ensure adequate ventilation.

· Reference to other sections

Neutralization solutions:

- 1. A mixture of 90% water. 3-8% ammonium hydroxide or concentrated ammonia, and 2% liquid detergent.
- 2. A mixture of 80% water, 20% non-ionic surfactant.

Apply solution. Wait 15 minutes. Collect in open-head container. Re-apply until surface is decontaminated. Apply drum lid but DO NOT secure. Let containers vent for 72 hours allowing carbon dioxide to escape. Secure drum lid.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Avoid prolonged or repeated contact with skin.

Avoid contact with eyes.

Wash thoroughly after handling.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Product reacts with water. Reaction may produce heat and/or gases. Container may rupture from gas generation in a fire situation. This reaction may be violent.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Keep containers tightly closed when not in use. Protect from atmospheric moisture.

- Information about storage in one common storage facility: Keep away from open flames and high temperatures.
- · Further information about storage conditions:

Storage Temperature - 32F - 90F

Keep receptacle tightly sealed.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

101-68-8 4,4'-methylenediphenyl diisocyanate (MDI)

PEL Ceiling limit value: 0.2 mg/m³, 0.02 ppm

REL Long-term value: 0.05 mg/m³, 0.005 ppm

Ceiling limit value: 0.2* mg/m³, 0.02* ppm

*10-min

TLV Long-term value: 0.051 mg/m³, 0.005 ppm

(Contd. on page 5)

Printing Date 07/22/2021 Revision Number 2 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 1

(Contd. of page 4)

· Additional information:

MDI products have poor warning properties, since recognition of an odor is far above the TLV. Observe OSHA regulations for respirator use (29 CFR 1910.134).

The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Chloroprene rubber, CR

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Face Shield

Safety glasses with side shields.



Tightly sealed goggles

Body protection:

Apron

Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Thick Liquid

(Contd. on page 6)

Printing Date 07/22/2021 Revision Number 2 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 1

	(Contd. of pag
Color:	Tan
Odor:	Aromatic
Change in condition	
Melting point:	Undetermined.
Boiling point:	Undetermined
Flash point:	93 °C (199.4 °F)
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Heating may cause an explosion.
Specific gravity at 20 °C (68 °F	F): 1.1 g/cm³ (9.1795 lbs/gal)
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
	Reacts with water
Viscosity:	
<i>Dynamic at 20 °C (68 °F):</i>	9500 CPS
Solvent content:	
Organic solvents:	0.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

Contact with moisture, other materials that react with isocyanates, or temperatures above 350F (177C), may cause polymerization.

· Possibility of hazardous reactions

Violent reaction with water at high temperatures.

May produce violent reactions with bases and numerous organic substances including alcohols and amines. MDI reacts slowly with water to form Carbon Dioxide gas. This gas can cause sealed containers to expand and possibly rupture. Contact with moisture, other materials that react with isocyanates, or temperatures above 350F, may cause polymerization.

· Conditions to avoid

Exposure to high temperatures.

Moisture

· Incompatible materials:

Reacts with amines, caustic alkali solutions, alcohols, ammonia, oxidizers, acids, polyols.

Reacts with water forming carbon dioxide-may rupture sealed containers if contaminated with water.

May produce violent reactions with bases and numerous organic substances including alcohols and amines.

Hazardous decomposition products:

Carbon dioxide, carbon monoxide, oxides of nitrogen, dense black smoke, hydrogen cyanide, isocyanic acid, other undeterminated compounds.

TICA

Printing Date 07/22/2021 Revision Number 2 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 1

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate (MDI)

Oral LD50 2200 mg/kg (mouse)

- · Primary irritant effect:
- on the skin:

Skin irritant.

Irritant to skin and mucous membranes.

- · on the eye: Irritating effect.
- · Sensitization:

Inhalation - Sensitization possible through inhalation.

Skin Contact - Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (Inter	national Agency for Research on Cancer)	
39420-98-9	Isocyanates, Reaction product of polyol with Methylenediphenyl diisocyanate	3
101-68-8	4,4'-methylenediphenyl diisocyanate (MDI)	3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Printing Date 07/22/2021 Revision Number 2 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 1

(Contd. of page 7)

Disposal must be made according to official regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADN, IMDG, IATA	not regulated
UN proper shipping name DOT, ADN, IMDG, IATA	not regulated
Transport hazard class(es)	
DOT, ADN, IMDG, IATA Class	not regulated
Packing group DOT, IMDG, IATA	not regulated
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
Transport in bulk according to Annex A MARPOL73/78 and the IBC Code	II of Not applicable.
Transport/Additional information:	MDI (CAS 101-68-8) exhibits a CERCLA RQ equal to 5,000 pounds. Quantites less than the RQ amount are not regulated in transportation.
UN "Model Regulation":	not regulated

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- · Section 313 (Specific toxic chemical listings):
- 39420-98-9 Isocyanates, Reaction product of polyol with Methylenediphenyl diisocyanate

101-68-8 4,4'-methylenediphenyl diisocyanate (MDI)

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· Proposition 65

Please contact H.B. Fuller for more information regarding Proposition 65 on this product: reg.request@hbfuller.com.

· (DSL) Canada Dosmestic Substance List

(Contd. on page 9)

Revision Date 07/22/2021 Printing Date 07/22/2021 Revision Number 2

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 1

(Contd. of page 8)

· Cancerogenity categories	
· EPA (Environmental Protection Agency)	
39420-98-9 Isocyanates, Reaction product of polyol with Methylenediphenyl diisocyanate	CBD
101-68-8 4,4'-methylenediphenyl diisocyanate (MDI)	D, CBD
· TLV (Threshold Limit Value)	
None of the ingredients listed.	
· MAK (German Maximum Workplace Concentration)	
39420-98-9 Isocyanates, Reaction product of polyol with Methylenediphenyl diisocyanate	4
101-68-8 4,4'-methylenediphenyl diisocyanate (MDI)	4
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- · Department issuing SDS: Global Regulatory Department.
- · Creation Date: 08/18/2016
- · Contact:
- · Date of preparation / last revision 07/22/2021 / 1
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3





Printing Date 07/22/2021 Revision Number 3 Revision Date 07/22/2021

1 Identification

- · Product identifier
- · Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 2
- · Article number: 730699
- · Relevant identified uses of the substance or mixture. Adhesive
- · Application of the substance / the mixture Adhesive
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Royal Adhesives & Sealants, LLC

17340 Munn Road

Chagrin Falls, OH 44023

Information Phone Number: 517-764-0334

- · Information department: Global Regulatory Department.
- · Emergency telephone number:

ChemTrec: Day or Night within USA and Canada: 1-800-424-9300. Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

Classification of the substance or mixture

The product does not meet the criteria for classification as hazardous under the GHS and 29 CFR 1910.1200

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system:
- · NFPA ratings (scale 0 4)




Health = 0

Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



0 Health = 0

1 Fire = 1

PHYSICAL HAZARD $\boxed{0}$ Physical Hazard = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture

(Contd. on page 2)

Printing Date 07/22/2021 Revision Number 3 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 2

(Contd. of page 1)

· Hazardous	components:	
1333-86-4	Carbon black	<i>≤</i> 2.5%
25973-55-1	2,(2H-Benzotriazol-2-yl)-4,6-ditertpentylphenol	≤0.5%

· Additional information:

All concentrations are in percent by weight unless the ingredient is a gas. Gas concentrations are in percent by volume. Any pigments or fillers in this product which may be considered "Hazardous" are potentially hazardous only if inhaled as an airborne dust. Exposure by these ingredients as used in sealants, putties, bedding compounds and non-sprayable products is highly unlikely. For the wording of the listed risk phrases refer to section 15.

4 First-aid measures

- Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Overexposure, remove to fresh air and seek medical attention.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Use fire fighting measures that suit the environment.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Protective clothing and respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

USA

Printing Date 07/22/2021 Revision Number 3 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 2

(Contd. of page 2)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Avoid prolonged or repeated contact with skin.

Avoid contact with eyes.

Wash thoroughly after handling.

Open containers in a well ventilated area and avoid breathing headspace vapors.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m³

REL Long-term value: 3.5* mg/m³
*0.1 in presence of PAHs;See Pocket Guide Apps.A+C

TLV Long-term value: 3* mg/m³
*inhalable fraction

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

- · Breathing equipment: Not necessary if room is well-ventilated.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

Printing Date 07/22/2021 Revision Number 3 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 2

(Contd. of page 3)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Safety glasses with side shields.
- · Body protection: Protective work clothing

9 Physical and chemical properties

· Information on	basic	physical	and	chemical	nronerties
THIOTHUMOU ON	vusic	DIIVSICUI	unu	Chemicui	DIODEIMES

- · General Information
- · Appearance:

Form: Liquid Color: Black

Odor: Minimal. Not distinctOdor threshold: Not determined.

• pH-value: Not determined.

· Change in condition

Melting point:Undetermined.Boiling point:Undetermined

• Flash point: 177 °C (350.6 °F)

Flammability (solid, gaseous): Not Applicable.
 Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

Auto igniting: Product is not selfigniting.
 Danger of explosion: Product does not present an explosion hazard.

· Vapor pressure: Not determined.

• Specific gravity at 20 °C (68 °F): 1.02 g/cm³ (8.5119 lbs/gal)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C (68 °F): 9400 CPS **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 0.0 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 5)

Printing Date 07/22/2021 Revision Number 3 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 2

(Contd. of page 4)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Exposure to high temperatures.
- · Incompatible materials: Reacts with oxidizing agents.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide tin oxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: May irritate the skin.
- · on the eye: May irritate the eye.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1333-86-4 Carbon black

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 6)

Printing Date 07/22/2021 Revision Number 3 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 2

(Contd. of page 5)

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number DOT, ADN, IMDG, IATA	not regulated
UN proper shipping name DOT, ADN, IMDG, IATA	not regulated
Transport hazard class(es)	
DOT, ADN, IMDG, IATA	
Class	not regulated
Packing group DOT, IMDG, IATA	not regulated
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
UN "Model Regulation":	not regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- ·Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

Please contact H.B. Fuller for more information regarding Proposition 65 on this product: reg.request@hbfuller.com.

(DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

1333-86-4 Carbon black

A4

(Contd. on page 7)

Printing Date 07/22/2021 Revision Number 3 Revision Date 07/22/2021

Trade name: Millennium Hurricane Force® Membrane Adhesive HS Part 2

(Contd. of page 6)

· MAK (German Maximum Workplace Concentration)

1333-86-4 Carbon black 3B

· NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 Carbon black

- · National regulations:
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- · Department issuing SDS: Global Regulatory Department.
- · Creation Date: 08/13/2015
- · Contact:
- · Date of preparation / last revision 07/22/2021 / 2
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OCIIA. Occupational Safety & Health

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

USA ·