



EternaBond® Foam Gasket Tape (FGT)

EternaBond™ FGT is a highly compressible PVC foam core encapsulated with high tack butyl adhesive/sealant. This flexible gasketing material conforms readily to corners and irregular contours.

It gives a secure seal that helps protect against water penetration and prevents corrosion and moisture damage.

Technology / Base	Butyl Coated Foam
Type of Product	Sealant/Gasket
Components	One component
Curing	No Cure
Appearance / Color	Black
Consistency	Rope

Features and Benefits

- Reliable primary seal that eliminates need for cap sealing
- Proven track record in Automotive gasketing for 30+ years
- High tack adhesive allows for single person install
- 100% Solids - Zero VOC
- High grade butyl will not cold or hot flow eliminating unsightly 'oozing'
- Allows for outstanding flexibility to irregular contoured surfaces
- Allows for thermal expansion of substrates thus eliminating moisture ingress

Basic Use

EternaBond® FGT is used as a sealant against moisture and dust elements for various applications including freezer seals, bus body and window, metal building, marine sealing, RV window & floor seals and modular windows.

Health & Safety

Prior to working with this, or any product, consult product label and Safety Data Sheet (SDS) for necessary health and safety precautions.

Storage and Shelf Life

Store material in original unopened container below 32°C (90°F). Shelf life is 1 year minimum when stored as recommended.

Technical Data		
Physical Properties	Typical Value	Test Method
Density, foam only	7.0 lbs/cu. Ft.	ASTM D-1667
Hardness: Shore 00	60	ASTM D-2240
* Water Penetration	Pass- No Leaks	AAMA 810.0
* Water Absorption % by volume	0.20%	NTP-35
Cold Flex @ 20 F	Pass- No Cracking	AAMA 810.0
Tensile Strength	80 PSI	NPT-7
Elongation	80%	NPT-7
Burn Rate- Flammability	1.00 in/min	FMVSS-302
* Tested at 30% compression		

Part Number	Stock Type	Dimensions
BC-1101	Rope	3/8" (10 mm) diameter x 35 LF per roll 20 rolls per case (20 lb. gross wt.) 45 CS/PLT
BC-1121	Rope	1/2" (12 mm) diameter x 27 LF per roll 17 rolls per case (19 lb. gross wt.) 45 CS/PLT
BC-1241	Flat	3/16"x1/2" (5x12 mm) diameter x 53 LF per roll 20 rolls per case (20 lb. gross wt.) 45 CS/PLT

Connecting what matters™

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience, and we believe this information to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

© and ™ are trademarks of H.B. Fuller Company or one of its affiliated entities.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

