



TECHNICAL SALES BULLETIN

SILAPRENE® DC 14079 HIGH STRENGTH CONTACT ADHESIVE

DC14079 is a high quality polychloroprene based contact adhesive designed for bonding a wide variety of rubber and plastic materials to themselves as well as to wood, metal, and fiberglass surfaces.

- Quick drying
- Quick grab
- High initial bond strength
- Fast development of ultimate strength
- Excellent heat resistance
- Excellent hot creep resistance
- Non-staining for light colored vinyl coated fabrics

SURFACE PREPARATION

Clean, dry, dust-free surfaces are required for optimum bond strength. Surface temperatures should be maintained at temperatures above 40° F.

APPLICATION METHODS

Suitable spray equipment is listed below. Others are available as well.

Binks HVLP BBR Mach I with .055 -.070 fluid tip Graco Delta with .055-.070 fluid tip Devilbiss JGMV530 with .055 - .070 fluid tip.

Always stir adhesive well prior to use. DC14079 is suitable for use with most any spray equipment, drying & lamination equipment. See your Royal Adhesive & Sealant representative for details on a specific system.

CLEAN-UP

Toluene is recommended for cleaning equipment and Acetone for over spray. Other solvents will provide varying degrees of cleaning capability.

TECHNICAL DATA

Physical Properties (Typical)
Base: Polychloroprene

Solids: 22%

Solvents: Acetone, Hexane, Toluene,

Color: Blue

Storage:

Viscosity: 300 cps (#2 @ 20rpm)

Approx. Weight: 6.7 lbs/gal

Cleaner: Toluene or Acetone

Store in closed container under

80°F.

Shelf Life: 6 months when stored below 80°F

in unopened containers.

PRECAUTIONARY DATA

Flammable. Keep from sparks and open flames. For Professional/Industrial use only.

- Read label and Material Safety Data Sheet carefully before use.
- Keep away from children.

DISPOSAL INFORMATION

Do not reuse container or remove label. Safely dispose of container and contents in accordance with law.

ROYAL EMERGENCY NUMBER

Chemtrec 800-424-9300

Royal Adhesives & Sealants, LLC an H.B. Fuller Company • 2001 W. Washington Street, South Bend, IN 46628 • Phone: 800-999-GLUE • Fax: 574-246-5425

^{*} Specification values available upon request