



# Weld Mount Stainless Steel Studs

Product Number	Description	Material	Dimensions	Tensile	Shear	Torque
<b>HS200-3816-12SS</b>	Heavy Load Studs	304 Stainless	0.75" tall x 2.00" diameter	1,200 Lbs.	1,500 Lbs.	-
<b>HS200-3816-16SS</b>	Heavy Load Studs	304 Stainless	1.00" tall x 2.00" diameter	1,200 Lbs.	1,500 Lbs.	-
<b>HS200-3816-246SS</b>	Heavy Load Studs	304 Stainless	1.50" tall x 2.00" diameter	1,200 Lbs.	1,500 Lbs.	-
<b>HS200-3816-32SS</b>	Heavy Load Studs	304 Stainless	2.00" tall x 2.00" diameter	1,200 Lbs.	1,500 Lbs.	-
<b>HS200-51618-24SS</b>	Heavy Load Studs	304 Stainless	1.50" tall x 2.00" diameter	1,200 Lbs.	1,500 Lbs.	-
<b>PS62-832-12SS</b>	Stud Thread (#8-32) *	304 Stainless	0.75" tall x 0.62" diameter	300 Lbs.	375 Lbs.	-
<b>PS62-832-16SS</b>	Stud Thread (#8-32)	304 Stainless	1.00" tall x 0.62" diameter	300 Lbs.	375 Lbs.	-
<b>PS62-832-20SS</b>	Stud Thread (#8-32)	304 Stainless	1.25" tall x 0.62" diameter	300 Lbs.	375 Lbs.	-
<b>PS62-832-24SS</b>	Stud Thread (#8-32)	304 Stainless	1.50" tall x 0.62" diameter	300 Lbs.	375 Lbs.	-
<b>PS62-832-8SS</b>	Stud Thread (#8-32)	304 Stainless	0.50" tall x 0.62" diameter	300 Lbs.	375 Lbs.	-
<b>ST125-1024-12SS</b>	Stud Thread (#10-24)	304 Stainless	0.75" tall	500 Lbs.	650 Lbs.	60 inch/Lbs.

<b>Product Number</b>	<b>Description</b>	<b>Material</b>	<b>Dimensions</b>	<b>Tensile</b>	<b>Shear</b>	<b>Torque</b>
<b>ST125-1024-16SS</b>	Stud Thread (#10-24)	304 Stainless	1.00" tall	500 Lbs.	650 Lbs.	60 inch/Lbs.
<b>ST125-1024-20SS</b>	Stud Thread (#10-24)	304 Stainless	1.25" tall	500 Lbs.	650 Lbs.	60 inch/Lbs.
<b>ST125-1024-24SS</b>	Stud Thread (#10-24)	304 Stainless	1.50" tall	500 Lbs.	650 Lbs.	60 inch/Lbs.
<b>ST125-1024-28SS</b>	Stud Thread (#10-24)	304 Stainless	1.75" tall	500 Lbs.	650 Lbs.	60 inch/Lbs.
<b>ST125-1024-32SS</b>	Stud Thread (#10-24)	304 Stainless	2.00" tall	500 Lbs.	650 Lbs.	60 inch/Lbs.
<b>ST125-1024-36SS</b>	Stud Thread (#10-24)	304 Stainless	2.25" tall	500 Lbs.	650 Lbs.	60 inch/Lbs.
<b>ST125-1024-40SS</b>	Stud Thread (#10-24)	304 Stainless	2.50" tall	500 Lbs.	650 Lbs.	60 inch/Lbs.
<b>ST125-1024-8SS</b>	Stud Thread (#10-24)	304 Stainless	0.50" tall	500 Lbs.	650 Lbs.	60 inch/Lbs.
<b>ST125-1420-12SS</b>	Stud Thread (1/4-20)	304 Stainless	0.75" tall	500 Lbs.	650Lbs.	90 inch/Lbs.

Product Number	Description	Material	Dimensions	Tensile	Shear	Torque
<b>ST125-1420-16SS</b>	Stud Thread (1/4-20)	304 Stainless	1.00" tall	500 Lbs.	650 Lbs.	90 inch/Lbs.
<b>ST125-1420-20SS</b>	Stud Thread (1/4-20)	304 Stainless	1.25" tall	500 Lbs.	650 Lbs.	90 inch/Lbs.
<b>ST125-1420-24SS</b>	Stud Thread (1/4-20)	304 Stainless	1.50" tall	500 Lbs.	650 Lbs.	90 inch/Lbs.
<b>ST125-1420-28SS</b>	Stud Thread (1/4-20)	304 Stainless	1.75" tall	500 Lbs.	650 Lbs.	90 inch/Lbs.
<b>ST125-1420-32SS</b>	Stud Thread (1/4-20)	304 Stainless	2.00" tall	500 Lbs.	650 Lbs.	90 inch/Lbs.
<b>ST125-1420-40SS</b>	Stud Thread (1/4-20)	304 Stainless	2.50" tall	500 Lbs.	650 Lbs.	90 inch/Lbs.

**For more information about our company, visit [www.hbfuller.com](http://www.hbfuller.com).**

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is user's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. The user is advised to review the specific context of the intended use to determine whether the user's intended use violates any law or infringes upon any patent(s). No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.