

# Weld Mount Adhesives

Product	Chemistry	Substrates	Benefits & Features	Cure Profile	Dispense Gun	Static Mix Tip
<b>AT-2010</b>	Acrylic	Fiberglass	Ideal for a fast-paced work environment	Room Temp Cure Set Time: 6 mins Working Strength: 18 mins Full cure: 24 hours	AT-300	AT-850 3.25" Mix Tip
<b>AT-6030</b>	Acrylic	Metal Carbon	Best for Metal Bonding 10:1 cartridge	Room Temp Cure Set Time: 15 mins Working Strength: 45 mins Full cure: 24 hours	AT-301	AT-650 3.5" Mix Tip
<b>AT-8040</b>	Acrylic	Almost all substrates (except low energy & rubber)	Non-slide General Purpose Bonder 30 ml cartridge. Seal cap included	Room Temp Cure Set Time: 12 mins Working Strength: 40 mins Full cure: 24 hours	AT-300	AT-850 3.25" Mix Tip
<b>AT-804030</b>	Acrylic	Almost all substrates (except low energy & rubber)	Non-slide General Purpose Bonder 30 ml cartridge. Seal cap included	Room Temp Cure Set Time: 12 mins Working Strength: 40 mins Full cure: 24 hours	Built In	Built In
<b>AT-880</b>	Acrylic	Polypropylene, HDPE, LDPE, PPE, UHMW, ABS Polycarbonate, Aluminum	10:1 Cartridge Minimal surface preparation	Room Temp Cure Open Time: 3 mins Full cure: 24 hours	AT-388	AT-858 3.25" Mix Tip



**AT-2010**



**AT-6030**



**AT-8040**

For more information about our company, visit [www.hbfuller.com](http://www.hbfuller.com).

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is user's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. The user is advised to review the specific context of the intended use to determine whether the user's intended use violates any law or infringes upon any patent(s). No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.