

Linear Low Density Polyethylene SLL118/21

Description:

SLL118/21 is a LLDPE Butene copolymer produced by Braskem. It was specially designed to provide outstanding processing performance. Films obtained with this grade show good physical and optical properties and enhanced sealability. The minimum biobased carbon content of this grade is 87%, determined according to ASTM D6866.

Aditivação:

Slip, Antiblock.

Aplicações:

Blends with HDPE, Blends with LDPE, Technical films for automatic packaging, Technical films, Liners

Processos:

Blown Film Extrusion

Control Properties:

Característica	Método	Unidades	Valores
Melt Flow Rate (190°C/2.16kg)	D 1238	g/10 min	1.0
Density	D 792	g/cm ³	0.918

Typical Properties - Films:

Blown Film Properties^a

Característica	Método	Unidades	Valores
Tensile Strength at Break (MD/TD)	D 882	MPa	40/30
Elongation at Break (MD/TD)	D 882	%	1070/1340
Tensile Modulus - 1% Secant (MD/TD)	D 882	MPa	210/230
Dart Drop Impact	D 1709	g/F50	130
Elmendorf Tear Strength (MD/TD)	D 1922	gF	180/400

(a) Film with 38 microns produce in a 40mm extruder and a blow-up ratio of 2.2:1. (MD = extrusion direction and TD = transversal direction).

Final Remarks:

1. The information presented in this Data Sheet reflects typical values obtained in our laboratories, but should not be considered as absolute or as warranted values. Only the properties and values mentioned on the Certificate of Quality are considered as guarantee of the product.
2. For regulatory information of the product, please refer to Regulatory Document or contact our Technical Assistance Area.
3. For information about safety, handling, individual protection, first aids and waste disposal, please refer to MSDS.
4. The mentioned values in this report can be changed at any moment without Braskem previous communication.