

## Ethylene-Vinyl Acetate Copolymer SVT2180

### Description:

SVT2180 is a copolymer of renewable ethylene with Vinyl Acetate (EVA) mainly used for the production of crosslinked foam sheets and other parts. It is a product with easy processability and high compatibility with mineral fillers, and thermoplastic and elastomeric resins. Other important characteristics are elasticity, flexibility, excellent stress cracking resistance (ESCR), chemical resistance, and low temperature strength. The exclusive morphologic characteristics give an outstanding crosslinkability. The components produced with SVT2180 have the following properties: low weight, resistance to deformation, low shrink, high capacity of sticking and color retention.

The minimum biobased carbon content of this grade is 80%, determined according to ASTM D6866.

### Additives:

Antioxidant

### Control Properties:

Characteristic	Method	Units	Values
Melt Flow Rate (190°C/2.16kg)	ASTM D 1238	g/10 min	2.1
Vinyl-Acetate Content	ASTM-D-5594-98	%	19

### Typical Properties - EVA:

Plaque Properties (a)

Characteristic	Method	Units	Values
Density	D 1505 / D 792	g/cm <sup>3</sup>	0.940
Tensile Strength at Break	D 638	MPa	19
Elongation at Break	D 638	%	750
5% Secant Modulus	D 638	MPa	33
Hardness	D 2240	Shore A / D	89/38
Melting Point	D 3418	°C	86
Vicat Softening Temperature at 10 N	D 1525	°C	61

(1) Braskem test method available for customers. (a) Test specimens prepared from compression molded plate according to ASTM D 4703. (b) Compression molded 2 mm thickness, 0.3 mm notched-plaques; 100% Igepal; 50°C.