

Hexano Circular

Description:

COMMERCIAL NAME

Hexano Circular

SYNONYMS

Recycled Hexane

ASPECT

Colorless liquid

PROPERTIES AND CHARACTERISTICS

- Aliphatic hydrocarbon solvent composed of a mixture of paraffinic hydrocarbons;
- Light solvent with an evaporation rate of 620 (n-butyl acetate=100).

APPLICATIONS

- Rubber
- Adhesives

Applications:

Adhesives, Rubber

Specification:

Feature	Method	Units	Values
Benzene	ASTM D5134	% mass	0,1 max.
Color (Pt/Co)	ASTM D5386	-	10 max.
Relative Density (20/4°C)	ASTM D4052	-	0,655 - 0,675
Initial Boiling Point (IBP)	ASTM D1078	°C	58 min.
Final Boiling Point (FBP)	ASTM D1078	°C	150 max.

Final Remarks:

1. The properties and values contained in the quality certificate must be considered as a guarantee of the product. For typical values, when provided, the information is given in good faith and obtained in our laboratories, and should not be considered as absolute or as a guarantee.
2. For any doubt concerning material handling or application, please contact the Technical Services area.
3. For safety, handling, personal protection, first aid, and waste disposal information, refer to the MSDS - Material Safety Data Sheet.
4. The mentioned values in this report can be changed at any moment without Braskem previous communication.
5. Shelf Life: Two years from the date of issuance of the quality certificate, provided that the storage conditions informed in the MSDS (Material Safety Data Sheet) are maintained.