

Ezolem 6/13

Description:

COMMERCIAL NAME

Ezolem™ 6/13

SYNONYMS

Coperaf, solvent for rubber, aliphatic solvent

ASPECT

Colorless liquid

PROPERTIES AND CHARACTERISTICS

- Aliphatic hydrocarbon solvent composed by a mixture of paraffinic and naphthenic hydrocarbons;
- Low concentration of olefin and sulphonated compounds.

Applications:

Adhesives, Rubber, Thinners, Industrial cleaning

Specification:

Feature	Method	Units	Values
Total Aromatics	ASTM 6563	% mass	0,8 max.
Benzene	ASTM 6563	ppm volume	500 max.
Color (Pt/Co)	ASTM 5386	-	30 max.
Relative Density (20/4°C)	ASTM D4052	-	0,67 - 0,70
Initial Boiling Point (IBP)	ASTM D86	°C	60 - 80
Final Boiling Point (FBP)	ASTM D86	°C	105 - 135
Total Sulfur	ASTM 4952	-	Negative

Final Remarks:

1. The properties and values contained in the quality certificate must be considered as a guarantee of the product. For typical values, when provided, the information is given in good faith and obtained in our laboratories, and should not be considered as absolute or as a guarantee.
2. For any doubt concerning material handling or application, please contact the Technical Services area.
3. For safety, handling, personal protection, first aid, and waste disposal information, refer to the MSDS - Material Safety Data Sheet.
4. The mentioned values in this report can be changed at any moment without Braskem previous communication.
5. Shelf Life: Two years from the date of issuance of the quality certificate, provided that the storage conditions informed in the MSDS (Material Safety Data Sheet) are maintained.