

Ezolem 6/15

Description:

COMMERCIAL NAME

Ezolem™ 6/15

SYNONYMS

PGH *Raffinate*, aliphatic solvent

ASPECT

Light yellow liquid

PROPERTIES AND CHARACTERISTICS

- Aliphatic hydrocarbon solvent composed by a mixture of paraffinic and naphthenic hydrocarbons;
- Low concentration of Olefin and Sulphonated compounds.

Applications:

Adhesives, Rubber, Thinners, Industrial cleaning

Specification:

Feature	Method	Units	Values
C9 Aromatic	ASTM 6563	% mass	Anotate
Benzene	ASTM D6563	% volume	0,1 max.
Color (Pt/Co)	ASTM D5386	-	30 max.
Relative Density (20/4°C)	ASTM D4052	-	Anotate
Initial Boiling Point (IBP)	ASTM D86	°C	50 min.
Final Boiling Point (FBP)	ASTM D86	°C	200 max.
Total Sulfur	ASTM D5453 / ASTM D6667	% mass	0.1

Final Remarks:

- The properties and values contained in the quality certificate must be considered as a guarantee of the product. For typical values, when provided, the information is given in good faith and obtained in our laboratories, and should not be considered as absolute or as a guarantee.
- For any doubt concerning material handling or application, please contact the Technical Services area.
- For safety, handling, personal protection, first aid, and waste disposal information, refer to the MSDS - Material Safety Data Sheet.
- The mentioned values in this report can be changed at any moment without Braskem previous communication.
- Shelf Life: Two years from the date of issuance of the quality certificate, provided that the storage conditions informed in the MSDS (Material Safety Data Sheet) are maintained.