

## Ezolem 6/17

### Description:

#### COMMERCIAL NAME

Ezolem™ 6/17

#### SYNONYMS

Raffinate C6-C8, aliphatic solvent

#### ASPECT

Colorless liquid

### PROPERTIES AND CHARACTERISTICS

- Aliphatic hydrocarbon solvent composed by a mixture of paraffinic and naphthenic hydrocarbons;
- Low concentration of olefin and sulphonated compounds.

### Applications:

Adhesives, Rubber, Thinners, Industrial cleaning

### Specification:

Feature	Method	Units	Values
Water	ASTM D4017	ppm mass	300 max.
Benzene	ASTM D5580	ppm mass	1000 max.
C6+ Aromatic	ASTM D5580	% mass	1,5 max.
Color (Pt/Co)	ASTM D5386	-	20 max.
Copper Strip Corrosion	ASTM D130	-	1A/1B
Relative Density (20/4°C)	ASTM D4052	-	0,700 - 0,740
Initial Boiling Point (IBP)	ASTM D86	°C	60 min.
Final Boiling Point (FBP)	ASTM D86	°C	170 max.
Bromine Number	ASTM D1159	gBr/100g	4 max.
Sulfolane	ASTM D5623	ppm mass	50 max.

### Final Remarks:

1. The properties and values contained in the quality certificate must be considered as a guarantee of the product. For typical values, when provided, the information is given in good faith and obtained in our laboratories, and should not be considered as absolute or as a guarantee.
2. For any doubt concerning material handling or application, please contact the Technical Services area.
3. For safety, handling, personal protection, first aid, and waste disposal information, refer to the MSDS - Material Safety Data Sheet.
4. The mentioned values in this report can be changed at any moment without Braskem previous communication.
5. Shelf Life: Two years from the date of issuance of the quality certificate, provided that the storage conditions informed in the MSDS (Material Safety Data Sheet) are maintained.