

Sensitis 22/25

Description:

COMMERCIAL NAME

Sensitis™ 22/25

SYNONYMS

Isoparaffin, hydrogenated solvente

ASPECT

Colorless liquid

PROPERTIES AND CHARACTERISTICS

- Hydrocarbon solvent composed by a mixture of isoparaffinic hydrocarbons;
- Low concentration of aromatic compounds.

Applications:

Degrease, Cutting Fluids, Industrial cleaning, Lubricants, Personal care

Specification:

Feature	Method	Units	Values
Water	ASTM E203	ppm mass	200 max.
Appearance	ASTM D4176		Clear and clean
Total Aromatics	ASTM D1840	ppm mass	80 max.
Color (Pt/Co)	ASTM D5386	-	5 max.
Relative Density (20/4°C)	ASTM D4052	-	0,778 - 0,788
Initial Boiling Point (IBP)	ASTM D86	°C	218 min.
Final Boiling Point (FBP)	ASTM D86	°C	259 max.
Flash Point	ASTM D93	°C	90 min.
Ultraviolet Absorption (260-319 / 320-329 / 330-350)	ASTM D2269	-	1,5 max. / 0,08 max. / 0,05 max.
Kinematic Viscosity at 37,8°C	ASTM D445	cSt	2,3 - 3,4
Bromine Index	ASTM D2710	mg/100g	70 max.

Final Remarks:

1. The properties and values contained in the quality certificate must be considered as a guarantee of the product. For typical values, when provided, the information is given in good faith and obtained in our laboratories, and should not be considered as absolute or as a guarantee.
2. For any doubt concerning material handling or application, please contact the Technical Services area.
3. For safety, handling, personal protection, first aid, and waste disposal information, refer to the MSDS - Material Safety Data Sheet.
4. The mentioned values in this report can be changed at any moment without Braskem previous communication.
5. Shelf Life: Two years from the date of issuance of the quality certificate, provided that the storage conditions informed in the MSDS (Material Safety Data Sheet) are maintained.