

**CILBOND 4000 Diluent** is used for diluting Cilbond 40 series products. It consists of a blend of solvents.

### BENEFITS OF CILBOND 4000 Diluent

- Ready to use solvent blend reduces inventory.
- Formulated to improve spray application of Cilbond 40 series products.
- Helps reduce or eliminate cobwebbing and dry spray.
- It can also be used with **Cilbond 36**.

### APPLICATION:

- Consult individual Cilbond 40 series technical data sheets for dilution ratios.
- Slowly add **Cilbond 4000 Diluent** to the Cilbond 40 series product whilst stirring. This will prevent any destabilisation, gelling or shocking of the blend.
- Ensure the diluted Cilbond is fully homogenous during use.

### TYPICAL PHYSICAL PROPERTIES OF CILBOND 4000 Diluent

Appearance	Clear
Non-Volatile Solids	0%
Specific Gravity @ 26°C (79°F)	0.82
Flash Point (Abel Pensky)	-6°C (21°F)
Solvent Type	Methyl Ethyl Ketone (MEK), Acetate, Ester
Shelf Life	24 months from date of manufacture

### PACKAGING

**Cilbond 4000 Diluent** is supplied in 25L and 200L containers.

### FURTHER INFORMATION

For more information on **Cilbond 4000 Diluent** or for details of our other products please visit [www.cilbond.com](http://www.cilbond.com) or e-mail [sales@cilbond.com](mailto:sales@cilbond.com)