

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

**SECTION 1. IDENTIFICATION**

Product name : ANTI-TERRA-P

**Manufacturer or supplier's details**

Company : BYK USA Inc.  
524 South Cherry Street  
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : [www.byk.com](http://www.byk.com)

E-mail address : [BRIEF.BYK.NAFTA@altana.com](mailto:BRIEF.BYK.NAFTA@altana.com)

Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1  
number 703-527-3887

**Recommended use of the chemical and restrictions on use**

Recommended use : Wetting &amp; Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3

**Acute toxicity (Oral) : Category 4**

Acute toxicity (Dermal) : Category 4

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3 (Respiratory system, Central nervous system)  
- single exposureSpecific target organ toxicity : Category 2 (Kidney, Liver)  
- repeated exposure**GHS label elements**

## ANTI-TERRA-P

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

Hazard pictograms :



Signal word :

**Danger**

Hazard statements :

H226 Flammable liquid and vapour.  
 H302 + H312 Harmful if swallowed or in contact with skin.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.  
 H361 Suspected of damaging fertility or the unborn child.  
 H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure.

Precautionary statements :

**Prevention:**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.  
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

P308 + P313 IF exposed or concerned: Get medical advice/attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture  
Chemical nature : Solution of a phosphoric acid salt of long chain carboxylic acid polyamine amides

**Hazardous components**

| Component             | CAS-No.    | Concentration (%)  |
|-----------------------|------------|--------------------|
| Phosphated alkylamine | 85099-25-8 | $\geq 32$ - $< 33$ |
| Isobutanol            | 78-83-1    | $\geq 25$ - $< 26$ |
| Polyamide phosphate   | -          | $\geq 19$ - $< 20$ |
| Xylene                | 1330-20-7  | $\geq 6$ - $< 7$   |
| Ethyl benzene         | 100-41-4   | $\geq 2$ - $< 3$   |

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

|   |   |
|---|---|
|   | If unconscious, place in recovery position and seek medical advice.   |
| In case of skin contact                                     | : If skin irritation persists, call a physician.<br>If on skin, rinse well with water.<br>If on clothes, remove clothes.  |
| In case of eye contact                                      | : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.<br>In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.<br>Continue rinsing eyes during transport to hospital.<br>Remove contact lenses.<br>Protect unharmed eye.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist. |
|   | Small amounts splashed into eyes can cause irreversible tissue damage and blindness.<br>In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.<br>Continue rinsing eyes during transport to hospital.<br>Remove contact lenses.<br>Protect unharmed eye.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist.   |
| If swallowed  | : Keep respiratory tract clear.<br>Do NOT induce vomiting.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician.<br>Take victim immediately to hospital.  |
| Most important symptoms and effects, both acute and delayed | : No information available.   |

**SECTION 5. FIREFIGHTING MEASURES**

|                                      |   |
|--------------------------------------|---|
| Suitable extinguishing media         | : Alcohol-resistant foam<br>Carbon dioxide (CO2)<br>Dry chemical            |
| Unsuitable extinguishing media       | : High volume water jet   |
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

## ANTI-TERRA-P

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

Conditions for safe storage : No smoking.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Keep away from oxidizing agents.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

| Components    | CAS-No.   | Value type<br>(Form of exposure) | Control parameters /<br>Permissible concentration | Basis    |
|---------------|-----------|----------------------------------|---|----------|
| Isobutanol    | 78-83-1   | TWA                              | 50 ppm  | ACGIH    |
| Isobutanol    |           | TWA                              | 100 ppm<br>300 mg/m <sup>3</sup>                  | OSHA Z-1 |
| Xylene        | 1330-20-7 | TWA                              | 100 ppm<br>435 mg/m <sup>3</sup>                  | OSHA Z-1 |
| Xylene        |           | STEL                             | 150 ppm<br>655 mg/m <sup>3</sup>                  | OSHA P0  |
| Xylene        |           | TWA                              | 100 ppm<br>435 mg/m <sup>3</sup>                  | OSHA P0  |
| Xylene        |           | TWA                              | 100 ppm   | ACGIH    |
| Xylene        |           | STEL                             | 150 ppm   | ACGIH    |
| Ethyl benzene | 100-41-4  | TWA                              | 20 ppm  | ACGIH    |
| Ethyl benzene |           | TWA                              | 100 ppm<br>435 mg/m <sup>3</sup>                  | OSHA Z-1 |
| Ethyl benzene |           | TWA                              | 100 ppm<br>435 mg/m <sup>3</sup>                  | OSHA P0  |
| Ethyl benzene |           | STEL                             | 125 ppm<br>545 mg/m <sup>3</sup>                  | OSHA P0  |

Hazardous components without workplace control parameters

**Engineering measures** : Use with local exhaust ventilation.

#### Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Material : Nitrile rubber

Remarks : Wear suitable gloves.  
 The suitability for a specific workplace should be discussed

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

|                          |   |
|--------------------------|---|
|                          | with the producers of the protective gloves.  |
| Eye protection           | : Eye wash bottle with pure water<br>Tightly fitting safety goggles<br>Wear face-shield and protective suit for abnormal processing problems. |
| Skin and body protection | : Impervious clothing<br>Choose body protection according to the amount and concentration of the dangerous substance at the work place.       |
| Hygiene measures         | : When using do not eat or drink.<br>When using do not smoke.<br>Wash hands before breaks and at the end of workday.                          |

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

|                           |  |
|---------------------------|--|
| Appearance                | : liquid   |
| Colour                    | : yellow   |
| Odour                     | : aromatic   |
| Odour Threshold           | : No data available  |
| pH                        | : 6, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-value indicator |
| Melting point/range       | : < 32 °F (< 0 °C)<br>Method: derived  |
| Initial boiling point     | : 212.00 °F (100.00 °C)<br>Method: derived                                   |
| Vapour pressure           | : 17 hPa (68.00 °F (20.00 °C))<br>Method: derived                            |
| Flash point               | : 78.80 °F (26.00 °C)<br>Method: 48 (Abel-Pensky)                            |
| Upper explosion limit     | : 10.70 %(V)   |
| Lower explosion limit     | : 1.20 %(V)  |
| Evaporation rate          | : No data available  |
| Flammability (solid, gas) | : No data available  |

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

|  |   |
|--|---|
| Relative vapour density                | : No data available   |
| Relative Density/Specific Gravity      | : No data available   |
| Density                                | : 0.9900 g/cm <sup>3</sup> (68.00 °F (20.00 °C))<br>Method: 4 (20°C oscillating U-tube) |
| Bulk density                           | : Not applicable  |
| Solubility(ies)<br>Water solubility    | : immiscible  |
| Solubility in other solvents           | : No data available   |
| Partition coefficient: n-octanol/water | : No data available   |
| Ignition temperature                   | : > 392 °F (> 200 °C)<br>Method: DIN 51794  |
| Thermal decomposition                  | : No data available   |
| Viscosity<br>Viscosity, dynamic        | : No data available   |
| Viscosity, kinematic                   | : No data available   |
| Surface tension                        | : No data available   |

**SECTION 10. STABILITY AND REACTIVITY**

|                                    |   |
|------------------------------------|---|
| Reactivity                         | : No decomposition if stored and applied as directed. |
| Chemical stability                 | : No decomposition if stored and applied as directed. |
| Possibility of hazardous reactions | : No decomposition if stored and applied as directed. |
|                                    | Vapours may form explosive mixture with air.          |
| Conditions to avoid                | : Heat, flames and sparks.                            |
| Incompatible materials             | : Strong oxidizing agents                             |
| Hazardous decomposition products   | : No data available                                   |



**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Skin contact  
Skin Absorption  
Inhalation  
Eyes  
Ingestion

**Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : 1,175 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 121.65 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 1,005 mg/kg  
Method: Calculation method

**Components:****85099-25-8 Phosphated alkylamine:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute dermal toxicity : LD50 (Rat): 380 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

**78-83-1 Isobutanol:**

Acute oral toxicity : LD50 (Rat): 2,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 8000 ppm  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 2,460 mg/kg

**- Polyamide phosphate:**

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg  
Method: OECD Test Guideline 423  
GLP: yes

**1330-20-7 Xylene:**

Acute oral toxicity : LD50 (Rat): 4,300 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)  
GLP: no

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

Acute inhalation toxicity : LC50 (Rat): 5000 ppm  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg  
LD50 (Rabbit): > 4,200 mg/kg  
GLP: No information available.

**100-41-4 Ethyl benzene:**

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg

**Skin corrosion/irritation****Product:**

Species: Rabbit

Assessment: Irritating to skin.

Method: OECD Test Guideline 404

Result: Skin irritation

Remarks: Extremely corrosive and destructive to tissue.

**Components:****85099-25-8 Phosphated alkylamine:**

Species: EPISKIN human epidermis skin constructs

Method: OECD Test Guideline 439

Result: No skin irritation

GLP: yes

**78-83-1 Isobutanol:**

Species: Rabbit

Result: Moderate skin irritation

**1330-20-7 Xylene:**

Species: Rabbit

Result: Moderate skin irritation

**100-41-4 Ethyl benzene:**

Species: Rabbit

Result: Moderate skin irritation

**Serious eye damage/eye irritation****Product:**

Species: Rabbit

Result: Risk of serious damage to eyes.

Assessment: Risk of serious damage to eyes.

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

Method: OECD Test Guideline 405

Remarks: May cause irreversible eye damage.

**Components:****85099-25-8 Phosphated alkylamine:**

Species: Bovine corneal opacity and permeability assay (BCOP)

Result: No eye irritation

Method: OECD Test Guideline 437

GLP: yes

**78-83-1 Isobutanol:**

Species: Rabbit

Result: Eye irritation

Method: OECD Test Guideline 405

GLP: yes

**- Polyamide phosphate:**

Species: Chicken eye

Result: Eye irritation

Assessment: Irritating to eyes.

Method: OECD Test Guideline 438

GLP: yes

**1330-20-7 Xylene:**

Species: Rabbit

Result: Eye irritation

**100-41-4 Ethyl benzene:**

Species: Rabbit

Result: Moderate eye irritation

**Respiratory or skin sensitisation****Product:**

Remarks: Causes sensitisation.

**Components:****78-83-1 Isobutanol:**

Test Type: Maximisation Test

Exposure routes: Dermal

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

**- Polyamide phosphate:**

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

Assessment: The product is a skin sensitizer, sub-category 1A.

Method: OECD Test Guideline 429

Result: Causes sensitisation.

GLP: yes

**Germ cell mutagenicity****Components:****- Polyamide phosphate:**

Genotoxicity in vitro

: Test Type: Ames test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes

**Carcinogenicity****IARC**

Group 2B: Possibly carcinogenic to humans

Ethyl benzene

100-41-4

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Repeated dose toxicity****Product:**

Remarks: Absorption of ingredients (solvents) by inhalation and/or repeated skin contact has caused injury to liver, kidney, brain, respiratory system, blood, and/or bone marrow in laboratory animals

Animal studies have shown Xylene to cause fetotoxic effects at dosage levels at or near maternal toxicity levels.

Excessive inhalation of Xylene has caused hearing loss in laboratory animals. Hexane used in conjunction w/Xylene greatly increased this effect. Chronic skin contact w/Xylene has caused dermatitis. Ingestion of Ethanol can increase effects of overexposure to Xylene.

Isobutanol has shown positive results in an in vitro test for potential mutagenicity.

Ethylbenzene is an IARC Group 2B carcinogen based on animal studies (increased tumors in rats and mice).

**Aspiration toxicity****Components:****78-83-1 Isobutanol:**

No aspiration toxicity classification

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

**Experience with human exposure****Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

Symptoms:

Contact will probably cause irritation; may cause skin sensitization.

Eye contact:

Symptoms:

Contact will probably cause severe irritation and corrosion.

Ingestion:

Symptoms:

May irritate the digestive tract and cause same symptoms as inhalation; high dosages may result in unconsciousness.

**Further information****Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

Toxicity to fish

:

Remarks: No data available

**Persistence and degradability****Product:**

Biodegradability

:

Remarks: No data available

**Bioaccumulative potential****Product:**

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

Bioaccumulation : Remarks: No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

EPA Hazardous Waste Code(s) : D001: Ignitable  
D018: Benzene

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(Isobutanol, Xylene)  
Class : 3

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Isobutanol, XYLENE)  
: )  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no  
Remarks : IMDG Code segregation group - none

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

UN/ID/NA number : UN 1993  
Proper shipping name : Flammable liquids, n.o.s.  
(Xylene, Isobutanol)  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID  
ERG Code : 128  
Marine pollutant : no  
Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

| Components | CAS-No.   | Component RQ<br>(lbs) | Calculated product RQ<br>(lbs) |
|------------|-----------|-----------------------|--------------------------------|
| Xylene     | 1330-20-7 | 100                   | 1559                           |

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

|               |           |       |
|---------------|-----------|-------|
| Xylene        | 1330-20-7 | 6.4 % |
| Ethyl benzene | 100-41-4  | 2.6 % |

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

|               |           |       |
|---------------|-----------|-------|
| Xylene        | 1330-20-7 | 6.4 % |
| Ethyl benzene | 100-41-4  | 2.6 % |

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

|               |           |        |
|---------------|-----------|--------|
| Isobutanol    | 78-83-1   | 25.7 % |
| Xylene        | 1330-20-7 | 6.4 %  |
| Ethyl benzene | 100-41-4  | 2.6 %  |

**Non-volatile (Wt)** : 39 - 44 %  
Method: 22 (10min/150°C)  
DIN EN ISO 3251  
Non-volatile information is not a specification.

**Massachusetts Right To Know**

|               |           |
|---------------|-----------|
| Isobutanol    | 78-83-1   |
| Xylene        | 1330-20-7 |
| Ethyl benzene | 100-41-4  |



**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

Benzene

71-43-2

**Pennsylvania Right To Know**

Phosphated alkylamine

85099-25-8

Isobutanol

78-83-1

Polyamide phosphate

-

Water

7732-18-5

Xylene

1330-20-7

Ethyl benzene

100-41-4

Cumene

98-82-8

Toluene

108-88-3

**New Jersey Right To Know**

Phosphated alkylamine

85099-25-8

Isobutanol

78-83-1

Polyamide phosphate

-

Water

7732-18-5

Xylene


1330-20-7

Ethyl benzene

100-41-4

**New Jersey Trade Secret** : 800963-5010  
**Registry Number for the**  
**product (NJ TSNR)**

**California Prop. 65**

 **WARNING:** This product can expose you to chemicals including Ethyl benzene, Cumene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**CONEG Heavy Metal:** We confirm that we use packaging and/or packaging components in which the sum of the incidental concentration levels of lead, mercury, cadmium and hexavalent chromium do not exceed 100 parts per million by weight.

**The components of this product are reported in the following inventories:**

**TSCA** : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

**Section 4 / 12(b)** : Not applicable

**Section 5** : Not applicable

**TSCA Inventory Active List** : All components of this product are listed active and/or are exempt

**DSL** : We certify that all of the components of this product are listed on the DSL.

**ANTI-TERRA-P**

Version 10

Revision Date 07/08/2020

Print Date 09/29/2022

**SECTION 16. OTHER INFORMATION**

Revision Date : 07/08/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.