

BYK-035

VOC-free defoamer on the basis of mineral oil for aqueous emulsion paints and high gloss emulsion systems. Contains silicone.

Product Data

Composition

Mixture of paraffinic mineral oils and hydrophobic components. Contains silicone.

VOC-free (< 1500 ppm). Does not contain alkyl phenol ethoxylates

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 °C): 0.88 g/ml VOC content: < 1500 ppm

Does not contain alkyl phenol ethoxylates

Food Contact Legal Status

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

Storage and Transportation

Separation possible. Mix well before use.

Applications

Coatings Industry

Special Features and Benefits

The defoamer is particularly recommended for emulsion systems with a PVC range between 20 and 40. High shear forces do not negatively impact its effectiveness.

Recommended Use

Particularly recommended for high gloss emulsion systems as well as gloss and semi-gloss emulsion paints. Also suitable for emulsion paints / exterior wall paints with higher PVC as well as emulsion plasters.

Recommended Levels

0.1-0.5% additive (as supplied) based upon total formulation. In exceptional cases up to 0.8%. The dosage levels are indicated for the purpose of orientation. Optimal dosage levels are determined through series of tests.

Incorporation and Processing Instructions

Generally, 2/3 of the defoamer are added to the millbase and 1/3 is added to the letdown or the finished paint. Sufficient shear forces are necessary for incorporation in order to avoid negative side effects.

BYK-035

Data Sheet Issue 07/2012

Germany Tel +49 281 670-0 Fax +49 281 65735

info@byk.com www.byk.com/additives