

# **BYK-054 T**

Version 1 Revision Date 06/20/2023 Print Date 06/29/2023

## **SECTION 1. IDENTIFICATION**

Product name : BYK-054 T

Manufacturer or supplier's details

Company : BYK USA Inc.

524 South Cherry Street Wallingford CT 06492

Telephone : (203) 265-2086 Visit our web site : www.byk.com

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1

number 703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Defoamer

Restrictions on use : Refer to Section 15 for any restrictions that may apply

## **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids : Category 3

Eye irritation : Category 2B

Aspiration hazard : Category 1

**GHS** label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H320 Causes eye irritation.

Precautionary statements : **Prevention:** 

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting

equipment.



# **BYK-054 T**

Version 1 Revision Date 06/20/2023 Print Date 06/29/2023

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P331 Do NOT induce vomiting.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : solution of polyolefin

**Hazardous components** 

Component	CAS-No.	Concentration (%)
Naphtha, petroleum, heavy alkylate	64741-65-7	>= 60 -< 80

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.



**BYK-054 T** 

Version 1 Revision Date 06/20/2023 Print Date 06/29/2023

If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

> Remove contact lenses. Protect unharmed eye.

Keep eve wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Cool closed containers exposed to fire with water spray.

Will not explode on mechanical impact.

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon oxides

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

for firefighters

Special protective equipment : Wear self-contained breathing apparatus for firefighting if

necessary.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**



# **BYK-054 T**

Version 1 Revision Date 06/20/2023 Print Date 06/29/2023

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Contains no substances with occupational exposure limit values. Hazardous components without workplace control parameters

## Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed



**BYK-054 T** 

Version 1 Revision Date 06/20/2023 Print Date 06/29/2023

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : clear, colourless

Odour : not significant

Odour Threshold : No data available

pH : 7, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-

value indicator

Melting point/range :  $< 59 \,^{\circ}\text{F} \, (< 15 \,^{\circ}\text{C})$ 

Method: derived

Initial boiling point : 311 - 347 °F (155 - 175 °C)

Method: derived

Vapour pressure : 3.0 hPa (68 °F (20 °C))

Method: derived

Flash point :  $106 \, ^{\circ}\text{F} \, (41 \, ^{\circ}\text{C})$ 

Method: 48 (Abel-Pensky) DIN 51755

Upper explosion limit : 7.00 %(V)

Lower explosion limit : 0.60 %(V)

Evaporation rate : No data available

Relative vapour density : No data available

Density : 0.77 g/cm3 (68 °F (20 °C))

Method: 4 (20°C oscillating U-tube)



# **BYK-054 T**

Version 1 Revision Date 06/20/2023 Print Date 06/29/2023

Solubility(ies)

Water solubility : immiscible

Partition coefficient: n-

octanol/water

: No data available

Ignition temperature : > 392 °F (> 200 °C)

Method: DIN 51794

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : 5 mPa.s (68 °F (20 °C))

Method: P/K 20°C

Viscosity, kinematic : 8.00 mm2/s (104 °F (40 °C))

Surface tension : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure

**Acute toxicity** 

**Product:** 



# **BYK-054 T**

Version 1 Revision Date 06/20/2023 Print Date 06/29/2023

Acute oral toxicity : Remarks: No data available

## **Components:**

64741-65-7 Naphtha, petroleum, heavy alkylate:

Acute oral toxicity : LD50 (Rat): 34,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 3684 ppm

Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 15,400 mg/kg

## Skin corrosion/irritation

### **Product:**

Remarks: No data available

#### **Components:**

64741-65-7 Naphtha, petroleum, heavy alkylate:

Species: Rabbit Result: slight irritation

## Serious eye damage/eye irritation

## **Product:**

Remarks: No data available

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

## **Components:**

# 64741-65-7 Naphtha, petroleum, heavy alkylate:

Species: Rabbit

Result: Mild eye irritation

# Respiratory or skin sensitisation

#### **Product:**

Remarks: No data available

# Carcinogenicity

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.



**BYK-054 T** 

Version 1 Revision Date 06/20/2023 Print Date 06/29/2023

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Repeated dose toxicity

**Product:** 

Remarks: No data available

**Further information** 

**Product:** 

Remarks: Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION** 

**Ecotoxicity** 

**Product:** 

Toxicity to fish

Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Persistence and degradability

**Product:** 

Biodegradability : Remarks: No data available

Bioaccumulative potential

**Product:** 

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a

Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).



**BYK-054 T** 

Version 1 Revision Date 06/20/2023 Print Date 06/29/2023

Additional ecological

information

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

## **SECTION 14. TRANSPORT INFORMATION**

## **International Regulations**

IATA-DGR

UN/ID No. : UN 3295

Proper shipping name : Hydrocarbons, liquid, solution, n.o.s.

: 366

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo

aircraft)

Packing instruction : 355

(passenger aircraft)

**IMDG-Code** 

UN number : UN 3295

Proper shipping name : HYDROCARBONS, LIQUID, SOLUTION, N.O.S.

Class : 3
Packing group : III
Labels : 3

EmS Code : F-E, S-D Marine pollutant : yes

Remarks : Above applies only to containers over 119 gallons or 450

liters. Not regulated if shipped in packages less than or equal to 119 gallons (450 liters). If transporting by vessel or aircraft, unless other means of transportation is impracticable, then the

product must be shipped as a flammable liquid.

IMDG Code segregation group - none

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.



## **BYK-054 T**

Version 1 Revision Date 06/20/2023 Print Date 06/29/2023

## **National Regulations**

**49 CFR** 

UN/ID/NA number : UN 3295

Proper shipping name : Hydrocarbons, liquid, n.o.s. solution

Class : 3 Packing group : III

Labels : FLAMMABLE LIQUID

ERG Code : 128 Marine pollutant : no

Remarks : Above applies only to containers over 119 gallons or 450

liters. Not regulated if shipped in packages less than or equal to 119 gallons (450 liters). If transporting by vessel or aircraft, unless other means of transportation is impracticable, then the

product must be shipped as a flammable liquid.

49CFR: no dangerous good in non-bulk packaging

#### **SECTION 15. REGULATORY INFORMATION**

# **EPCRA - Emergency Planning and Community Right-to-Know Act**

## US. EPA CERCLA Hazardous Substances (40 CFR 302)

This material does not contain any components with a CERCLA RQ.

## SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

# US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA

harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for

reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act



# **BYK-054 T**

Version 1 Revision Date 06/20/2023 Print Date 06/29/2023

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : 25.00 %

Method: 22 (10min/150°C)

**DIN EN ISO 3251** 

Massachusetts Right To Know

No components are subject to the Massachusetts Right to

Know Act.

Pennsylvania Right To Know

Naphtha, petroleum, heavy alkylate 64741-65-7

Polymer -

**New Jersey Right To Know** 

New Jersey Trade Secret : 800963-6437

Registry Number for the product (NJ TSRN)

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

Section 5a : No substances are subject to a Significant New Use Rule.

Section 4 / 12(b) : No substances are subject to TSCA 12(b) export notification

requirements.

DSL : We certify that all of the components of this product are listed

on the DSL.

## **SECTION 16. OTHER INFORMATION**

Revision Date : 06/20/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is



# **BYK-054 T**

Version 1 Revision Date 06/20/2023 Print Date 06/29/2023

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.