

# **BYK-313**

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

#### **SECTION 1. IDENTIFICATION**

Product name : BYK-313

Manufacturer or supplier's details

Company : BYK USA Inc.

524 South Cherry Street Wallingford CT 06492

Telephone : (203) 265-2086 Visit our web site : www.byk.com

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1

number 703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Surface Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

# **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids : Category 3

Specific target organ toxicity

- single exposure

: Category 3 (Central nervous system)

**GHS** label elements

Hazard pictograms :





Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention**:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.



# **BYK-313**

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/

doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Solution of a polyester modified polydimethylsiloxane

**Hazardous components** 

Component	CAS-No.	Concentration (%)
1-Methoxy-2-propanol acetate	108-65-6	>= 84 -< 85

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.



**BYK-313** 

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: No information available.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Will not explode on mechanical impact.

Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon oxides

Nitrogen oxides (NOx) silicone compounds formaldehyde

Torrnaiderry

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, : Remove all sources of ignition.



# **BYK-313**

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

protective equipment and emergency procedures

Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive

concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Keep away from oxidizing agents.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxy-2-propanol acetate	108-65-6	TWA	50 ppm	US WEEL

**Engineering measures** : Use with local exhaust ventilation.



# **BYK-313**

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

## Personal protective equipment

Respiratory protection : Unless air monitoring demonstrates dusts/mists/vapors are

below the recommended exposure levels and/or WEEL, wear a properly fitted respirator (NIOSH) or dust mask during

exposure.

In the case of vapour formation use a respirator with an

approved filter.

Hand protection

Material : Nitrile rubber

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Clean long legged, long sleeved work clothes.

If splashing is possible, wear chemically resistant protective

clothing.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : colourless

Odour : solvent-like

Odour Threshold : No data available

pH : 6, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-

value indicator

Melting point/range : < 41 °F (< 5 °C)

Method: derived

Initial boiling point : 295 °F (146 °C)

5/13



**BYK-313** 

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

Method: derived

Vapour pressure : 3.37 hPa (68 °F (20 °C))

Method: derived

Flash point : ca. 113 °F (45 °C)

Method: 48 (Abel-Pensky)

Upper explosion limit : No data available

Lower explosion limit : No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Relative vapour density : No data available

Relative Density/Specific

Gravity

: No data available

Density : ca. 0.98 g/cm3 (68 °F (20 °C))

Method: 4 (20°C oscillating U-tube)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Ignition temperature :  $> 392 \, ^{\circ}\text{F} \, (> 200 \, ^{\circ}\text{C})$ 

Method: DIN 51 794/ DIN prEN 14 522

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : ca. 3.0 mPa.s (68 °F (20 °C))

Method: 11 (NV, 20°C)

Viscosity, kinematic : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.



**BYK-313** 

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

: 1-Methoxy-2-propanol acetate may form peroxides of

unknown stability.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

# Information on likely routes of exposure

Inhalation Ingestion Eyes

Skin Absorption Skin contact

## **Acute toxicity**

## **Components:**

#### 108-65-6 1-Methoxy-2-propanol acetate:

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 100 ppm

Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

#### Skin corrosion/irritation

**Product:** 

Remarks: No data available

#### **Components:**

# 108-65-6 1-Methoxy-2-propanol acetate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes



# **BYK-313**

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

## Serious eye damage/eye irritation

**Product:** 

Remarks: No data available

## **Components:**

108-65-6 1-Methoxy-2-propanol acetate:

Species: Rabbit Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes

## Respiratory or skin sensitisation

**Product:** 

Remarks: No data available

#### **Components:**

## 108-65-6 1-Methoxy-2-propanol acetate:

Species: Guinea pig

Method: OECD Test Guideline 406 Result: Not a skin sensitizer.

GLP: yes

## Carcinogenicity

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**OSHA**No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### Repeated dose toxicity

## **Product:**

Remarks: Solvent absorption by inhalation and/or repeated skin contact may cause injury to liver, kidney and respiratory system.

Studies suggest that 2-Methoxy-1-propanol acetate is teratogenic in animals. There is also evidence of fetotoxicity.



**BYK-313** 

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

**Experience with human exposure** 

**Product:** 

Inhalation:

Symptoms: High concentrations are irritating to the

respiratory tract. Has caused headaches, dizziness, nausea, vomiting and CNS depression (drowsiness, loss of coordination

and fatigue).

Skin contact:

Symptoms: Contact will probably cause irritation.

Eye contact:

Symptoms: Contact will probably cause irritation.

Ingestion:

Symptoms: Ingestion will probably irritate the digestive

tract; high dosages may cause CNS

depression.

**Further information** 

**Product:** 

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects..

Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION** 

**Ecotoxicity** 

**Product:** 

Toxicity to fish

Remarks: No data available

Persistence and degradability

**Product:** 

Biodegradability : Remarks: No data available

**Bioaccumulative potential** 

**Product:** 

Bioaccumulation : Remarks: No data available



# **BYK-313**

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

## Mobility in soil

No data available

#### Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a

Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological

information

: There is no data available for this product.

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

**EPA Hazardous Waste** 

Code(s)

: D001: Ignitable

Waste from residues : Dispose of in accordance with applicable local/municipal,

state/provincial and federal regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

# **International Regulations**

IATA-DGR

UN/ID No. : UN 3272
Proper shipping name : Esters, n.o.s.

(1-Methoxy-2-propanol acetate)

Class : 3 Packing group : III

10 / 13



## **BYK-313**

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

Labels : Flammable Liquids

Packing instruction (cargo : 366

aircraft)

Packing instruction : 355

(passenger aircraft)

**IMDG-Code** 

UN number : UN 3272

Proper shipping name : ESTERS, N.O.S.

(1-Methoxy-2-propanol acetate)

: )

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-D

Marine pollutant : no

Remarks : IMDG Code segregation group - none

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **National Regulations**

**49 CFR** 

UN/ID/NA number : UN 3272 Proper shipping name : Esters, n.o.s.

(1-Methoxy-2-propanol acetate)

Class : 3 Packing group : III

Labels : FLAMMABLE LIQUID

ERG Code : 127 Marine pollutant : no

Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

#### **SECTION 15. REGULATORY INFORMATION**

#### **EPCRA - Emergency Planning and Community Right-to-Know Act**

## US. EPA CERCLA Hazardous Substances (40 CFR 302)

Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

# US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.



## **BYK-313**

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA

harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for

reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

#### Massachusetts Right To Know

No components are subject to the Massachusetts Right to

Know Act.

#### Pennsylvania Right To Know

1-Methoxy-2-propanol acetate 108-65-6

Polyester modified polydimethylsiloxane -

## **New Jersey Right To Know**

1-Methoxy-2-propanol acetate 108-65-6

Polyester modified polydimethylsiloxane

New Jersey Trade Secret : 800963-5183

Registry Number for the product (NJ TSRN)

## California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## The components of this product are reported in the following inventories:

TSCA : We certify that all of the components of this product are either

listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).



# **BYK-313**

Version 6 Revision Date 02/25/2022 Print Date 05/06/2022

Section 4 / 12(b) : Not applicable

TSCA Inventory Active List 
All components of this product are listed active and/or are

exempt

DSL : We certify that all of the components of this product are listed

on the DSL.

#### **SECTION 16. OTHER INFORMATION**

Revision Date : 02/25/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.