

BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

SECTION 1. IDENTIFICATION

Product name : BYK-377

Manufacturer or supplier's details

Company : BYK USA Inc.

524 South Cherry Street Wallingford CT 06492

Telephone : (203) 265-2086 Visit our web site : www.byk.com

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1

number 703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Surface Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements : H361 Suspected of damaging fertility or the unborn child.

Precautionary statements : **Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P281 Use personal protective equipment as required.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/

attention. **Storage:**

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Polyether modified polydimethylsiloxane

Hazardous components

Component	CAS-No.	Concentration (%)
Octamethylcyclotetrasiloxane	556-67-2	>= 0 -<1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Remove to fresh air. Administer artificial respiration if

necessary. Get medical aid as soon as possible.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. Wash thoroughly with soap

and water.

In case of eye contact : Immediately flush with plenty of water for at least 20 minutes.

Get medical aid.

Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting; aspiration hazard. Dilute with 1-2

glasses of water. Get medical aid. If vomiting occurs

spontaneously, keep head below hips to prevent aspiration of

liquid into lungs.

Induce vomiting immediately and call a physician.

Keep respiratory tract clear.



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed

: No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Foam

Carbon dioxide (CO2)

Dry chemical

Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: No information available.

High volume water jet

Specific hazards during

firefighting

: Cool closed containers exposed to fire with water spray.

Will not explode on mechanical impact.

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Carbon oxides

silicone compounds

formaldehyde

Further information : Keep away from heat and sources of ignition.

Keep away from oxidizing agents.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

Personal precautions, protective equipment and emergency procedures : Wear protective equipment: goggles, chemically resistant clothing and gloves, and appropriate respirator if in a confined area.

: Use personal protective equipment.

Environmental precautions : Prevent spilled material from entering the ground, water

and/or air by using appropriate containment methods.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Stop leak. Dike and contain spill.

Pump into salvage tanks and/or absorb with suitable material.

Use sparkless shovels to remove material.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes.

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Handle as an industrial chemical. Keep container tightly closed.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep in a dry, cool and well-ventilated place.

Keep product and empty container away from heat and

sources of ignition.

Take measures to prevent the build up of electrostatic charge.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Keep away from oxidizing agents.



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : If handling heated or misted product in a poorly ventilated

area, wear a properly fitted respirator (NIOSH) during

exposure.

In the case of vapour formation use a respirator with an

approved filter.

Hand protection

Material : Neoprene gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety Glasses

Goggles

Eye wash bottle with pure water Tightly fitting safety goggles

Skin and body protection : Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : Clean long legged, long sleeved work clothes.

Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : light brown

Odour : not significant



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

Odour Threshold : No data available

pH : 7, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-

value indicator

Melting point/range : $< 32 \, ^{\circ}F \, (< 0 \, ^{\circ}C)$

Method: derived

Initial boiling point : $> 212 \,^{\circ}\text{F} \, (> 100 \,^{\circ}\text{C})$

Method: derived

Vapour pressure : < 1 hPa (ca. ())

Method: derived

Flash point : $> 212.00 \, ^{\circ}\text{F} \, (> 100.00 \, ^{\circ}\text{C})$

Method: 49 (Pensky-Martens)

Upper explosion limit : No data available

Lower explosion limit : No data available

Evaporation rate : No data available

Relative vapour density : No data available

Relative Density/Specific

Gravity

: No data available

Density : 1.0200 g/cm3 (68.00 °F (20.00 °C))

Method: 4 (20°C oscillating U-tube)

Bulk density : Not applicable

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Ignition temperature : $> 392 \, ^{\circ}\text{F} \, (> 200 \, ^{\circ}\text{C})$

Method: DIN 51 794/ DIN prEN 14 522

Thermal decomposition : No data available



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

Viscosity

Viscosity, dynamic : 1,148.000 mPa.s (68.00 °F (20.00 °C))

Method: P/K 20°C

Viscosity, kinematic : No data available

Surface tension : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

No decomposition if stored and applied as directed.

Chemical stability : Stable; polymerization will not occur

No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

: No data available

No decomposition if stored and applied as directed.

Conditions to avoid : None known.

No data available

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: None expected

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Skin Absorption Inhalation Eyes Ingestion

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

Skin corrosion/irritation

Product:

Remarks: No data available

Components:

556-67-2 Octamethylcyclotetrasiloxane:

Species: Rabbit Result: slight irritation

Serious eye damage/eye irritation

Product:

Remarks: No data available

Components:

556-67-2 Octamethylcyclotetrasiloxane:

Species: Rabbit

Result: Mild eye irritation

Respiratory or skin sensitisation

Product:

Remarks: No data available

Components:

556-67-2 Octamethylcyclotetrasiloxane:

Species: Guinea pig

Method: OECD Test Guideline 406 Result: Does not cause skin sensitisation.

GLP: yes

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks: No data available

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development

: Remarks: No data available

STOT - single exposure

Product:

Remarks: No data available

STOT - repeated exposure

Product:

Remarks: No data available

Repeated dose toxicity

Product:

Remarks: Inhalation (300 ppm)/ingestion (1600 mg/kg) dosages of Octamethylcyclotetrasiloxane has caused liver weight increases in laboratory animals. Liver weight changes via inhalation were reversible. A reproductive study (rats, inhalation: 700 ppm/70 days) showed a statistically significant reduction in mean litter size and implantation sites. The relevance of this data to humans is uncertain.



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

Aspiration toxicity

Product:

No data available

Experience with human exposure

Product:

Inhalation:

Symptoms: High concentrations of vapors resulting from

the product being heated, misted or sprayed may cause irritation of the respiratory tract, mucous membranes, and CNS depression.

Skin contact:

Symptoms: Contact may cause irritation.

Eye contact:

Symptoms: Contact may cause irritation.

Ingestion:

Symptoms: Ingestion may irritate the digestive tract.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a

Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological

information

: No data available

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

EPA Hazardous Waste

Code(s)

: Not applicable.

Waste from residues : Dispose of in accordance with applicable local/municipal,

state/provincial and federal regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Siloxanes)

Class : 9
Packing group : III



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

Labels : Miscellaneous

Packing instruction (cargo : 964

aircraft)

Packing instruction : 964

(passenger aircraft)

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (Siloxanes)

:)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F

Marine pollutant : yes

Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Siloxanes)

Class : 9 Packing group : III

Labels : CLASS 9
ERG Code : 171
Marine pollutant : no

Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

US. EPA CERCLA Hazardous Substances (40 CFR 302)

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA

harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for

reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

Non-volatile (Wt) : 96 - 100 %

Method: 51 (60min/105°C/1g)

DIN EN ISO 3251

Non-volatile information is not a specification.

Massachusetts Right To Know

No components are subject to the Massachusetts Right to

Know Act.

Pennsylvania Right To Know

Polysiloxanes -

_

New Jersey Right To Know

Polysiloxanes -

_

New Jersey Trade Secret Registry Number for the

product (NJ TSRN)

: 800963-5270

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA: We certify that all of the components of this product are either

listed on the TSCA Inventory or are not subject to the



BYK-377

Version 5 Revision Date 05/12/2022 Print Date 09/29/2022

notification requirements per 40 CFR 720 30(h).

Section 4 / 12(b) : Not applicable

TSCA Inventory Active List
All components of this product are listed active and/or are

exempt

DSL : We certify that all of the components of this product are listed

on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 05/12/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.