

BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

SECTION 1. IDENTIFICATION

Product name : BYK-A 515

Manufacturer or supplier's details

Company : BYK USA Inc.

524 South Cherry Street Wallingford CT 06492

Telephone : (203) 265-2086 Visit our web site : www.byk.com

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1

number 703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Air Release Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2B

Specific target organ toxicity

- single exposure

: Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity

- repeated exposure

: Category 1

GHS label elements

Hazard pictograms :







Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H315 + H320 Causes skin and eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated



BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

exposure.

Precautionary statements : **Prevention**:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell. P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : solution of polyalkylene ether



BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

Hazardous components

Component	CAS-No.	Concentration (%)
Naphtha, petroleum, hydrodesulfurized heavy	64742-82-1	>= 79 - < 80

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during : Will not explode on mechanical impact.



DV	′K-	٨	51	
ОΙ	'T\-	A	O I	Э

Version 8 Print Date 09/29/2022 Revision Date 03/11/2020

firefighting Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon oxides

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.



BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Keep away from strong acids.

Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values. Hazardous components without workplace control parameters

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an

approved filter.

Hand protection

Material : Nitrile rubber

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid



BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

Colour : light yellow

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/range : $< 5 \, ^{\circ}F \, (< -15 \, ^{\circ}C)$

Method: derived

Initial boiling point : ca. 291 °F (144 °C)

Method: derived

Vapour pressure : No data available

Flash point : 109 °F (43 °C)

Method: 48 (Abel-Pensky)

Upper explosion limit : 8 %(V)

Lower explosion limit : 0.6 %(V)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Relative vapour density : No data available

Relative Density/Specific

Gravity

: No data available

Density : 0.808 g/cm3 (68 °F (20 °C))

Method: 4 (20°C oscillating U-tube)

0.796 g/cm3 (104 °F (40 °C))

Method: 5 (40°C oscillating U-tube)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Ignition temperature : 446 °F (230 °C)



BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

Method: calculated

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : 54 mPa.s (104 °F (40 °C))

Method: P/K 40°C

Viscosity, kinematic : 67.8 mm2/s (104 °F (40 °C))

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids

Strong oxidizing agents

Hazardous decomposition

products

: No data available

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Ingestion Eyes

Skin Absorption Skin contact

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute dermal toxicity : Acute toxicity estimate : 3,126 mg/kg

Method: Calculation method



BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

Components:

64742-82-1 Naphtha, petroleum, hydrodesulfurized heavy: Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 11.6 mg/l

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: No data available

Components:

64742-82-1 Naphtha, petroleum, hydrodesulfurized heavy:

Species: Rabbit

Result: Moderate skin irritation

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

64742-82-1 Naphtha, petroleum, hydrodesulfurized heavy:

Species: Rabbit Result: Eye irritation

Respiratory or skin sensitisation

Product:

Remarks: No data available

Carcinogenicity

IARC Group 2B: Possibly carcinogenic to humans

Cumene 98-82-8

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Reasonably anticipated to be a human carcinogen

Cumene 98-82-8



BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

STOT - repeated exposure

Product:

Assessment: Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Product:

Remarks: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.

Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. Absorption of ingredients (solvents) by inhalation and/or repeated skin contact may cause injury to the liver/kidney.

Experience with human exposure

Product:

Inhalation:

Symptoms: High concentrations are irritating to the

respiratory tract. Has caused headaches, dizziness, nausea, vomiting and CNS depression (drowsiness, loss of coordination

and fatigue).

Skin contact:

Symptoms: Contact will probably cause irritation.

Absorption has caused same symptoms as

inhalation.

Eye contact:

Symptoms: Contact will probably cause irritation.

Ingestion:

Symptoms: Ingestion will probably irritate the digestive

tract; high dosages may cause CNS

depression.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.



BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Mobility in soil
No data available

Other adverse effects

Product:

Results of PBT and vPvB

assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or

very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a

Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

EPA Hazardous Waste

Code(s)

: D001: Ignitable

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.



BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1268

Proper shipping name : Petroleum distillates, n.o.s.

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo : 366

aircraft)

Packing instruction : 355

(passenger aircraft)

IMDG-Code

UN number : UN 1268

Proper shipping name : PETROLEUM DISTILLATES, N.O.S.

Class : 3
Packing group : III
Labels : 3

EmS Code : F-E, S-E Marine pollutant : yes

Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1268

Proper shipping name : Petroleum distillates, n.o.s.

Class : 3 Packing group : III

Labels : FLAMMABLE LIQUID

ERG Code : 128 Marine pollutant : no

Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples



BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

US. EPA CERCLA Hazardous Substances (40 CFR 302)

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA

harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for

reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject

to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and

40 CFR part 372.

1,2,4-Trimethylbenzene 95-63-6 1.5 %

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III. Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).



BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

Massachusetts Right To Know

 1,4-Dioxane
 123-91-1

 Benzene
 71-43-2

Pennsylvania Right To Know

Naphtha, petroleum, hydrodesulfurized 64742-82-1

heavy

Polymer -

 Cumene
 98-82-8

 Ethyl benzene
 100-41-4

 Naphthalene
 91-20-3

New Jersey Right To Know

Naphtha, petroleum, hydrodesulfurized 64742-82-1

heavy Polymer

New Jersey Trade Secret : 800963-5332

Registry Number for the product (NJ TSRN)

California Prop. 65

WARNING: This product can expose you to chemicals including Cumene, Ethyl benzene, Naphthalene, 1,4-Dioxane, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CONEG Heavy Metal: We confirm that we use packaging and/or packaging components in which the sum of the incidental concentration levels of lead, mercury, cadmium and hexavalent chromium do not exceed 100 parts per million by weight.

The components of this product are reported in the following inventories:

TSCA : We certify that all of the components of this product are either

listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

TSCA Inventory Active List : All components of this product are listed active and/or are

exempt

Section 4 / 12(b) Not applicable

DSL : We certify that all of the components of this product are listed

on the DSL.

SECTION 16. OTHER INFORMATION

Revision Date : 03/11/2020



BYK-A 515

Version 8 Revision Date 03/11/2020 Print Date 09/29/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.