

BYK-LP N 6322

Version 8

Revision Date 07/23/2019

Print Date 09/29/2022

SECTION 1. IDENTIFICATION

Product name : BYK-LP N 6322

Manufacturer or supplier's details

Company : BYK USA Inc.
524 South Cherry Street
Wallingford CT 06492

Telephone : (203) 265-2086

Visit our web site : www.byk.com

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone number : 203-265-2086; CHEMTREC 1-800-424-9300 / +1 703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Wetting & Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.

BYK-LP N 6322

Version 8

Revision Date 07/23/2019

Print Date 09/29/2022

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Solution of a salt of unsaturated fatty acid polyamine amides and acidic polyesters

Hazardous components

HMIRA# 9600 Filing Date 12.08.2015

Component	CAS-No.	Concentration (%)
Polyamine amide salt	-	>= 52 - < 53
Naphtha, petroleum, heavy alkylate		>= 47 - < 48

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : Remove to fresh air. Administer artificial respiration if necessary. Get medical aid as soon as possible.

BYK-LP N 6322

Version 8

Revision Date 07/23/2019

Print Date 09/29/2022

In case of skin contact	: Remove contaminated clothing. Wash thoroughly with soap and water.
In case of eye contact	: Immediately flush with plenty of water for at least 20 minutes. Get medical aid.
If swallowed	: Do not induce vomiting. Dilute with 1-2 glasses of water. Get medical aid. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	: No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: No information available.
Specific hazards during firefighting	: Cool closed containers exposed to fire with water spray. Will not explode on mechanical impact.
Hazardous combustion products	: Carbon oxides Nitrogen oxides (NO _x)
Further information	: Keep away from heat and sources of ignition. Take precautionary measures against static discharges.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Eliminate all sources of ignition. Ventilate area if indoors. Wear self-contained breathing apparatus and full protective clothing.
Environmental precautions	: Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods.
Methods and materials for containment and cleaning up	: Stop leak. Dike and contain spill. Pump into salvage tanks and/or absorb with suitable material. Use sparkless shovels to remove material.

BYK-LP N 6322

Version 8

Revision Date 07/23/2019

Print Date 09/29/2022

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Harmful in contact with skin.
Avoid contact with skin and eyes.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Handle as an industrial chemical.
Keep container tightly closed.
- Conditions for safe storage : Keep in a dry, cool and well-ventilated place.
Keep product and empty container away from heat and sources of ignition.
Take measures to prevent the build up of electrostatic charge.
- Materials to avoid : Keep away from oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Contains no substances with occupational exposure limit values.

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

- Respiratory protection : Unless air monitoring demonstrates vapor/mist/dust levels are below the PEL/TLV wear a properly fitted respirator (NIOSH approved) or dust mask during exposure.
- Hand protection
Material : Viton
- Eye protection : Safety Glasses
Goggles
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : Clean long legged, long sleeved work clothes.
Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : light brown

BYK-LP N 6322

Version 8

Revision Date 07/23/2019

Print Date 09/29/2022

Odour	: amine-like
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: < 32 °F (< 0 °C) Method: derived
Initial boiling point	: 307.40 °F (153.00 °C) Method: derived
Vapour pressure	: 13.0000000 hPa (68.00 °F (20.00 °C)) Method: calculated
Flash point	: 100.40 °F (38.00 °C) Method: 48 (Abel-Pensky)
Upper explosion limit	: 7.00 %(V)
Lower explosion limit	: 0.60 %(V)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.8650 g/cm ³ (68.00 °F (20.00 °C)) Method: 4 (20°C oscillating U-tube)
Bulk density	: Not applicable
Solubility(ies) Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51794
Thermal decomposition	: No data available

BYK-LP N 6322

Version 8

Revision Date 07/23/2019

Print Date 09/29/2022

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 199.000 mm²/s (68.00 °F (20.00 °C))54 mm²/s (104.00 °F (40.00 °C))

Surface tension

: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable; polymerization will not occur

Possibility of hazardous reactions : No data available

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : None expected

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact

Skin Absorption

Inhalation

Eyes

Ingestion

Acute toxicity**Product:**

Acute oral toxicity : Remarks: No data available

Components:**Naphtha, petroleum, heavy alkylate:**

Acute oral toxicity : LD50 (Rat): 34,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 3684 ppm
Exposure time: 4 h

BYK-LP N 6322

Version 8

Revision Date 07/23/2019

Print Date 09/29/2022

Acute dermal toxicity : LD50 (Rabbit): 15,400 mg/kg

Skin corrosion/irritation**Components:****Naphtha, petroleum, heavy alkylate:**

Species: Rabbit

Result: slight irritation

Serious eye damage/eye irritation**Components:****Naphtha, petroleum, heavy alkylate:**

Species: Rabbit

Result: Mild eye irritation

Respiratory or skin sensitisation**Product:**

Remarks: No data available

Carcinogenicity**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

BYK-LP N 6322

Version 8

Revision Date 07/23/2019

Print Date 09/29/2022

Repeated dose toxicity**Product:**

Remarks: Absorption of ingredients (solvents) by inhalation and/or repeated skin contact may cause injury to the liver/kidney.

Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.

Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Inhalation of Naphtha has caused fetotoxic effects at maternally toxic doses in laboratory animals.

Experience with human exposure**Product:**

Inhalation:

Symptoms:

High concentrations of vapors may be irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

Symptoms:

Contact will probably cause irritation.

Eye contact:

Symptoms:

Contact will probably cause irritation.

Ingestion:

Symptoms:

Ingestion may irritate the digestive tract; high dosages may cause CNS depression.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Product:**

Bioaccumulation

: Remarks: No data available

Mobility in soil

No data available

BYK-LP N 6322

Version 8

Revision Date 07/23/2019

Print Date 09/29/2022

Other adverse effects**Product:**

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste Code(s) : D001: Ignitable

Waste from residues : Dispose of in accordance with applicable local/municipal, state/provincial and federal regulations.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 3295
Proper shipping name : Hydrocarbons, liquid, n.o.s.
Class : 3
Packing group : III
Labels : Flammable liquid
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 3295
Proper shipping name : HYDROCARBONS, LIQUID, N.O.S.
Class : 3
Packing group : III
Labels : 3

BYK-LP N 6322

Version 8

Revision Date 07/23/2019

Print Date 09/29/2022

EmS Code : F-E, S-D
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 3295
Proper shipping name : Hydrocarbons, liquid, n.o.s.
Class : 3
Packing group : III
Labels : Flammable liquid
ERG Code : 128
Marine pollutant : no
Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

BYK-LP N 6322

Version 8

Revision Date 07/23/2019

Print Date 09/29/2022

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

Non-volatile (Wt) : 50 - 54 %
Method: 22 (10min/150°C)
DIN EN ISO 3251
Non-volatile information is not a specification.

Massachusetts Right To Know

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know


Polyamine amide salt	-
Naphtha, petroleum, heavy alkylate	Not Assigned

New Jersey Right To Know

Polyamine amide salt	-
Naphtha, petroleum, heavy alkylate	Not Assigned

New Jersey Trade Secret : 800963-5042
Registry Number for the product (NJ TSRN)

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Propylene oxide, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CONEG Heavy Metal: We confirm that we use packaging and/or packaging components in which the sum of the incidental concentration levels of lead, mercury, cadmium and hexavalent chromium do not exceed 100 parts per million by weight.

The components of this product are reported in the following inventories:

TSCA : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

Section 4 / 12(b) : Not applicable

TSCA Inventory Active List All components of this product are listed active and/or are exempt

DSL : We certify that all of the components of this product are listed on the DSL.

BYK-LP N 6322

Version 8

Revision Date 07/23/2019

Print Date 09/29/2022

SECTION 16. OTHER INFORMATION

Revision Date : 07/23/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.