

BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

SECTION 1. IDENTIFICATION

Product name : BYK-UV 3505

Manufacturer or supplier's details

Company : BYK USA Inc.

524 South Cherry Street Wallingford CT 06492

Telephone : (203) 265-2086 Visit our web site : www.byk.com

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1

number 703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Surface Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Specific target organ toxicity

- single exposure

: Category 3 (Respiratory system)

GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements : H227 Combustible liquid.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.



BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

Precautionary statements : **Prevention**:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Acryl functional dimethylpolysiloxane

Hazardous components

Component	CAS-No.	Concentration (%)
Tripropylene glycol diacrylate	42978-66-5	>= 59 -< 60



BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Will not explode on mechanical impact.

Cool closed containers exposed to fire with water spray.

Hazardous combustion

products

: Carbon oxides

Nitrogen oxides (NOx) silicone compounds formaldehyde

Further information : For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.



BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage No smoking.

> Keep in a well-ventilated place. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid Keep away from strong acids.

> Keep away from strong bases. Keep away from metals.

Keep away from oxidizing agents.



BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values. Hazardous components without workplace control parameters

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : If handling heated or misted product in a poorly ventilated

area, wear a properly fitted respirator (NIOSH) during

exposure.

In the case of vapour formation use a respirator with an

approved filter.

Hand protection

Material : Nitrile rubber

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Goggles

Safety glasses with side-shields Eye wash bottle with pure water Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Clean long legged, long sleeved work clothes.

If splashing is possible, wear chemically resistant protective

clothing.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid



BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

Colour : light yellow

Odour : acrylic-like

Odour Threshold : No data available

pH : 6, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-

value indicator

Melting point/freezing point : $< 32 \,^{\circ}\text{F} (< 0 \,^{\circ}\text{C})$

Method: Melting point DSC

Initial boiling point and boiling

range

 $: > 347 \, ^{\circ}\text{F} (> 175 \, ^{\circ}\text{C})$

Vapour pressure : < 1 hPa (68 °F (20 °C))

Method: calculated

Flash point : 183 °F (84 °C)

Method: 49 (Pensky-Martens)

Upper explosion limit : No data available

Lower explosion limit : No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Relative vapour density : No data available

Relative Density/Specific

Gravity

: No data available

Density : 1.062 g/cm3 (68 °F (20 °C))

Method: 4 (20°C oscillating U-tube)

Bulk density : Not applicable

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Ignition temperature : > 392 °F (> 200 °C)



BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

Method: DIN 51 794/ DIN prEN 14 522

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Surface tension : No data available

Molecular weight : 6,500 g/mol

Method: GPC method 04

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids and bases

Strong oxidizing agents

Metals

Hazardous decomposition

products

: No data available

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation

Ingestion

Eyes

Skin Absorption Skin contact

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available



BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

42978-66-5 Tripropylene glycol diacrylate:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Product:

Remarks: Causes serious eye irritation.

Components:

42978-66-5 Tripropylene glycol diacrylate:

Species: Rabbit

Result: Severe eye irritation

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Components:

42978-66-5 Tripropylene glycol diacrylate:

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

Carcinogenicity

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHANo component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.



BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

Repeated dose toxicity

Product:

Remarks: No known chronic health effects.

Experience with human exposure

Product:

Inhalation:

Symptoms: High concentrations of vapors resulting from

the product being heated, misted or sprayed may cause irritation of the respiratory tract

and mucous membranes.

Skin contact:

Symptoms: Contact will probably cause irritation; may

cause skin sensitization.

Eye contact:

Symptoms: Contact will probably cause severe irritation.

Ingestion:

Symptoms: Ingestion will probably cause irritation of the

digestive tract.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

9/13



BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Mobility in soilNo data available

Other adverse effects

Product:

Results of PBT and vPvB

assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a

Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological

information

: Not available

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

EPA Hazardous Waste

Code(s)

: Not applicable.

Waste from residues : Dispose of in accordance with applicable local/municipal,

state/provincial and federal regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.



BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Tripropylene glycol diacrylate)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction : 964

(passenger aircraft)

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Tripropylene glycol diacrylate)

:)

: 964

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Remarks : IMDG Code segregation group - none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

Marine pollutant

49 CFR

UN/ID/NA number : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Tripropylene glycol diacrylate)

Class : 9
Packing group : III

Labels : CLASS 9 ERG Code : 171

Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

SECTION 15. REGULATORY INFORMATION



BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

EPCRA - Emergency Planning and Community Right-to-Know Act

US. EPA CERCLA Hazardous Substances (40 CFR 302)

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA

harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for

reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Massachusetts Right To Know

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know

Tripropylene glycol diacrylate 42978-66-5
Acryl functional dimethylpolysiloxane Not Assigned

New Jersey Right To Know

Tripropylene glycol diacrylate 42978-66-5 Acryl functional dimethylpolysiloxane Not Assigned



BYK-UV 3505

Version 7 Revision Date 06/09/2021 Print Date 09/29/2022

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : 800963-5392

California Prop. 65

WARNING: This product can expose you to chemicals including Toluene, Bisphenol A, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : We certify that all of the components of this product are either

listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

TSCA Inventory Active List : All components of this product are listed active and/or are

exempt

Section 4 / 12(b) Not applicable

DSL : The following component(s) is/are not listed on the DSL:

CEPA Category : Polymer
Weight percent : 40 %
NSN Filed : None
Max. NSN Required : Schedule 10

SECTION 16. OTHER INFORMATION

Revision Date : 06/09/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.