

**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

**SECTION 1. IDENTIFICATION**

Product name : BYK-SILCLEAN 3720

**Manufacturer or supplier's details**

Company : BYK USA Inc.  
524 South Cherry Street  
Wallingford CT 06492  
Telephone : (203) 265-2086  
Visit our web site : [www.byk.com](http://www.byk.com)  
E-mail address : [BRIEF.BYK.NAFTA@altana.com](mailto:BRIEF.BYK.NAFTA@altana.com)

Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1  
number 703-527-3887

**Recommended use of the chemical and restrictions on use**

Recommended use : Surface Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3  
Reproductive toxicity : Category 1B  
Specific target organ toxicity : Category 3 (Respiratory system, Central nervous system)  
- single exposure

**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H360D May damage the unborn child.

Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Solution of a polyether modified hydroxy functional polydimethylsiloxane

**Hazardous components**

Component	CAS-No.	Concentration (%)
1-Methoxy-2-propanol	107-98-2	>= 74 - < 75
2-Methoxy-1-propanol (impurity)	1589-47-5	>= 0.1 - < 1

The specific chemical identity/weight percent of proprietary ingredient(s) is a trade secret

**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

**SECTION 4. FIRST AID MEASURES**

- |   |   |
|---|---|
| General advice  | : Move out of dangerous area.<br>Show this safety data sheet to the doctor in attendance.<br>Do not leave the victim unattended.  |
| If inhaled  | : Consult a physician after significant exposure.<br>If unconscious, place in recovery position and seek medical advice.  |
| In case of skin contact                                     | : If on skin, rinse well with water.<br>If on clothes, remove clothes.  |
| In case of eye contact                                      | : Flush eyes with water as a precaution.<br>Remove contact lenses.<br>Protect unharmed eye.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist.                                   |
| If swallowed  | : Keep respiratory tract clear.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician.<br>Take victim immediately to hospital. |
| Most important symptoms and effects, both acute and delayed | : No information available.   |

**SECTION 5. FIREFIGHTING MEASURES**

- |                                      |   |
|--------------------------------------|---|
| Suitable extinguishing media         | : Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical   |
| Unsuitable extinguishing media       | : High volume water jet   |
| Specific hazards during firefighting | : Will not explode on mechanical impact.<br>Cool closed containers exposed to fire with water spray.<br><br>Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products        | : Carbon oxides   |
| Further information                  | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  |

**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with

**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

the technological safety standards.

Materials to avoid : Keep away from oxidizing agents.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxy-2-propanol	107-98-2	TWA	50 ppm	ACGIH
1-Methoxy-2-propanol		STEL	100 ppm	ACGIH

Hazardous components without workplace control parameters

**Engineering measures** : Use with local exhaust ventilation.**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Material : Nitrile rubber

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water  
Tightly fitting safety goggles

Skin and body protection

: Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : light brown

Odour : solvent-like

Odour Threshold : No data available

**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

pH	: 7, Concentration: 10 % (68 °F (20 °C)) Method: Universal pH-value indicator
Melting point/freezing point	: < 32 °F (< 0 °C) Method: derived
Initial boiling point and boiling range	: 248 °F (120 °C) Method: derived
Vapour pressure	: 13 hPa (68 °F (20 °C)) Method: derived
Flash point	: 88 °F (31 °C) Method: 48 (Abel-Pensky)
Upper explosion limit	: 13.7 %(V)
Lower explosion limit	: 1.5 %(V)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.945 g/cm <sup>3</sup> (68 °F (20 °C)) Method: 4 (20°C oscillating U-tube)
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 392 °F (> 200 °C) Method: DIN 51794
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available

**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: 1-Methoxy-2-propanol acetate/DPM may form peroxides of unknown stability.  No decomposition if stored and applied as directed.  Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: None expected No decomposition if stored and applied as directed.

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Ingestion  
Eyes  
Skin Absorption  
Skin contact

**Acute toxicity****Product:**

Acute oral toxicity : Remarks: No data available

Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

**Components:****107-98-2 1-Methoxy-2-propanol:**

Acute oral toxicity : LD50 (Rat, male and female): 4,016 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): 1500 ppm

Acute dermal toxicity : LD50 (Rabbit): 13,000 mg/kg

**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

**Skin corrosion/irritation****Product:**

Remarks: No data available

**Components:****107-98-2 1-Methoxy-2-propanol:**

Species: Rabbit

Method: Directive 67/548/EEC, Annex V, B.4.

Result: No skin irritation

GLP: yes

**Serious eye damage/eye irritation****Product:**

Remarks: No data available

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:****107-98-2 1-Methoxy-2-propanol:**

Species: Rabbit

Result: No eye irritation

Method: Directive 67/548/EEC, Annex V, B.5.

GLP: yes

**Respiratory or skin sensitisation****Product:**

Remarks: No data available

**Components:****107-98-2 1-Methoxy-2-propanol:**

Test Type: Maximisation Test

Exposure routes: Dermal

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Does not cause skin sensitisation.

GLP: yes

**Carcinogenicity****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.



**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Repeated dose toxicity****Product:**

Remarks: Solvent absorption by inhalation and/or repeated skin contact may cause injury to liver, kidney and respiratory system.

Studies suggest that 2-Methoxy-1-propanol acetate is teratogenic in animals. There is also evidence of fetotoxicity.

**Experience with human exposure****Product:**

Inhalation:

Symptoms:

High concentrations are irritating to the respiratory tract. Has caused headaches, dizziness, nausea, vomiting and CNS depression (drowsiness, loss of coordination and fatigue).

Skin contact:

Symptoms:

Contact will probably cause irritation.

Eye contact:

Symptoms:

Contact will probably cause irritation.

Ingestion:

Symptoms:

Ingestion may irritate the digestive tract; high dosages may cause CNS depression.

**Further information****Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

Toxicity to fish :  
Remarks: No data available

**Persistence and degradability****Product:**

Biodegradability : Remarks: No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : There is no data available for this product.

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

EPA Hazardous Waste Code(s) : D001: Ignitable

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

UN/ID No. : UN 3092  
Proper shipping name : 1-Methoxy-2-propanol, solution  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 3092  
Proper shipping name : 1-METHOXY-2-PROPANOL, SOLUTION  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-D  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

UN/ID/NA number : UN 3092  
Proper shipping name : 1-Methoxy-2-propanol, solution  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID  
ERG Code : 129  
Marine pollutant : no  
Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 - Emergency Release Notification**

**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

**Non-volatile (Wt)** : 25 %  
Method: 22 (10min/150°C)  
DIN EN ISO 3251  
Non-volatile information is not a specification.

**Massachusetts Right To Know**

1-Methoxy-2-propanol 107-98-2

**Pennsylvania Right To Know**

1-Methoxy-2-propanol 107-98-2

Polyether modified polydimethylsiloxane -

**New Jersey Right To Know**

1-Methoxy-2-propanol 107-98-2

Polyether modified polydimethylsiloxane -

**New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : 800963-5134


**BYK-SILCLEAN 3720**

Version 6

Revision Date 02/18/2022

Print Date 05/06/2022

**California Prop. 65**

 **WARNING:** This product can expose you to chemicals including Formaldehyde, Acetaldehyde, 1,4-Dioxane, Ethylene oxide, which is/are known to the State of California to cause cancer, and Ethylene oxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**

TSCA	: We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).
Section 4 / 12(b)	: Not applicable
TSCA Inventory Active List	All components of this product are listed active and/or are exempt
CEPA Category	: Polymer
Weight percent	: 24 %
NSN Filed	: None
Max. NSN Required	: Schedule 10

**SECTION 16. OTHER INFORMATION**

Revision Date : 02/18/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.