

DISPERBYK-2025

Version 8 Revision Date 03/03/2022 Print Date 01/15/2024

SECTION 1. IDENTIFICATION

Product name : DISPERBYK-2025

Manufacturer or supplier's details

Company : BYK USA Inc.

524 South Cherry Street Wallingford CT 06492

Telephone : (203) 265-2086 Visit our web site : www.byk.com

E-mail address : BRIEF.BYK.NAFTA@altana.com

Emergency telephone : 203-265-2086; CHEMTREC 1-800-424-9300 / +1

number 703-527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Wetting & Dispersing Additive

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Specific target organ toxicity

- single exposure

: Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :





Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.



Version 8 Revision Date 03/03/2022 Print Date 01/15/2024

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a POISON CENTER/

doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Solution of a structured acrylic copolymer with pigment affinic

groups

Hazardous components

Component	CAS-No.	Concentration (%)	
1-Methoxy-2-propanol acetate	108-65-6	>= 31 - < 32	

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.



DISPERBYK-2025

Version 8 Revision Date 03/03/2022 Print Date 01/15/2024

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

t symptoms : No information available. oth acute and

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

: High volume water jet

Dry chemical

Unsuitable extinguishing

media

Specific hazards during

firefighting

: Will not explode on mechanical impact.

Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon oxides

Oxides of phosphorus Nitrogen oxides (NOx)

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.



Version 8 Revision Date 03/03/2022 Print Date 01/15/2024

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Open drum carefully as content may be under pressure.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Keep away from oxidizing agents.

Keep away from metals.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxy-2-propanol acetate	108-65-6	TWA	50 ppm	US WEEL

Engineering measures : Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : Unless air monitoring demonstrates dusts/mists/vapors are

below the recommended exposure levels and/or WEEL, wear a properly fitted respirator (NIOSH) or dust mask during

exposure.

In the case of vapour formation use a respirator with an

approved filter.



DISPERBYK-2025

Version 8 Revision Date 03/03/2022 Print Date 01/15/2024

Hand protection

Material : Nitrile rubber

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid Colour : yellow

Odour : characteristic
Odour Threshold : No data available

pH : 6, Concentration: 1 % (68 °F (20 °C)) Method: Universal pH-

value indicator

Melting point/range : $< 32 \, ^{\circ}\text{F} \, (< 0 \, ^{\circ}\text{C})$

Method: derived

Boiling point/boiling range : ca. 293 °F (145 °C)

Method: derived

Vapour pressure : 3.37 hPa (68 °F (20 °C))

Method: derived

Flash point : 118 °F (48 °C)

(1,013 hPa)

Method: 48 (Abel-Pensky)

Upper explosion limit : 10.8 %(V)

Lower explosion limit : 1.5 %(V)

Evaporation rate : No data available

Relative vapour density : No data available

Relative Density/Specific

Gravity

: No data available



DISPERBYK-2025

Version 8 Revision Date 03/03/2022 Print Date 01/15/2024

Density : 1.036 g/cm3 (68 °F (20 °C))

Method: 4 (20°C oscillating U-tube)

Bulk density : Not applicable

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

Ignition temperature

: No data available

: > 392 °F (> 200 °C) Method: DIN 51794

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 650 mm2/s (68 °F (20 °C))

Surface tension : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity No decomposition if stored and applied as directed. : No decomposition if stored and applied as directed. Chemical stability Possibility of hazardous : 1-Methoxy-2-propanol acetate may form peroxides of

reactions

unknown stability.

Vapours may form explosive mixture with air. Gives off hydrogen by reaction with metals.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid Heat, flames and sparks. Incompatible materials : Strong oxidizing agents

Metals

Hazardous decomposition

products

: None expected



DISPERBYK-2025

Version 8 Revision Date 03/03/2022 Print Date 01/15/2024

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eyes Skin contact Skin Absorption

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Components:

108-65-6 1-Methoxy-2-propanol acetate:

Acute oral toxicity : LD50 (Rat, female): > 5,000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 100 ppm

Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: No data available

Components:

108-65-6 1-Methoxy-2-propanol acetate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

Serious eye damage/eye irritation

Product:

Remarks: No data available

Components:

108-65-6 1-Methoxy-2-propanol acetate:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes



Version 8 Revision Date 03/03/2022 Print Date 01/15/2024

Respiratory or skin sensitisation

Product:

Remarks: No data available

Components:

108-65-6 1-Methoxy-2-propanol acetate:

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Not a skin sensitizer.

GLP: yes

Carcinogenicity

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Repeated dose toxicity

Product:

Remarks: Animal studies show that 1-Methoxy-2-propanol acetate has caused damage to the respiratory system.

Solvent absorption by inhalation and/or repeated skin contact may cause injury to liver, kidney and respiratory system.

Studies suggest that 2-Methoxy-1-propanol acetate is teratogenic in animals. There is also evidence of fetotoxicity.

Experience with human exposure

Product:

Inhalation:

Symptoms: High concentrations of vapors may be

irritating to the respiratory tract. May cause headaches, dizziness, nausea and vomiting. May cause CNS depression (drowsiness,

loss of coordination and fatigue).

Skin contact:

Symptoms: Contact will probably cause irritation.



DISPERBYK-2025

Version 8 Revision Date 03/03/2022 Print Date 01/15/2024

Eye contact:

Symptoms: Contact will probably cause irritation.

Ingestion:

Symptoms: Ingestion will probably irritate the digestive

tract; high dosages may cause CNS

depression.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a

Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).



DISPERBYK-2025

Version 8 Revision Date 03/03/2022 Print Date 01/15/2024

Additional ecological

information

: There is no data available for this product.

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

EPA Hazardous Waste

Code(s)

: D001: Ignitable

Waste from residues : Dispose of in accordance with applicable local/municipal,

state/provincial and federal regulations. Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3272
Proper shipping name : Esters, n.o.s.

(1-Methoxy-2-propanol acetate)

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo

aircraft)

Packing instruction : 355

(passenger aircraft)

IMDG-Code

UN number : UN 3272

Proper shipping name : ESTERS, N.O.S.

(1-Methoxy-2-propanol acetate)

:)

: 366

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-D

Marine pollutant : no

Remarks : IMDG Code segregation group - none

10 / 13



Version 8 Revision Date 03/03/2022 Print Date 01/15/2024

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 3272
Proper shipping name : Esters, n.o.s.

(1-Methoxy-2-propanol acetate)

Class : 3 Packing group : III

Labels : FLAMMABLE LIQUID

ERG Code : 127 Marine pollutant : no

Container sizes: 55 gallon drums, 5 or 6-gallon pails, 2oz/16oz samples

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

US. EPA CERCLA Hazardous Substances (40 CFR 302)

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA

harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for

reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).



DISPERBYK-2025

Print Date 01/15/2024 Version 8 Revision Date 03/03/2022

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : 70 %

Method: 46 (30min/150°C + EA)

DIN EN ISO 3251

Non-volatile information is not a specification.

Massachusetts Right To Know

No components are subject to the Massachusetts Right to

Know Act.

Pennsylvania Right To Know

Polymer Not Assigned 1-Methoxy-2-propanol acetate 108-65-6

New Jersey Right To Know

Polymer Not Assigned 1-Methoxy-2-propanol acetate 108-65-6

: 800963-5229 **New Jersey Trade Secret**

Registry Number for the product (NJ TSRN)

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA : We certify that all of the components of this product are either

> listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

Section 4 / 12(b) : Not applicable

TSCA Inventory Active List All components of this product are listed active and/or are

exempt

DSL This product contains one or several components that are not

on the Canadian DSL nor NDSL.

: Polymer **CEPA Category** Weight percent : 70 % NSN Filed : Schedule 9 Max. NSN Required : Schedule 10



DISPERBYK-2025

Version 8 Revision Date 03/03/2022 Print Date 01/15/2024

SECTION 16. OTHER INFORMATION

Revision Date : 03/03/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.