

Version 9	Revision Date 05/12/2022	Print Date 05/10/2024
SECTION 1. IDENTIFICATION		
Product name	: DISPERBYK-2151	
Manufacturer or supplier's	details	
Company	: BYK USA Inc. 524 South Cherry Street Wallingford CT 06492	
Telephone Visit our web site	: (203) 265-2086 : www.byk.com	
E-mail address	: BRIEF.BYK.NAFTA@altana	.com
Emergency telephone number	: 203-265-2086; CHEMTREC 703-527-3887	1-800-424-9300 / +1
Recommended use of the	chemical and restrictions on use	•
Recommended use Restrictions on use	: Wetting & Dispersing Additiv : Refer to Section 15 for any re	
SECTION 2. HAZARDS IDENTIF	ICATION	
GHS Classification		
Flammable liquids	: Category 3	
Skin irritation	: Category 2	
Eye irritation	: Category 2A	
Aspiration hazard	: Category 1	
GHS label elements		
Hazard pictograms		!
Signal word	: Danger	
Hazard statements	 H226 Flammable liquid and H304 May be fatal if swallow H315 Causes skin irritation. H319 Causes serious eye irr 	ed and enters airways.
Precautionary statements	 Prevention: P210 Keep away from heat/ No smoking. P233 Keep container tightly P240 Ground/bond container P241 Use explosion-proof el 	r and receiving equipment.
	1 / 13	

DISPERBYK-2151

Version 9	Revision Date	05/12/2022	Print Date 05/10/2024
	Revision Date	03/12/2022	1 1111 Date 03/10/2024
	Revision Date 05/12/2022 Print Date 05/10/2 equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P264 Wash skin thoroughly after handling. P264 Wash skin thoroughly after handling. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ eye protection/ face protection. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediate all contaminated clothing. Rinse skin with water/ shower. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and ear to do. Continue rinsing. P331 Do NOT induce vomiting. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Storage: P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.		ndling. rotection/ face protection. hediately call a POISON or hair): Take off immediately n with water/ shower. inse cautiously with water it lenses, if present and easy c Get medical advice/ s: Get medical advice/ g and wash before reuse. y sand, dry chemical or ed place. Keep cool.
Other hazards None known.			
SECTION 3. COMPOSITION/INFORM	MATION ON ING	REDIENTS	
Substance / Mixture : Chemical nature : Hazardous components	Mixture High molecular	polyester	
Component		CAS-No.	Concentration (%)
1-Methoxy-2-propanol acetate		108-65-6	>= 19 - < 20
SECTION 4. FIRST AID MEASURES			
General advice :	Symptoms of p	ngerous area. ty data sheet to the d oisoning may appear ie victim unattended.	
If inhaled :			sition and seek medical

DISPERBYK-2151

ersion 9	Revision Date 05/12/2022	Print Date 05/10/2024
	advice. If symptoms persist, call a physicia	n.
In case of skin contact	: If skin irritation persists, call a phys If on skin, rinse well with water. If on clothes, remove clothes.	
In case of eye contact	 Immediately flush eye(s) with plent Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. 	-
If swallowed	If eye irritation persists, consult a s Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic bevera Never give anything by mouth to ar If symptoms persist, call a physicia Take victim immediately to hospital	ages. n unconscious person. n.
Most important symptoms and effects, both acute and delayed	: No information available.	
ECTION 5. FIREFIGHTING MEAS	SURES	
Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	: High volume water jet	
Specific hazards during firefighting	: Will not explode on mechanical imp Cool closed containers exposed to	
	Do not allow run-off from fire fightir courses.	ig to enter drains or water
Hazardous combustion products	: Carbon oxides Nitrogen oxides (NOx)	
Further information	: Collect contaminated fire extinguisl must not be discharged into drains. Fire residues and contaminated fire be disposed of in accordance with For safety reasons in case of fire, of separately in closed containments. Use a water spray to cool fully clos	e extinguishing water must local regulations. cans should be stored
Special protective equipment for firefighters	: Wear self-contained breathing approved a water spray to cool fully close a water spray to cool fully close a spr	
ECTION 6. ACCIDENTAL RELEA	SE MEASURES	
Personal precautions, protective equipment and	: Use personal protective equipment Ensure adequate ventilation.	<u>.</u>
emergency procedures	Remove all sources of ignition.	

DISPERBYK-2151

ersion 9		Revision Date 05/12/2022	Print Date 05/10/20
		Evacuate personnel to safe areas. Beware of vapours accumulating to concentrations. Vapours can accum	
Environmental precautions	:	Prevent product from entering drain Prevent further leakage or spillage If the product contaminates rivers a respective authorities.	if safe to do so.
Methods and materials for containment and cleaning up	:	Contain spillage, and then collect w absorbent material, (e.g. sand, eart vermiculite) and place in container t local / national regulations (see sec	h, diatomaceous earth, for disposal according to
CTION 7. HANDLING AND STO	DR.A	GE	
Advice on safe handling	:	Avoid formation of aerosol. Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section Smoking, eating and drinking shoul application area. Take precautionary measures again	d be prohibited in the
		Provide sufficient air exchange and Open drum carefully as content ma Dispose of rinse water in accordance regulations	/or exhaust in work rooms. y be under pressure.
Conditions for safe storage	:	Open drum carefully as content ma	Vor exhaust in work rooms. by be under pressure. ce with local and national ry and well-ventilated be carefully resealed and

О ВУК

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxy-2-propanol acetate	108-65-6	TWA	50 ppm	US WEEL
Engineering measures	Use with local	exhaust ventilat	tion.	



	Revision Date 05/12/2022	Print Date 05/10/2
Personal protective equipme	nt	
Respiratory protection	: Unless air monitoring demonstrates below the recommended exposure a properly fitted respirator (NIOSH) exposure.	levels and/or WEEL, wear
Hand protection Material	: Nitrile rubber	
Remarks	: The suitability for a specific workpla with the producers of the protective	
Eye protection	: Goggles Safety glasses with side-shields Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective sui problems.	
Skin and body protection	 Choose body protection according t concentration of the dangerous sub Impervious clothing Choose body protection according t concentration of the dangerous sub 	stance at the work place. to the amount and
Hygiene measures	 Handle in accordance with good incorpractice. Clean long legged, long sleeved wood if splashing is possible, wear chemic clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the statement of the statem	ork clothes. cally resistant protective
TION 9. PHYSICAL AND CHE	MICAL PROPERTIES	
Appearance	: liquid	
Colour	: amber	
	•	
Colour Odour	: amber : characteristic	C)) Method: Universal pH-
Colour Odour Odour Threshold	 amber characteristic No data available 6, Concentration: 1 % (68 °F (20 °C) 	C)) Method: Universal pH-
Colour Odour Odour Threshold pH	 amber characteristic No data available 6, Concentration: 1 % (68 °F (20 °C value indicator < 32 °F (< 0 °C) 	C)) Method: Universal pH-
Colour Odour Odour Threshold pH Melting point/freezing point Initial boiling point and boiling	 amber characteristic No data available 6, Concentration: 1 % (68 °F (20 °C) value indicator < 32 °F (< 0 °C) Method: derived ca. 293 °F (145 °C) 	C)) Method: Universal pH-

DISPERBYK-2151

rsion 9		Revision Date 05/12/2022	Print Date 05/10/20
Flash point	:	111 °F (44 °C) Method: 49 (Pensky-Martens)	
Upper explosion limit	:	No data available	
Lower explosion limit	:	No data available	
Evaporation rate	:	No data available	
Flammability (solid, gas)	:	No data available	
Relative vapour density	:	No data available	
Relative Density/Specific	:	No data available	
Gravity Density	:	1.060 g/cm3 (68 °F (20 °C)) Method: 4 (20°C oscillating U-tube)	
Bulk density	:	Not applicable	
Solubility(ies) Water solubility	:	immiscible	
Solubility in other solvents	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Ignition temperature	:	> 392 °F (> 200 °C) Method: DIN 51794	
Thermal decomposition	:	No data available	
Viscosity Viscosity, dynamic	:	No data available	
Viscosity, kinematic	:	No data available	
Conductivity	:	0.21 µS/cm	

O BYK

Reactivity: No decomposition if stored and applied as directed.Chemical stability: No decomposition if stored and applied as directed.Possibility of hazardous
reactions: 1-Methoxy-2-propanol acetate may form peroxides of
unknown stability.No decomposition if stored and applied as directed.

6/13



	Revision Date 05/12/2022	Print Date 05/10/20
	Vapours may form explosive mi	xture with air.
Conditions to avoid Incompatible materials Hazardous decomposition products	Heat, flames and sparks.Strong oxidizing agents	
CTION 11. TOXICOLOGICAL	INFORMATION	
Information on likely routes Inhalation Eyes Skin contact Skin Absorption	of exposure	
Acute toxicity		
Product: Acute oral toxicity	: Remarks: No data available	
	Acute toxicity estimate : 3,126 m Method: Calculation method	ıg/kg
Components: 108-65-6 1-Methoxy-2-propa Acute oral toxicity	anol acetate: : LD50 (Rat, female): > 5,000 mg/ Method: OECD Test Guideline 4 GLP: yes	kg 01
Acute inhalation toxicity	: LC50 (Rat): > 100 ppm Exposure time: 4 h	
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg	
Skin corrosion/irritation		
Product:		
Remarks: No data available		
Remarks: No data available Remarks: May cause skin irrit	tation in susceptible persons.	



· •		
rsion 9	Revision Date 05/12/2022	Print Date 05/10/2024
Serious eye damage/eye irrit	ation	
Product:		
Remarks: No data available		
Remarks: Causes serious eye	irritation.	
Components: 108-65-6 1-Methoxy-2-propar Species: Rabbit Result: No eye irritation Method: OECD Test Guideline GLP: yes		
Respiratory or skin sensitisa	ition	
Product: Remarks: No data available		
Components: 108-65-6 1-Methoxy-2-propar Species: Guinea pig Method: OECD Test Guideline Result: Not a skin sensitizer. GLP: yes		
Carcinogenicity		
IARC	No component of this product present a equal to 0.1% is identified as probable, human carcinogen by IARC.	
OSHA	No component of this product present a equal to 0.1% is on OSHA's list of regu	
NTP	No component of this product present a equal to 0.1% is identified as a known by NTP.	
Repeated dose toxicity		
Product:		
	by inhalation and/or repeated skin contac stem.	ct may cause injury to
Experience with human expo	osure	
Product:		

О ВУК

rsion 9	Revision Da	ate 05/12/2022	Print Date 05/10/20
Inhalation:	Symptoms:	respiratory trad dizziness, nau	ations are irritating to the ct. Has caused headaches, sea, vomiting and CNS owsiness, loss of coordinat
Skin contact:	Symptoms:	Contact will pr	obably cause irritation.
Eye contact:	Symptoms:	Contact will pr	obably cause irritation.
Ingestion:	Symptoms:		probably irritate the digestive ages may cause CNS
Product:			
Remarks: Solvents m CTION 12. ECOLOGIC Ecotoxicity <u>Product:</u>	nay degrease the skin.		
Remarks: Solvents m CTION 12. ECOLOGIC Ecotoxicity <u>Product:</u> Toxicity to fish Toxicity to daphnia ar	CAL INFORMATION : Remarks: No	o data available o data available	
Remarks: Solvents m CTION 12. ECOLOGIC Ecotoxicity <u>Product:</u> Toxicity to fish	CAL INFORMATION : Remarks: No nd other : Remarks: No gradability	o data available o data available o data available	
Remarks: Solvents m CTION 12. ECOLOGIC Ecotoxicity <u>Product:</u> Toxicity to fish Toxicity to daphnia ar aquatic invertebrates Persistence and deg <u>Product:</u>	CAL INFORMATION : Remarks: No nd other : Remarks: No gradability : Remarks: No	o data available	
Remarks: Solvents m CTION 12. ECOLOGIC Ecotoxicity <u>Product:</u> Toxicity to fish Toxicity to daphnia and aquatic invertebrates Persistence and deg <u>Product:</u> Biodegradability	CAL INFORMATION : Remarks: No nd other : Remarks: No gradability : Remarks: No otential	o data available	



DISPERBYK-2151			
Version 9		Revision Date 05/12/2022	Print Date 05/10/2024
Mobility in soil No data available			
Other adverse effects No data available			
Product:			
Regulation		40 CFR Protection of Environment; Stratospheric Ozone - CAA Section	
Remarks		This product neither contains, nor w Class I or Class II ODS as defined b Section 602 (40 CFR 82, Subpt. A,	by the U.S. Clean Air Act
Additional ecological information	:	No data available	
ECTION 13. DISPOSAL CONS	DEF	ATIONS	
Disposal methods			
EPA Hazardous Waste Code(s)	:	D001: Ignitable	
Waste from residues Contaminated packaging	:	Dispose of in accordance with appli state/provincial and federal regulation Do not dispose of waste into sewer. Do not contaminate ponds, waterwat chemical or used container. Send to a licensed waste managem Empty remaining contents. Dispose of as unused product.	ons. ays or ditches with
		Do not re-use empty containers. Do not burn, or use a cutting torch o	on, the empty drum.
SECTION 14. TRANSPORT INFO	ORM	ATION	
International Regulations			
IATA-DGR UN/ID No. Proper shipping name	:	UN 3272 Esters, n.o.s. (1-Methoxy-2-propanol acetate)	
Class Packing group Labels	:	3 III Flammable Liquids	
Packing instruction (cargo aircraft)	:	366	
Packing instruction (passenger aircraft)	:	355	
		10 / 13	

DISPERBYK-2151

SPERBYK-2151		
rsion 9	Revision Date 05/12/2022	Print Date 05/10/20
IMDG-Code		
UN number	: UN 3272	
Proper shipping name	: ESTERS, N.O.S.	
	(1-Methoxy-2-propanol acetate)	
	:)	
Class	: 3	
Packing group	: 111	
Labels EmS Code	: 3 : F-E, S-D	
Marine pollutant	: no	
Remarks	: IMDG Code segregation group - nor	ne
	ng to Annex II of MARPOL 73/78 and the	
-	-	IBC Code
Not applicable for product a	s supplied.	
National Regulations		
49 CFR		
UN/ID/NA number	: UN 3272	
Proper shipping name		
r topor ompping name	(1-Methoxy-2-propanol acetate)	
Class	: 3	
Packing group	: 11	
Labels	: FLAMMABLE LIQUID	
ERG Code	: 127	
	: 127 : no	
Marine pollutant	rums, 5 or 6-gallon pails, 2oz/16oz sample	
TION 15. REGULATORY IN	IFORMATION	
EPCRA - Emergency Plan	ning and Community Right-to-Know Act	
•••	bus Substances (40 CFR 302)	
Calculated RQ exceeds rea	sonably attainable upper limit.	
SARA 304 - Emergency Re	elease Notification	
	ain any components with a section 304 EHS	S RQ.
	ning and Community Right-To-Know Ac zardous Substance (40 CFR 355, Appen	
-		
This material does not conta	ain any components with a SARA 302 RQ.	
SARA 311/312 Hazards	: Per the June 13, 2016 Federal Regi	ster notice, EPA
	harmonized the EPCRA 311/312 ha	zard categories with the
	2012 OSHA hazard communication	
	and labeling of chemicals (i.e. GHS)	
	of the SDS to identify the appropriat	e nazard categories for
	11 / 13	

О ВУК

sion 9	Revision Date 05/12	2/2022	Print Date 05/10/2	
	reporting purposes.			
SARA 302		No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.		
SARA 313	known CAS numbers	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.		
Clean Air Act				
This product does not contain Act Section 112 (40 CFR 61)		nts (HAP), as de	fined by the U.S. Clean	
This product does not contain Accidental Release Prevention			Air Act Section 112(r) f	
This product does not contair Intermediate or Final VOC's (er the U.S. Clean	Air Act Section 111 SO	
Non-volatile (Wt)	DIN EN ISO 3251	Method: 22 (10min/150°C)		
Massachusetts Right To Kr			na shun atta Diakt ta	
	No components are s Know Act.	subject to the Ma	ssachusetts Right to	
Pennsylvania Right To Kno	w			
Polyester		-		
•				
1-Methoxy-	2-propanol acetate	108-65-6	i	
•		108-65-6 98-88-4	i	
1-Methoxy-	loride		i	
1-Methoxy- Benzoyl Ch New Jersey Right To Know Polyester	loride		i	
1-Methoxy- Benzoyl Ch New Jersey Right To Know Polyester	loride			
1-Methoxy- Benzoyl Ch New Jersey Right To Know Polyester 1-Methoxy- New Jersey Trade Secret Registry Number for the	2-propanol acetate : 800963-5444	98-88-4 - 108-65-6	i	
1-Methoxy- Benzoyl Ch New Jersey Right To Know Polyester 1-Methoxy- New Jersey Trade Secret Registry Number for the product (NJ TSRN) California Prop. 65 This product does not contair defects, or any other reprodu	2-propanol acetate : 800963-5444 n any chemicals known to s	98-88-4 - 108-65-6 State of California	a to cause cancer, birth	
1-Methoxy- Benzoyl Ch New Jersey Right To Know Polyester 1-Methoxy- New Jersey Trade Secret Registry Number for the product (NJ TSRN) California Prop. 65 This product does not contain	2-propanol acetate : 800963-5444 n any chemicals known to s ctive harm.	98-88-4 - 108-65-6 State of California following inven the components of iventory or are no	a to cause cancer, birth tories: of this product are either ot subject to the	



DISPERBYK-2151

	/2024
Section 4 / 12(b) : Not applicable	
TSCA Inventory Active List All components of this product are listed active and/or are exempt	
DSL : We certify that all of the components of this product are liste on the DSL.	d

SECTION 16. OTHER INFORMATION

Revision Date : 05/12/2022 The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.