

**DURASTRENGTH® 350 Impact Modifier**

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Company**

Arkema Inc.  
900 First Avenue  
King of Prussia, Pennsylvania 19406

Arkema Coating Resins

**Customer Service Telephone Number:** (877) 331-6696  
(Monday through Friday, 8:00 AM to 5:00 PM EST)

**Emergency Information**

**Transportation:** CHEMTREC: (800) 424-9300  
(24 hrs., 7 days a week)  
**Medical:** Rocky Mountain Poison Center: (866) 767-5089  
(24 hrs., 7 days a week)

**Product Information**

**Product name:** DURASTRENGTH® 350 Impact Modifier  
**Synonyms:** Not available  
**Molecular formula:** Complex Mixture  
**Chemical family:** acrylic polymer  
**Product use:** Impact modifier

**2. HAZARDS IDENTIFICATION**

**Emergency Overview**

**Color:** white  
**Physical state:** solid  
**Form:** powder  
**Odor:** slightly acrylic

**\*Classification of the substance or mixture:**  
See Supplemental Hazard Statements below.

**GHS-Labeling**

Signal word: **Warning**

**Hazard statements:**

This material is considered hazardous under the OSHA Hazard Communication Standard criteria, based on hazard(s) not otherwise classified.

**Supplemental Hazard Statements:**

May form combustible dust concentrations in air. Processing may release vapors and/or fumes which cause eye, skin and respiratory tract irritation.

**DURASTRENGTH® 350 Impact Modifier**
**Supplemental information:**
**Potential Health Effects:**

The product, in the form supplied, is not anticipated to produce significant adverse human health effects. Contains high molecular weight polymer(s). Effects due to processing releases: Irritating to eyes, respiratory system and skin. Prolonged or repeated exposure may cause: headache, drowsiness, nausea, weakness, (severity of effects depends on extent of exposure).

**Other:**

Handle in accordance with good industrial hygiene and safety practice. (powder) Mechanical irritation effects from dust exposure are possible at ambient temperature. This product may release fume and/or vapor of variable composition depending on processing time and temperature. Note: The hazard classification is based on the proportion of the surfactant that is extractable in aqueous media.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No.	Wt/Wt	GHS Classification**
Acrylic polymer	Proprietary*	>= 90 - <= 94 %	Not classified
Carbonic acid calcium salt (1:1)	471-34-1	>= 2 - <= 6 %	Not classified
Surfactant	Proprietary*	>= 2 - <= 3 %	H228, H302, H315, H318, H335, H402
Water	7732-18-5	<= 1.2 %	Not classified

\*The specific chemical identity is withheld because it is trade secret information of Arkema Inc.

\*\*For the full text of the H-Statements mentioned in this Section, see Section 16.

**4. FIRST AID MEASURES**
**Inhalation:**

If inhaled, remove victim to fresh air.

**Skin:**

In case of contact, immediately flush skin with plenty of water. If molten polymer gets on the skin, cool rapidly with cold water. Do not peel solidified product off the skin. Obtain medical treatment for thermal burns. Remove material from clothing. Wash clothing before reuse. Thoroughly clean shoes before reuse.

**DURASTRENGTH® 350 Impact Modifier****Eyes:**

Immediately flush eye(s) with plenty of water. Obtain medical treatment for thermal burns.

**Ingestion:**

If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

**5. FIREFIGHTING MEASURES****Extinguishing media (suitable):**

Water spray, Carbon dioxide (CO<sub>2</sub>), Foam, Dry chemical

**Extinguishing media (unsuitable):**

High volume water jet

**Protective equipment:**

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

**Further firefighting advice:**

Do not use a solid stream of water.

A solid stream of water can cause a dust explosion.

Fire fighting equipment should be thoroughly decontaminated after use.

**Fire and explosion hazards:**

When burned, the following hazardous products of combustion can occur:

Carbon oxides

Hazardous organic compounds

Sulphur oxides

Dust clouds generated during handling and/or storage can form explosive mixtures with air. Dust explosion characteristics vary with the particle size, particle shape, moisture content, contaminants, and other variables.

Note: Check that all equipment is properly grounded and installed to satisfy electrical classification requirements. As with any dry material, pouring this material or allowing it to free-fall or to be conveyed through chutes or pipes can accumulate and generate electrostatic sparks, potentially causing ignition of the material itself, or of any flammable materials which may come into contact with the material or its container.

**6. ACCIDENTAL RELEASE MEASURES****In case of spill or leak:**

Prevent further leakage or spillage if you can do so without risk. Evacuate area of all unnecessary personnel.

Ventilate the area. Eliminate all ignition sources. Avoid dust formation and dispersal of dust in the air. Wet down (dampen) the spilled material with water. Sweep or scoop up using non-sparking tools and place into suitable properly labeled containers for prompt disposal. The sweepings should be wetted down further with water. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Implement workplace practices such that dusts are not allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

# DURASTRENGTH® 350 Impact Modifier

## 7. HANDLING AND STORAGE

### Handling

#### General information on handling:

Avoid breathing dust.  
 Keep away from heat, sparks and flames.  
 Keep container closed.  
 Avoid creating dust in handling, transfer or clean up.  
 Prevent dust accumulation.  
 Implement routine housekeeping practices to ensure that dusts do not accumulate on surfaces.  
 Check that all equipment is properly grounded and installed to satisfy electrical classification requirements.  
 Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations.  
 Container hazardous when empty.  
 Follow label warnings even after container is emptied.  
**RESIDUAL DUSTS MAY EXPLODE ON IGNITION.**  
**DO NOT CUT, DRILL, GRIND, OR WELD ON OR NEAR THIS CONTAINER.**  
 Improper disposal or reuse of this container may be dangerous and/or illegal.  
 Emptied container retains product residue.  
 Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin, and clothing.

### Storage

#### General information on storage conditions:

Keep in a dry, cool place. Store in closed containers, in a secure area to prevent container damage and subsequent spillage. Store in well ventilated area away from heat and sources of ignition such as flame, sparks and static electricity. Ensure that all storage and handling equipment is properly grounded and installed to satisfy electrical classification requirements. Static electricity may accumulate when transferring material. All metal and groundable storage containers, including but not limited to drums, cylinders, Returnable Intermodal Bulk Containers (RIBCs) and Class C Flexible Intermodal Bulk Containers (FIBCs) must be bonded and grounded during filling and emptying operations. Observe all federal, state and local regulations and National Fire Protection Association (NFPA) Codes, which pertain to the specific local conditions of storage and use, including NFPA 654.

#### Storage incompatibility – General:

Store separate from:

Oxidizing agents

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Airborne Exposure Guidelines:

#### Carbonic acid calcium salt (1:1) (471-34-1)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

<b>Form:</b>	Respirable fraction.
<b>PEL:</b>	5 mg/m <sup>3</sup>

<b>Form:</b>	Total dust
<b>PEL:</b>	15 mg/m <sup>3</sup>

## DURASTRENGTH® 350 Impact Modifier

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions.

### Engineering controls:

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Check that all dust control equipment such as local exhaust ventilation, material transport systems, and air-material separation devices involved in handling this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Isolation devices may be appropriate to prevent propagation from one unit to another. Ensure that dust-handling systems are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Consult ACGIH ventilation manual, NFPA Standard 91 and NFPA Standard 654 for design of exhaust system and safe handling.

### Respiratory protection:

Avoid breathing dust. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components and substances released during processing. Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

### Skin protection:

Processing of this product releases vapors or fumes which may cause skin irritation. Minimize skin contamination by following good industrial hygiene practice. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after contact with processing fumes or vapors. Wash thoroughly after handling.

### Eye protection:

Use good industrial practice to avoid eye contact. Processing of this product releases vapors or fumes which may cause eye irritation. Where eye contact may be likely, wear chemical goggles and have eye flushing equipment available.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Color:</b>	white
<b>Physical state:</b>	solid
<b>Form:</b>	powder
<b>Odor:</b>	slightly acrylic
<b>Odor threshold:</b>	No data available

## DURASTRENGTH® 350 Impact Modifier

<b>Flash point</b>	Not applicable
<b>Auto-ignition temperature:</b>	752 °F (400 °C)
<b>Lower flammable limit (LFL):</b>	No data available
<b>Upper flammable limit (UFL):</b>	No data available
<b>pH:</b>	Not applicable
<b>Density:</b>	No data available
<b>Bulk density:</b>	250 - 500 kg/m <sup>3</sup>
<b>Vapor pressure:</b>	Not applicable
<b>Vapor density:</b>	Not applicable
<b>Boiling point/boiling range:</b>	Not applicable
<b>Melting point/range:</b>	not determined
<b>Evaporation rate:</b>	No data available
<b>Solubility in water:</b>	insoluble
<b>Oil/water partition coefficient:</b>	No data available
<b>Thermal decomposition</b>	No data available
<b>Flammability:</b>	See GHS Classification in Section 2

### 10. STABILITY AND REACTIVITY

**Stability:**

The product is stable under normal handling and storage conditions.

**Hazardous reactions:**

Hazardous polymerization does not occur.

**Materials to avoid:**

Oxidizing agents

**Conditions / hazards to avoid:**

See HANDLING AND STORAGE section of this MSDS for specified conditions. See Hazardous Decomposition Products below.

**DURASTRENGTH® 350 Impact Modifier****Hazardous decomposition products:**

Thermal decomposition giving flammable and toxic products  
Carbon oxides  
Acrylates  
Methacrylates  
Sulphur oxides  
Hazardous organic compounds

**11. TOXICOLOGICAL INFORMATION**

Data on this material and/or its components are summarized below.

**Data for Acrylic polymer (Proprietary)****Acute toxicity****Oral:**

No deaths occurred. (rat) LD50 > 2,000 mg/kg.

**Skin Irritation:**

Practically non-irritating. (rabbit) (4 h)

**Eye Irritation:**

Causes mild eye irritation. (rabbit)

**Other information**

The information presented is from representative materials with this Chemical Abstract Service (CAS) Registry number. The results vary depending on the size and composition of the test substance. Effects due to processing releases or residual monomer:

Possible cross sensitization with other acrylates and methacrylates

**Human experience****Skin contact:**

Skin: Irritation, dermatitis. Isolated case reports after exposure to a mixture containing this substance.

**Data for Carbonic acid calcium salt (1:1) (471-34-1)****Acute toxicity****Oral:**

Practically nontoxic. (rat) LD50 = 6,450 mg/kg.

**Dermal:**

No deaths occurred. (rat) LD0 >= 2,000 mg/kg.

**Inhalation:**

No deaths occurred. (rat) 4 h LC0 >= 3 mg/l. signs: No specific toxic effects (aerosol, Maximum concentration technically possible)

**DURASTRENGTH® 350 Impact Modifier**

---

**Skin Irritation:**

Not irritating. (rabbit) Irritation Index: 0.0 / 8.0. (4 h)

**Eye Irritation:**

Causes mild eye irritation. (rabbit)

**Skin Sensitization:**

Not a sensitizer. LLNA: Local Lymph Node Assay. (mouse) No effect is reported.

**Repeated dose toxicity**

Repeated oral administration to rat, mouse / No adverse systemic effects reported.

**Genotoxicity****Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, animal cells, human cells

**Developmental toxicity**

Exposure during pregnancy. dietary (sheep) / bone effects in lambs (at doses that produce effects in mothers, blood chemistry changes)

Exposure during pregnancy. dietary (rat) / No birth defects were observed.

**Reproductive effects**

Reproductive/Developmental Effects Screening Assay. oral (rat) / No toxicity to reproduction

**Human experience****General:**

Dust contact with the eyes can lead to mechanical irritation. Contact with dust can cause mechanical irritation or drying of the skin.

**Human experience****Inhalation:**

Upper respiratory tract: Local irritation, coughing. (dust) (severity of effects depends on extent of exposure)

**Human experience****Ingestion:**

Kidney: failure, weakness, nausea. (effects of excessive exposure)

**Data for Surfactant (Proprietary)****Acute toxicity****Oral:**

Harmful if swallowed. (Rat) LD50 1,830 mg/kg.

**Skin Irritation:**

Causes skin irritation. (rabbit) (4 h) (similar material)

**Eye Irritation:**

Causes serious eye damage. (rabbit) (similar material)

**Repeated dose toxicity**

Subchronic oral administration to rat / affected organ(s): Gastrointestinal tract, liver / signs: Local

---



**DURASTRENGTH® 350 Impact Modifier**

effects due to an irritant effect, increased organ weight / (similar material)

**Genotoxicity****Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, animal cells, (data for a similar material)

**12. ECOLOGICAL INFORMATION****Chemical Fate and Pathway**

Data on this material and/or its components are summarized below.

**Data for Surfactant (Proprietary)****Biodegradation:**

Readily biodegradable. (28 d) biodegradation > 60 % / similar material

**Octanol Water Partition Coefficient:**

log Pow < 4

**Ecotoxicology**

Data on this material and/or its components are summarized below.

**Data for Carbonic acid calcium salt (1:1) (471-34-1)****Aquatic toxicity data:**

No effect up to the limit of solubility. Oncorhynchus mykiss (rainbow trout) 96 h

**Aquatic invertebrates:**

No effect up to the limit of solubility. Daphnia magna (Water flea) 48 h

**Algae:**

No effect up to the limit of solubility. Desmodesmus subspicatus (green algae) 72 h

**Microorganisms:**

Respiration inhibition / Activated sludge 3 h EC50 > 1,000 mg/l

**Data for Surfactant (Proprietary)****Aquatic toxicity data:**

Toxic. Leuciscus idus (Golden orfe) 48 h LC50 = 9.3 mg/l (nominal concentrations reported, similar material)

**Aquatic invertebrates:**

Toxic. Ceriodaphnia dubia 48 h EC50 1.4 mg/l

**Algae:**

Harmful. Pseudokirchneriella subcapitata (microalgae) 72 h EC50 60 mg/l

**13. DISPOSAL CONSIDERATIONS****Waste disposal:**

Where possible recycling is preferred to disposal or incineration. If recycling is not an option, incinerate or dispose of

**DURASTRENGTH® 350 Impact Modifier**

in accordance with federal, state, and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

**14. TRANSPORT INFORMATION**

**US Department of Transportation (DOT):** not regulated

**International Maritime Dangerous Goods Code (IMDG):** not regulated

**15. REGULATORY INFORMATION**
**Chemical Inventory Status**

EU. EINECS	EINECS	Conforms to
United States TSCA Inventory	TSCA	The components of this product are all on the TSCA Inventory.
Canadian Domestic Substances List (DSL)	DSL	All components of this product are on the Canadian DSL.
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Conforms to
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Conforms to
Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	Conforms to
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	Conforms to
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	The mixture contains a polymer. The monomers for this polymer have been notified., Conforms to
Australia Inventory of Chemical Substances (AICS)	AICS	Conforms to

**United States – Federal Regulations**
**SARA Title III – Section 302 Extremely Hazardous Chemicals:**

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

**SARA Title III - Section 311/312 Hazard Categories:**

Fire Hazard

# DURASTRENGTH® 350 Impact Modifier

## SARA Title III – Section 313 Toxic Chemicals:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):

The components in this product are either not CERCLA regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

## United States – State Regulations

### New Jersey Right to Know

<u>Chemical Name</u>	<u>CAS-No.</u>
Carbonic acid calcium salt (1:1)	471-34-1

### Pennsylvania Right to Know

<u>Chemical Name</u>	<u>CAS-No.</u>
Acrylic polymer	Proprietary
Carbonic acid calcium salt (1:1)	471-34-1

### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.

## 16. OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3.

H228	Flammable solid.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H402	Harmful to aquatic life.

### Miscellaneous:

Other information:	Refer to National Fire Protection Association (NFPA) Code 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.
--------------------	---

### Latest Revision(s):

Reference number:	000000076641
Date of Revision:	04/25/2015
Date Printed:	04/25/2015

**DURASTRENGTH® 350 Impact Modifier**

---

DURASTRENGTH® is a registered trademark of Arkema Inc.

Arkema Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of Arkema Inc., Arkema Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.