



Safety Data Sheet (SDS)

North American

Revision date: 2016-11-04

SECTION 1: Identification

Product identifiers:

Product trade name:	D and C Red 6 Barium Lake
Company product number:	5L3006
Other means of identification:	Not Available

Recommended use of the chemical and restrictions on use:

Uses:	D&C Color
Restrictions on use:	None identified

Details of the supplier:

Manufacturer/Supplier:	Dystar L.P. Pine Brook III 9844 Southern Pine Blvd Charlotte, NC 28273, USA Telephone: (800) 439-7827 FAX: (704) 561-3098
------------------------	--

Emergency telephone number:

Chemtrec (24 hours): USA: 1-800-424-9300; International: +001-703-527-3887.

SECTION 2: Hazard(s) identification

Information in accordance with U.S. 29 CFR 1910.1200 (Hazcom 2012) and Canada Hazardous Products Regulations (WHMIS 2015):

Classification of the product:

Skin Sensitizer, category 1
Respiratory Sensitizer, category 1
Combustible Dust

Label elements:

Hazard pictogram(s):



Signal word:

Danger

Hazard statements:

H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
USH001 May form combustible dust concentrations in air.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves.
P284 [In case of inadequate ventilation] wear respiratory protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P362+P364 Take off contaminated clothing and wash it before reuse.

SDS Name: D and C Red 6 Barium Lake

P501 Dispose of contents/container in accordance with local, regional and international regulations.

Supplemental information: Skin may discolor due to contact with pigment.

Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS) - Annex III. Regulations in individual countries/regions may determine which statements are required on the product label. See product label for specifics.

Hazards not otherwise classified:

Physical hazards not otherwise classified: No Additional Information

Health hazards not otherwise classified: No Additional Information

See Section 11 for toxicological information.

SECTION 3: Composition/information on ingredients

Mixture:

<u>CAS-No.</u>	<u>Chemical Name</u>
0017852-98-1	D&C Red No. 6 Barium Lake
0007727-43-7	Barium sulfate
0068188-14-7	Resin acids and rosin acids, barium salts

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits. Exact percentage values for components are proprietary in accordance with 29 CFR 1910.1200(i).

SECTION 4: First-aid measures

Description of first aid measures:

General: If irritation or other symptoms occur or persist from any route of exposure, remove the affected individual from the area: see a physician/get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. Get medical attention if symptoms occur.

Skin contact: Immediately remove contaminated clothing and shoes. Wash the affected area with plenty of soap and water until no evidence of the chemical remains (at least 15-20 minutes). Launder clothing before reuse. If skin irritation occurs: Get medical advice/attention.

Inhalation: If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse out the mouth with water. Get medical attention immediately.

Protection of first aid responders: Wear proper personal protective clothing and equipment.

Most important symptoms and effects, both acute and delayed: Asthma, Irritation, Shortness of breath, Skin contact may discolor skin due to pigment. Preexisting sensitization, skin and/or respiratory disorders or diseases may be aggravated. See section 11 for additional information.

Indication of any immediate medical attention and special treatment needed, if necessary: Treat symptomatically.

SECTION 5: Fire-fighting measures

NFPA flammability class: N/A (Combustible solid)

Extinguishing media:

Suitable: Carbon dioxide, foam, dry chemical, water.

Unsuitable: Avoid hose streams or any method which will create dust clouds.

Special hazards arising From the chemical:

Unusual fire/explosion hazards: Concentrated dust/air combinations may produce explosive conditions. As with all organic dusts, fine particles suspended in air in critical proportions and in the presence of an ignition source may ignite and/or explode. Dust may be sensitive to ignition by electrostatic discharge, electrical arcs, sparks, welding torches, cigarettes, open flame, or other significant heat sources. As a precaution, implement standard safety measures for handling finely divided organic

SDS Name: D and C Red 6 Barium Lake

powders. See Section 7 for suggested measures.

Hazardous combustion products: Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See section 10 (Hazardous decomposition products) for additional information.

Special protective equipment and precautions for fire-fighters: Avoid hose streams or any method which will create dust clouds. Wear self-contained breathing apparatus (SCBA) equipped with a full facepiece and operated in a pressure-demand mode (or other positive pressure mode) and approved protective clothing. Personnel without suitable respiratory protection must leave the area to prevent significant exposure to hazardous gases from combustion, burning or decomposition. In an enclosed or poorly ventilated area, wear SCBA during cleanup immediately after a fire as well as during the attack phase of firefighting operations.

See section 9 for additional information.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures: See Section 8 for recommendations on the use of personal protective equipment. If spilled in an enclosed area, ventilate. Avoid raising powdered material due to explosion hazard. Use spark-proof and explosion-proof equipment. If inhalation of dust cannot be avoided, wear an approved particulate respirator. Personal Protective Equipment must be worn.

Environmental precautions: Do not flush product into public sewer, water systems or surface waters.

Methods and materials for containment and cleaning up: Contain spill. Wear proper personal protective clothing and equipment. Using care to avoid dust generation, vacuum or sweep into a closed container for reuse or disposal. Use approved industrial vacuum cleaner for removal. Avoid causing dust. Place into labeled, closed container; store in safe location to await disposal. Change contaminated clothing and launder before reuse.

SECTION 7: Handling and storage

Precautions for safe handling: As with any chemical product, use good laboratory/workplace procedures. Do not breathe dust, vapor, aerosol, mist or gas. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Avoid eye and skin contact. Avoid drinking, tasting, swallowing or ingesting this product. Avoid routine inhalation of dust of any kind. Exercise care when emptying containers, sweeping, mixing or doing other tasks which can create dust. Wash contaminated clothing before reuse. Provide eyewash fountains and safety showers in the work area. As a precaution to control dust explosion potential, implement the following safety measures: Eliminate ignition sources (e.g., sparks, static buildup, excessive heat, etc.). In general, dust of organic materials is a static charge generator which may be ignited by electrostatic discharge, electrical arcs, sparks, welding torches, cigarettes, open flame, or other significant heat sources. Use spark-proof tools and equipment. Bond, ground and properly vent conveyors, dust control devices and other transfer equipment. Prohibit flow of polymer, powder or dust through non-conductive ducts, vacuum hoses or pipes, etc.; only use grounded, electrically conductive transfer lines when pneumatically conveying product. Good housekeeping and controlling of dusts are necessary for safe handling of product. Prevent accumulation of dust (e.g., well-ventilated conditions, promptly vacuuming spills, cleaning overhead horizontal surfaces, etc.). A properly engineered explosion suppression system must be considered. See standards such as the National Fire Protection Association NFPA 654, "Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids"; NFPA 69, "Standard on Explosion Prevention Systems"; NFPA 68, "Standard on Explosion Protection by Deflagration Venting"; NFPA 77, "Recommended Practice on Static Electricity" and other standards as the need exists.

Conditions for safe storage, including any incompatibilities: Store cool and dry, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use.

SECTION 8: Exposure controls / personal protection

Control parameters:

Occupational exposure limits (OEL):

Chemical Name

D&C Red No. 6 Barium Lake
Barium sulfate

Resin acids and rosin acids, barium salts

Chemical Name

ACGIH - TWA/Ceiling

N/E
5 mg/m³ TWA (inhalable particulate matter,
particulate matter)
N/E

OSHA - PEL

OSHA - STEL

ACGIH - STEL

N/E
N/E

N/E
OSHA - Ceiling

Mexico

SDS Name: D and C Red 6 Barium Lake

Chemical Name	OSHA - PEL	OSHA - STEL	OSHA - Ceiling	Mexico
D&C Red No. 6 Barium Lake	N/E	N/E	N/E	N/E
Barium sulfate	15 mg/m3 TWA (total dust), 5 mg/m3 TWA (respirable fraction)	N/E	N/E	N/E
Resin acids and rosin acids, barium salts	N/E	N/E	N/E	N/E

N/E=Not established (no exposure limits established for the listed substances for listed country/region/organization).

PNOS: ACGIH has recommended the following exposure limits for Particulates (insoluble or poorly soluble) not otherwise specified (PNOS): 10 mg/m3 TWA (inhalable particles), 3 mg/m3 TWA (respirable particles). OSHA exposure limits for Particulates not otherwise regulated are 15 mg/m3 TWA (total dust) and 5 mg/m3 TWA (respirable fraction).

Exposure controls:

Appropriate engineering controls: Always provide effective general and, when necessary, local exhaust ventilation to draw dust away from workers to prevent routine inhalation. Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Eliminate ignition sources (e.g., sparks, static buildup, excessive heat, etc.). Prohibit flow of powder or dust through non-conductive ducts, vacuum hoses, or pipes, etc. Bond, ground, and properly vent conveyors, dust control devices and other transfer equipment. (Ventilation guidelines/techniques may be found in publications such as Industrial Ventilation: American Conference of Governmental Industrial Hygienists, 1330 Kemper Meadow Drive, Cincinnati, OH, 45240-1634, USA.) (<http://www.acgih.org/home.htm>).

Individual protection measures, such as personal protective equipment (PPE):

Eye/face protection: Wear eye protection.

Skin and body protection: Wear chemical resistant (impervious) gloves. Use good laboratory/workplace procedures including personal protective clothing: labcoat, safety glasses and protective gloves.

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment. If inhalation of dust cannot be avoided, wear an approved particulate respirator. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR).

Further information: Eyewash fountains and safety showers are recommended in the work area.

SECTION 9: Physical and chemical properties

Form:	Powder	pH:	Not Available
Appearance:	Red-Orange	Relative density:	Not Available
Odor:	None	Partition coefficient (n-octanol/water):	Not Available
Odor threshold:	Not Available	% Volatile by weight:	Not Available
Solubility in water:	Insoluble	VOC:	Not Available
Evaporation rate:	Not Available	Boiling point °C:	Not Applicable
Vapor pressure:	Not Available	Boiling point °F:	Not Applicable
Vapor density:	Not Available	Flash point:	Not Applicable
Viscosity:	Not Applicable	Auto-ignition temperature:	Not Available
Melting point/Freezing point:	Not Available	Flammability (solid, gas):	Not flammable (may form combustible dust-air mixtures)
Oxidizing properties:	Not oxidizing	Flammability or explosive limits:	LFL/LEL Not Available
Explosive properties:	Not explosive		UFL/UEL Not Available
Decomposition temperature:	Not Available		

Other information: Amounts specified are typical and do not represent a specification.

SECTION 10: Stability and reactivity

Reactivity: None known.

Chemical stability: This product is stable.

SDS Name: D and C Red 6 Barium Lake

Possibility of hazardous reactions: Hazardous polymerization will not occur.

Conditions to avoid: Avoid dust formation.

Incompatible materials: Avoid strong acids, bases, and oxidizing agents.

Hazardous decomposition products: Oxides of carbon, oxides of nitrogen, oxides of sulfur. Oxides of barium.

SECTION 11: Toxicological information

Information on likely routes of exposure:

General: Caution must be exercised through the prudent use of protective equipment and handling procedures to minimize exposure. Repeated and prolonged inhalation of barium and insoluble barium compounds fumes or dust may cause a benign pneumoconiosis called baritosis.

Eyes: Solid particles on the eye (powder/dust) may cause pain and be accompanied by irritation.

Skin: May cause allergic skin reaction. Repeated or prolonged skin contact may cause irritation.

Inhalation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Ingestion: Ingestion may cause irritation.

Symptoms/effects, acute and delayed: Asthma, Irritation, Shortness of breath, Skin contact may discolor skin due to pigment

Acute toxicity information: Not classified (based on available data, the classification criteria are not met). No toxicity studies have been conducted on this product. ATEMix (oral): >2000 mg/kg. ATEMix (inhal.): >5 mg/L, 4 hours.

<u>Chemical Name</u>	<u>Inhalation LC50</u>	<u>Species</u>	<u>Oral LD50</u>	<u>Species</u>	<u>Dermal LD50</u>	<u>Species</u>
D&C Red No. 6 Barium Lake	>5 mg/L (4 hours, dust, similar materials)	Rat/ adult	>2000 mg/kg (similar materials)	Rat/ adult	N/E	N/E
Barium sulfate	N/E	N/E	>15000 mg/kg	Rat/ adult	>2000 mg/kg (similar materials)	Rat/ adult
Resin acids and rosin acids, barium salts	N/E	N/E	N/E	N/E	N/E	N/E

Skin corrosion/irritation: Not classified (based on available data, the classification criteria are not met).

<u>Chemical Name</u>	<u>Skin irritation</u>	<u>Species</u>
D&C Red No. 6 Barium Lake	Non-irritant	Similar materials
Barium sulfate	Non-irritant	In-Vitro
Resin acids and rosin acids, barium salts	N/E	N/E

Serious eye damage/irritation: Not classified (based on available data, the classification criteria are not met).

<u>Chemical Name</u>	<u>Eye irritation</u>	<u>Species</u>
D&C Red No. 6 Barium Lake	Non-irritant	Similar materials
Barium sulfate	Non-irritant	Rabbit/ adult
Resin acids and rosin acids, barium salts	N/E	N/E

Respiratory or skin sensitization: Respiratory sensitization (Category 1). Skin sensitization (Category 1).

<u>Chemical Name</u>	<u>Skin sensitisation</u>	<u>Species</u>
D&C Red No. 6 Barium Lake	Non-sensitizer	Similar material(s)
Barium sulfate	Non-sensitizer	Mouse/Local lymph node assay
Resin acids and rosin acids, barium salts	Sensitizer	Similar material(s)

Carcinogenicity: Not classified.

Carcinogenic status: The components of this mixture are not known to be listed or regulated by IARC (Group 1 or 2), NTP, OSHA or ACGIH.

Germ cell mutagenicity: Not classified.

Reproductive toxicity: Not classified.

Specific target organ toxicity (STOT) - single exposure: Not classified.

Specific target organ toxicity (STOT) - repeated exposure: Not classified.

SDS Name: D and C Red 6 Barium Lake

Aspiration hazard: Not classified (technical impossibility to obtain the data).

Other toxicity information: No additional information available.

SECTION 12: Ecological information

Ecotoxicity: No ecological testing has been conducted on this product.

<u>Chemical Name</u>	<u>Fish 96 hour LC50</u>	<u>Fish 96 hour LC50</u>	<u>Fish Chronic NOEC</u>
D&C Red No. 6 Barium Lake	>100 mg/L (similar materials)	N/E	N/E
Barium sulfate	>174 mg/L	N/E	N/E
Resin acids and rosin acids, barium salts	N/E	N/E	N/E
<u>Chemical Name</u>	<u>Invertebrates 48 hour EC50</u>	<u>Invertebrates 24 hour EC50</u>	<u>Invertebrates Chronic NOEC</u>
D&C Red No. 6 Barium Lake	>100 mg/L (similar materials)	N/E	N/E
Barium sulfate	14500 ug/L	N/E	N/E
Resin acids and rosin acids, barium salts	N/E	N/E	N/E
<u>Chemical Name</u>	<u>Algae 96 hour EC50</u>	<u>Algae 72 hour EC50</u>	<u>Algae Chronic NOEC</u>
D&C Red No. 6 Barium Lake	N/E	>100 mg/L (similar materials)	N/E
Barium sulfate	N/E	>100 mg/L	N/E
Resin acids and rosin acids, barium salts	N/E	N/E	N/E

Persistence and degradability:

<u>Chemical Name</u>	<u>Biodegradation</u>
D&C Red No. 6 Barium Lake	Not expected to be readily biodegradable
Barium sulfate	N/E
Resin acids and rosin acids, barium salts	N/E

Bioaccumulative potential:

<u>Chemical Name</u>	<u>Bioconcentration Factor (BCF)</u>	<u>Log Kow</u>
D&C Red No. 6 Barium Lake	N/E	N/E
Barium sulfate	N/E	N/E
Resin acids and rosin acids, barium salts	N/E	N/E

Mobility in soil:

<u>Chemical Name</u>	<u>Mobility in soil (Koc/Kow)</u>
D&C Red No. 6 Barium Lake	N/E
Barium sulfate	N/E
Resin acids and rosin acids, barium salts	N/E

Other adverse effects: No additional information available.

SECTION 13: Disposal considerations

HAZARDOUS WASTE: Dispose of waste (incinerate) in a RCRA permitted hazardous waste disposal facility. Barium: This product contains barium compounds (EPA Hazardous Waste No. D005, 40CFR261.24). You must determine by appropriate test if any waste exhibits the characteristic of TCLP Toxicity. Federal, state and local regulations where the waste material is generated, treated, and/or disposed of must be examined to verify the appropriate waste classification.

See Section 8 for recommendations on the use of personal protective equipment.

SECTION 14: Transport information

The information below is provided to assist in documentation. It may supplement the information on the package. The package in your possession may carry a different version of the label depending on the date of manufacture. Depending on inner packaging quantities and packaging instructions, it may be subject to specific regulatory exceptions.

UN number: N/A

UN proper shipping name:

Not regulated - See Bill of Lading for Details

Transport hazard class(es):

U.S. DOT hazard class: N/A

Canada TDG hazard class: N/A

Europe ADR/RID hazard class: N/A

IMDG Code (ocean) hazard class: N/A

SDS Name: D and C Red 6 Barium Lake

ICAO/IATA (air) hazard class: N/A

A "N/A" listing for the hazard class indicates the product is not regulated for transport by that regulation.

Packing group: N/A

Environmental hazards:

Marine pollutant: Not Applicable

Hazardous substance (USA): Not Applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code:

Not Applicable

Special precautions for user: Not Applicable

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question:

U.S. federal and state regulations/legislation:

This SDS has been prepared in accordance with the hazard criteria of the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

U.S. Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Reportable Quantity (RQ):

Not Applicable

U.S. Superfund Amendments and Reauthorization Act (SARA) - SARA Section 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372:

D&C Red No. 6 Barium Lake

Resin acids and rosin acids, barium salts

U.S. TSCA Section 12(b) Export Notification:

This product is not subject to TSCA 12(b) reporting requirements.

California Proposition 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

None known to be present or none in reportable amounts for occupational exposure as per OSHA's approval of the California Hazard Communication Standard, Federal Register, page 31159 ff, 6 June 1997.

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards:

None known to be present or none in reportable amounts for occupational exposure as per OSHA's approval of the California Hazard Communication Standard, Federal Register, page 31159 ff, 6 June 1997.

Notes: No additional information

Canada regulations/legislation:

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

Notes: No additional information

Mexico regulations/legislation:

This SDS contains the information required by NOM-018-STPS-2000 Workplace Hazardous Chemical Substances Communication and Identification Standard.

Notes: No additional information

Chemical inventories:

<u>Regulation</u>	<u>Status</u>
Australian Inventory of Chemical Substances (AICS):	Y
Canadian Domestic Substances List (DSL):	Y
Canadian Non-Domestic Substances List (NDSL):	N
China Inventory of Existing Chemical Substances (IECSC):	Y

Regulation**Status**

European Inventory of Existing Chemical Substances (EINECS):

Y

European List of Notified Chemical Substances (ELINCS):

N

Japan Existing and New Chemical Substances (ENCS):

N

Japan Industrial Safety and Health Law (ISHL):

N

Korean Existing and Evaluated Chemical Substances (KECL):

Y

New Zealand Inventory of Chemicals (NZIoC):

Y

Philippines Inventory of Chemicals and Chemical Substances (PICCS):

Y

Taiwan Inventory of Existing Chemicals:

Y

U.S. Toxic Substances Control Act (TSCA):

Y

A "Y" listing indicates all intentionally added components are either listed or are otherwise compliant with the regulation. A "N" listing indicates that for one or more components: 1) there is no listing on the public inventory; 2) no information is available; or 3) the component has not been reviewed. A "Y" for New Zealand may mean that a qualified group standard may exist for the components in this product.

Europe REACH (EC) 1907/2006: Not all applicable components are pre-registered or registered. REACH is only relevant to substances either manufactured or imported into the EU. REACH information regarding this product is provided for informational purposes only. Each Legal Entity may have differing REACH obligations, depending on their place in the supply chain. For material manufactured outside of the EU, the importer of record must understand and meet their specific obligations under the regulation.

SECTION 16: Other information**SDS Revision date:** 2016-11-04**HMIS (Hazardous Materials Identification System) Ratings:****Health:** 2* **Flammability:** 1 **Physical hazard:** 0 **Personal Protection:** X**NFPA (National Fire Protection Association) Ratings:****Health:** 2 **Flammability:** 1 **Instability:** 0

Key: 0=Insignificant; 1=Slight; 2=Moderate; 3=High; 4=Extreme. An asterisk appearing after the HMIS Health numerical rating denotes a chronic hazard.

Hazardous Materials Identification System (HMIS), National Paint and Coating Association, rating applies to product "as packaged" (i.e., ambient temperature). Ratings are based upon HMIS® III and NFPA 704 (2007). An asterisk appearing after the HMIS Health® III numerical rating denotes a chronic hazard. National Fire Protection Association (NFPA) rating identifies the severity of hazards of material during a fire emergency (i.e., "on fire").

Legend:

* : Trademark owned by Dystar L.P.

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA WEEL: American Industrial Hygiene Association (AIHA) Workplace Environmental Exposure Level (WEEL)

N/A: Not Applicable

N/E: None Established

STEL: Short Term Exposure Limit

TWA: Time Weighted Average (exposure for 8-hour workday)

Users Responsibility/Disclaimer of Liability:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.

This bulletin cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to develop appropriate work practice guidelines and employee instructional programs for your operation.

Safety Data Sheet Preparer:

SDS Name: D and C Red 6 Barium Lake

Product Compliance Department