



Safety Data Sheet (SDS)

North American

Revision date: 2016-12-01

SECTION 1: Identification

Product identifiers:

Product trade name: Phthalo Blue RS NCNF
Company product number: 42A305
Other means of identification: Not Available

Recommended use of the chemical and restrictions on use:

Uses: Pigment dispersion
Restrictions on use: None identified

Details of the supplier:

Manufacturer/Supplier: Dystar L.P.
Pine Brook III
9844 Southern Pine Blvd
Charlotte, NC 28273, USA
Telephone: (800) 439-7827
FAX: (704) 561-3098

Emergency telephone number:

Chemtrec (24 hours): USA: 1-800-424-9300; International: +001-703-527-3887.

SECTION 2: Hazard(s) identification

Information in accordance with U.S. 29 CFR 1910.1200 (Hazcom 2012) and Canada Hazardous Products Regulations (WHMIS 2015):

Classification of the product:

Flammable Liquid, category 3
Skin Sensitizer, category 1
Carcinogenicity, category 2

Label elements:

Hazard pictogram(s):



Signal word:

Warning

Hazard statements:

H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.

Precautionary statements:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: Use carbon dioxide, dry chemical, foam to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local, regional and international regulations.
Supplemental information: 45-55 percent of the mixture consists of ingredient(s) of unknown acute toxicity. Contains 45-55 % of components with unknown hazards to the aquatic environment. Skin may discolor due to contact with pigment.
Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS) - Annex III.
Regulations in individual countries/regions may determine which statements are required on the product label. See product label for specifics.

Hazards not otherwise classified:

Physical hazards not otherwise classified: No Additional Information

Health hazards not otherwise classified: No Additional Information

See Section 11 for toxicological information.

SECTION 3: Composition/information on ingredients

Mixture:

<u>CAS-No.</u>	<u>Chemical Name</u>
0064742-88-7	Solvent naphtha (petroleum), medium aliphatic
0000147-14-8	C.I. Pigment blue 15 (Copper phthalocyanine pigment)
0000096-29-7	2-Butanone oxime (MEKO)

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits. Exact percentage values for components are proprietary in accordance with 29 CFR 1910.1200(i).

SECTION 4: First-aid measures

Description of first aid measures:

General: If irritation or other symptoms occur or persist from any route of exposure, remove the affected individual from the area: see a physician/get medical attention.

Eye contact: Immediately flush eyes with plenty of clean water for an extended time, not less than fifteen (15) minutes. Flush longer if there is any indication of residual chemical in the eye. Ensure adequate flushing of the eyes by separating the eyelids with fingers and roll eyes in a circular motion. If eye irritation persists: Get medical advice/attention.

Skin contact: Immediately remove contaminated clothing and shoes. Wash the affected area with plenty of soap and water until no evidence of the chemical remains (at least 15-20 minutes). Launder clothing before reuse. If skin irritation occurs: Get medical advice/attention.

Inhalation: If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion: Do not induce vomiting. Extreme care must be taken to prevent aspiration. If victim is unconscious and breathing, position the person on their side to prevent aspiration. Never give anything by mouth to an unconscious person. Rinse out the mouth with water. Get medical attention immediately.

Protection of first aid responders: Wear proper personal protective clothing and equipment.

Most important symptoms and effects, both acute and delayed: Dizziness, Drowsiness, Headache, Irritation, Nausea, Skin contact may discolor skin due to pigment. Pre-existing skin problems may be aggravated by prolonged or repeated contact. See section 11 for additional information.

Indication of any immediate medical attention and special treatment needed, if necessary: Treat symptomatically.

SECTION 5: Fire-fighting measures

NFPA flammability class: II

Extinguishing media:

Suitable: NFPA Class II (Combustible Liquid): Use water spray, ABC dry chemical, "alcohol" foam or CO₂. Use water to keep fire-exposed containers cool. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect emergency responders attempting to stop a leak. Water spray may be used to flush spills away from exposures and to dilute spills to nonflammable mixtures.

Unsuitable: Do not use direct water stream. May spread fire.

Special hazards arising From the chemical:

Unusual fire/explosion hazards: Issue warning: combustible liquid. Eliminate all ignition sources. Ventilate the area. If spill is large, be prepared to isolate the hazard area. Deny access to the spill area to persons who are not involved in the cleanup and/or who have not been properly trained in spill management of hazardous/flammable liquids. Vapors may explode if ignited in an enclosed area. Run off to sewer may cause a fire or explosion hazard. Protect product from flames of any kind; maintain proper clearance when using heat devices, etc. Closed container may rupture (due to build up in pressure) when exposed to extreme heat. Product may burn if an ignition source is present. Gives off volatile vapors that are heavier than air and may travel along the ground or may be moved by ventilation and ignited by flame, sparks, heaters, or other ignition sources at distant locations (flashback potential).

Hazardous combustion products: Irritating or toxic substances will be emitted upon burning, combustion or decomposition. See section 10 (Hazardous decomposition products) for additional information.

Special protective equipment and precautions for fire-fighters: Use water/water spray to keep fire-exposed containers cool. Water spray may be used to flush spills away from exposures and to dilute spills to non-combustible mixtures. Do not flush combustible liquids into sewer as a fire or vapor explosion hazard may result. Never direct a hose stream directly onto a burning flammable/combustible liquid. Solid or straight hose stream will cause fire to spread if directed onto a burning spill or into an open container of burning liquid. Wear self-contained breathing apparatus (SCBA) equipped with a full facepiece and operated in a pressure-demand mode (or other positive pressure mode) and approved protective clothing. Personnel without suitable respiratory protection must leave the area to prevent significant exposure to hazardous gases from combustion, burning or decomposition. In an enclosed or poorly ventilated area, wear SCBA during cleanup immediately after a fire as well as during the attack phase of firefighting operations.

See section 9 for additional information.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures: See Section 8 for recommendations on the use of personal protective equipment. Eliminate ignition sources. Ventilate areas of spill. Personal Protective Equipment must be worn.

Environmental precautions: Do not flush liquid into public sewer, water systems or surface waters.

Methods and materials for containment and cleaning up: Contain by diking with sand, earth or other non-combustible material. Wear proper personal protective clothing and equipment. Absorb spill with an inert material. Place into labeled, closed container; store in safe location to await disposal. Change contaminated clothing and launder before reuse.

SECTION 7: Handling and storage

Precautions for safe handling: As with any chemical product, use good laboratory/workplace procedures. Do not cut, puncture, or weld on or near the container. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Provide eyewash fountains and safety showers in the work area. Bond and ground all containers when transferring chemical. Eliminate ignition sources (e.g., sparks, static buildup, excessive heat, etc.). Use spark-proof tools and equipment. Vapors may travel to distant ignition sources.

Conditions for safe storage, including any incompatibilities: Store in combustible storage area and away from heat and open flame. Keep away from heat, sparks and open flames. Store under well-ventilated conditions. Keep container upright, when not in use, to prevent leakage. Avoid storing containers in direct sunlight as vapors may accumulate in the head space creating pressure. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep

container closed when not in use. Emptied container may contain residual vapors or liquid which may ignite or explode. Do not reuse empty container without commercial cleaning or reconditioning. Bond and ground all containers when transferring chemical.

SECTION 8: Exposure controls / personal protection

Control parameters:

Occupational exposure limits (OEL):

<u>Chemical Name</u>	<u>ACGIH - TWA/Ceiling</u>	<u>ACGIH - STEL</u>		
Solvent naphtha (petroleum), medium aliphatic	5 mg/m3 TWA (inhalable particulate matter)	N/E		
C.I. Pigment blue 15 (Copper phthalocyanine pigment)	1 mg/m3 TWA (dust and mist)(as Cu)	N/E		
2-Butanone oxime (MEKO)	N/E	N/E		
<u>Chemical Name</u>	<u>OSHA - PEL</u>	<u>OSHA - STEL</u>	<u>OSHA - Ceiling</u>	<u>Mexico</u>
Solvent naphtha (petroleum), medium aliphatic	5 mg/m3 TWA (oil mist)	N/E	N/E	5 mg/m3 TWA, 10 mg/m3 STEL (oil mist, mineral)
C.I. Pigment blue 15 (Copper phthalocyanine pigment)	N/E	N/E	N/E	N/E
2-Butanone oxime (MEKO)	N/E	N/E	N/E	N/E
<u>Chemical Name</u>	<u>AIHA - WEEL</u>			
2-Butanone oxime (MEKO)	10 ppm TWA (Skin sensitizer)			

N/E=Not established (no exposure limits established for the listed substances for listed country/region/organization).

Contains mineral oil. Under conditions which may generate mists, observe the ACGIH 5 mg/m3 TWA (inhalable fraction).

Exposure controls:

Appropriate engineering controls: Always provide effective general and, when necessary, local exhaust ventilation to draw spray, aerosol, fume, mist and vapor away from workers to prevent routine inhalation. Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Eliminate ignition sources (e.g., sparks, static buildup, excessive heat, etc.). (Ventilation guidelines/techniques may be found in publications such as Industrial Ventilation: American Conference of Governmental Industrial Hygienists, 1330 Kemper Meadow Drive, Cincinnati, OH, 45240-1634, USA.) (<http://www.acgih.org/home.htm>).

Individual protection measures, such as personal protective equipment (PPE):

Eye/face protection: Safety glasses or goggles required.

Skin and body protection: Wear chemical resistant (impervious) gloves. Use good laboratory/workplace procedures including personal protective clothing: labcoat, safety glasses and protective gloves.

Respiratory protection: Wear an approved respirator (e.g., an organic vapor respirator, a full face air purifying respirator for organic vapors, or a self-contained breathing apparatus) whenever exposure to aerosol, mist, spray, fume or vapor exceed the applicable exposure limit(s) of any chemical substance listed in this SDS. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR).

Further information: Eyewash fountains and safety showers are recommended in the work area.

SECTION 9: Physical and chemical properties

Form:	Dispersion	pH:	Not Available
Appearance:	Blue	Relative density:	1.00
Odor:	Mineral Spirits	Partition coefficient (n-octanol/water):	Not Available
Odor threshold:	Not Available	% Volatile by weight:	44.7%
Solubility in water:	Insoluble	VOC:	44.7% Calculated
Evaporation rate:	Slower than n-butyl acetate	Boiling point °C:	Not Available
Vapor pressure:	Not Available	Boiling point °F:	Not Available
Vapor density:	Heavier than air	Flash point:	51 °C (124 °F)
Viscosity:	Not Available	Auto-ignition temperature:	Not Available
Melting point/Freezing point:	Not Available	Flammability (solid, gas):	Not Applicable (liquid)
Oxidizing properties:	Not oxidizing	Flammability or explosive limits:	LFL/LEL 1% (Solvent)
Explosive properties:	Not explosive		UFL/UEL 7% (Solvent)

SDS Name: Phthalo Blue RS NCNF

Decomposition temperature: Not Available

Other information: Amounts specified are typical and do not represent a specification.

SECTION 10: Stability and reactivity

Reactivity: None known.

Chemical stability: This product is stable.

Possibility of hazardous reactions: Hazardous polymerization will not occur.

Conditions to avoid: Excessive heat and ignition sources.

Incompatible materials: Avoid strong acids, bases, and oxidizing agents.

Hazardous decomposition products: Oxides of carbon, oxides of nitrogen, oxides of copper. Hydrocarbons.

SECTION 11: Toxicological information

Information on likely routes of exposure:

General: Caution must be exercised through the prudent use of protective equipment and handling procedures to minimize exposure. Overexposure may cause central nervous system depression.

Eyes: May cause eye irritation.

Skin: May cause skin irritation. May cause allergic skin reaction. Repeated or prolonged contact may cause irritation, dermatitis, defatting and drying or cracking of the skin.

Inhalation: Inhalation of high vapor concentration may cause headache, drowsiness and irritation of the eyes and respiratory tract.

Ingestion: Ingestion may cause abdominal discomfort, nausea, and diarrhea.

Symptoms/effects, acute and delayed: Dizziness, Drowsiness, Headache, Irritation, Nausea, Skin contact may discolor skin due to pigment

Acute toxicity information: Not classified (based on available data, the classification criteria are not met). No toxicity studies have been conducted on this product. ATEmix (oral): >5000 mg/kg. ATEmix (dermal): >2000 mg/kg. ATEmix (inhal.): >5 mg/L, 4 hours. The physical, chemical and toxicological properties of component(s) of this mixture may have not been fully determined.

<u>Chemical Name</u>	<u>Inhalation LC50</u>	<u>Species</u>	<u>Oral LD50</u>	<u>Species</u>	<u>Dermal LD50</u>	<u>Species</u>
Solvent naphtha (petroleum), medium aliphatic	>5.28 mg/L (4 hours)	Rat/ adult	>5000 mg/kg	Rat/ adult	>3000 mg/kg	Rabbit/ adult
C.I. Pigment blue 15 (Copper phthalocyanine pigment)	N/E	N/E	>5000 mg/kg	Rat/ adult	N/E	N/E
2-Butanone oxime (MEKO)	>4.83 mg/L (4 hours, vapor)	Rat/ adult	2326 mg/kg	Rat/ adult male	>1000 mg/kg	Rabbit/ adult

Skin corrosion/irritation: Not classified (based on available data, the classification criteria are not met).

<u>Chemical Name</u>	<u>Skin irritation</u>	<u>Species</u>
Solvent naphtha (petroleum), medium aliphatic	N/E	N/E
C.I. Pigment blue 15 (Copper phthalocyanine pigment)	Non-irritant	Rabbit/ adult
2-Butanone oxime (MEKO)	Slight to moderate irritant	Rabbit/ adult

Serious eye damage/irritation: Not classified (based on available data, the classification criteria are not met).

<u>Chemical Name</u>	<u>Eye irritation</u>	<u>Species</u>
Solvent naphtha (petroleum), medium aliphatic	N/E	N/E
C.I. Pigment blue 15 (Copper phthalocyanine pigment)	Non-irritant	Rabbit/ adult
2-Butanone oxime (MEKO)	Severe irritant	Rabbit/ adult

Respiratory or skin sensitization: Skin sensitization (Category 1).

<u>Chemical Name</u>	<u>Skin sensitisation</u>	<u>Species</u>
Solvent naphtha (petroleum), medium aliphatic	N/E	N/E
C.I. Pigment blue 15 (Copper phthalocyanine pigment)	Non-sensitizer	Human
2-Butanone oxime (MEKO)	Sensitizer	Guinea Pig/ adult

Carcinogenicity: Suspected of causing cancer (Category 2). 2-BUTANONE OXIME (MEKO): Liver carcinomas were observed in a lifetime inhalation study in which mice and rats were exposed to MEKO 6 hrs/day, 5 days/week for 18 months and 26 months, respectively. These carcinomas were statistically increased in males at a MEKO concentration of 375 ppm. In addition, degenerative effects on the olfactory epithelium of the nasal passages occurred in a concentration related manner in males and females of both species at MEKO concentrations of 15, 75, and 375 ppm.

Carcinogenic status: The components of this mixture are not known to be listed or regulated by IARC (Group 1 or 2), NTP, OSHA or ACGIH. 2-BUTANONE OXIME (MEKO): European CLP GHS categorization of Carcinogenicity 2-Suspected of causing cancer; not listed or regulated by IARC, NTP or ACGIH.

Germ cell mutagenicity: Not classified. 2-BUTANONE OXIME (MEKO): MEKO is not considered mutagenic based on several in vitro and in vivo studies.

Reproductive toxicity: Not classified.

Specific target organ toxicity (STOT) - single exposure: Not classified.

Specific target organ toxicity (STOT) - repeated exposure: Not classified. 2-BUTANONE OXIME (MEKO): In a subchronic oral toxicity animal study, MEKO produced an adverse effect upon red blood cells (anemia). This was found for all dose levels tested. In an acute dermal animal study, 200 mg/kg caused mild hematologic (blood) effects. No effects were seen at 20 mg/kg.

Aspiration hazard: Not classified (based on available data, the classification criteria are not met).

Other toxicity information: 2-BUTANONE OXIME (MEKO) absorption through the skin, inhalation or ingestion may produce blood effects, reducing the blood's ability to transport oxygen (methemoglobinemia and anemia). Male rats and mice exposed to MEKO throughout their lifetimes developed liver tumors.

SECTION 12: Ecological information

Ecotoxicity: No ecological testing has been conducted on this product.

<u>Chemical Name</u>	<u>Fish 96 hour LC50</u>	<u>Fish 96 hour LC50</u>	<u>Fish Chronic NOEC</u>
Solvent naphtha (petroleum), medium aliphatic	800 mg/L	N/E	N/E
C.I. Pigment blue 15 (Copper phthalocyanine pigment)	N/E	N/E	N/E
2-Butanone oxime (MEKO)	>100 mg/L	760 mg/L	100 mg/L (14 days, mortality)
<u>Chemical Name</u>	<u>Invertebrates 48 hour EC50</u>	<u>Invertebrates 24 hour EC50</u>	<u>Invertebrates Chronic NOEC</u>
Solvent naphtha (petroleum), medium aliphatic	>100 mg/L	N/E	N/E
C.I. Pigment blue 15 (Copper phthalocyanine pigment)	N/E	N/E	N/E
2-Butanone oxime (MEKO)	201 mg/L	N/E	>=100 mg/L (21 days, reproduction)
<u>Chemical Name</u>	<u>Algae 96 hour EC50</u>	<u>Algae 72 hour EC50</u>	<u>Algae Chronic NOEC</u>
Solvent naphtha (petroleum), medium aliphatic	450 mg/L	N/E	N/E
C.I. Pigment blue 15 (Copper phthalocyanine pigment)	N/E	N/E	N/E
2-Butanone oxime (MEKO)	83 mg/L	11.8 mg/L	2.56 mg/L (72 hours, growth rate)

Persistence and degradability: No specific information available.

<u>Chemical Name</u>	<u>Biodegradation</u>
Solvent naphtha (petroleum), medium aliphatic	Readily biodegradable
C.I. Pigment blue 15 (Copper phthalocyanine pigment)	Not readily biodegradable
2-Butanone oxime (MEKO)	Inherently biodegradable (OECD 302B)

Bioaccumulative potential: No specific information available.

<u>Chemical Name</u>	<u>Bioconcentration Factor (BCF)</u>	<u>Log Kow</u>
Solvent naphtha (petroleum), medium aliphatic	N/E	4.2-6.7

SDS Name: Phthalo Blue RS NCNF

Chemical Name	Bioconcentration Factor (BCF)	Log Kow
C.I. Pigment blue 15 (Copper phthalocyanine pigment)	0.33-11 (OECD 305C)	6.6 (calculated)
2-Butanone oxime (MEKO)	0.5-0.6 (OECD305C)	0.63

Mobility in soil: No specific information available.

Chemical Name	Mobility in soil (Koc/Kow)
Solvent naphtha (petroleum), medium aliphatic	N/E
C.I. Pigment blue 15 (Copper phthalocyanine pigment)	67
2-Butanone oxime (MEKO)	N/E

Other adverse effects: No additional information available.

SECTION 13: Disposal considerations

HAZARDOUS WASTE: Dispose of waste (incinerate) in a RCRA permitted hazardous waste disposal facility. Flash point below 140°F (60°C) - EPA Hazardous Waste No.: D001. Federal Resource Conservation and Recovery Act (RCRA), 40CFR261.21.

See Section 8 for recommendations on the use of personal protective equipment.

SECTION 14: Transport information

The information below is provided to assist in documentation. It may supplement the information on the package. The package in your possession may carry a different version of the label depending on the date of manufacture. Depending on inner packaging quantities and packaging instructions, it may be subject to specific regulatory exceptions.

UN number: UN1268

UN proper shipping name:

Petroleum Distillates, N.O.S.

Transport hazard class(es):

U.S. DOT hazard class: 3

Canada TDG hazard class: 3

Europe ADR/RID hazard class: 3

IMDG Code (ocean) hazard class: 3

ICAO/IATA (air) hazard class: 3

A "N/A" listing for the hazard class indicates the product is not regulated for transport by that regulation.

Packing group: III

Environmental hazards:

Marine pollutant: Not Applicable

Hazardous substance (USA): Not Applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code:

Not Applicable

Special precautions for user: Not Applicable

Notes: For surface shipment within the United States, flammable liquids with a flash point of 100-141 F (38-60 C) may be reclassified: In containers of 119 gallons capacity or less: NOT REGULATED. In containers of more than 119 gallons capacity: COMBUSTIBLE LIQUID.

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question:

U.S. federal and state regulations/legislation:

This SDS has been prepared in accordance with the hazard criteria of the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

U.S. Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Reportable Quantity (RQ):

Not Applicable

U.S. Superfund Amendments and Reauthorization Act (SARA) - SARA Section 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372:

None known

U.S. TSCA Section 12(b) Export Notification:

This product is not subject to TSCA 12(b) reporting requirements.

California Proposition 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

None known to be present or none in reportable amounts for occupational exposure as per OSHA's approval of the California Hazard Communication Standard, Federal Register, page 31159 ff, 6 June 1997.

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards:

None known to be present or none in reportable amounts for occupational exposure as per OSHA's approval of the California Hazard Communication Standard, Federal Register, page 31159 ff, 6 June 1997.

Notes: No additional information

Canada regulations/legislation:

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

Notes: 2-BUTANONE OXIME (MEKO): Listed on Canadian Environmental Protection Act - Schedule 1 - List of Toxic Substances.

Mexico regulations/legislation:

This SDS contains the information required by NOM-018-STPS-2000 Workplace Hazardous Chemical Substances Communication and Identification Standard.

Notes: No additional information

Chemical inventories:

<u>Regulation</u>	<u>Status</u>
Australian Inventory of Chemical Substances (AICS):	Y
Canadian Domestic Substances List (DSL):	Y
Canadian Non-Domestic Substances List (NDSL):	N
China Inventory of Existing Chemical Substances (IECSC):	Y
European Inventory of Existing Chemical Substances (EINECS):	Y
European List of Notified Chemical Substances (ELINCS):	N
Japan Existing and New Chemical Substances (ENCS):	N
Japan Industrial Safety and Health Law (ISHL):	N
Korean Existing and Evaluated Chemical Substances (KECL):	Y
New Zealand Inventory of Chemicals (NZIoC):	Y
Philippines Inventory of Chemicals and Chemical Substances (PICCS):	Y
Taiwan Inventory of Existing Chemicals:	N
U.S. Toxic Substances Control Act (TSCA):	Y

A "Y" listing indicates all intentionally added components are either listed or are otherwise compliant with the regulation. A "N" listing indicates that for one or more components: 1) there is no listing on the public inventory; 2) no information is available; or 3) the component has not been reviewed. A "Y" for New Zealand may mean that a qualified group standard may exist for the components in this product.

Europe REACH (EC) 1907/2006: Not all applicable components are pre-registered or registered. REACH is only relevant to substances either manufactured or imported into the EU. REACH information regarding this product is provided for informational purposes only. Each Legal Entity may have differing REACH obligations, depending on their place in the supply chain. For material manufactured outside of the EU, the importer of record must understand and meet their specific obligations under the regulation.

SECTION 16: Other information

SDS Revision date: 2016-12-01

HMIS (Hazardous Materials Identification System) Ratings:

Health: 2* **Flammability:** 2 **Physical hazard:** 0 **Personal Protection:** X

NFPA (National Fire Protection Association) Ratings:

Health: 2 **Flammability:** 2 **Instability:** 0

Key: 0=Insignificant; 1=Slight; 2=Moderate; 3=High; 4=Extreme. An asterisk appearing after the HMIS Health numerical rating denotes a chronic hazard.

Hazardous Materials Identification System (HMIS), National Paint and Coating Association, rating applies to product "as packaged" (i.e., ambient temperature). Ratings are based upon HMIS® III and NFPA 704 (2007). An asterisk appearing after the HMIS Health® III numerical rating denotes a chronic hazard. National Fire Protection Association (NFPA) rating identifies the severity of hazards of material during a fire emergency (i.e., "on fire").

Legend:

* : Trademark owned by Dystar L.P.

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA WEEL: American Industrial Hygiene Association (AIHA) Workplace Environmental Exposure Level (WEEL)

N/A: Not Applicable

N/E: None Established

STEL: Short Term Exposure Limit

TWA: Time Weighted Average (exposure for 8-hour workday)

Users Responsibility/Disclaimer of Liability:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.

This bulletin cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to develop appropriate work practice guidelines and employee instructional programs for your operation.

Safety Data Sheet Preparer:

Product Compliance Department