oncan			SDS Page No	
	SAFETY DATA SHEET			1/4
	According to Com	mission Regulation (EU) 2020/878	of 18 June 2020.	
			RELEASE DATE	15.10.2018
ATERIAL NAME EPLAMID 6 GFR 35 BK Q2D003 REVISION No/DATE			1 / 24.04.2023	
ECTION 1. IDENTIFICATION	OF THE SUBSTANCE/MIXTURE AND	OF THE COMPANY/UNDERTAKING		
.1 Product identifier				
Trade Name	EPLAMID 6 GFR 35	BK Q2D003		
Material Infor	mation Polyamide 6	Glass Fiber Reinforced		
.2 Relevant identified uses o	f the substance or mixture and uses a	advised against		
Identified use	Plastic Material			
3 Details of the supplier of t	he safety data sheet			
Manufacturer	Epsan Plastik San. v	e Tic. A.Ş.		
Address	Demirtaş Organize S	Demirtaş Organize Sanayi Bölgesi A.O.S. Cd. No :16 / 16369 Bursa - TURKEY		
Telephone	+90 224 261 20 20	+90 224 261 20 20		
Fax	+90 224 261 27 18	+90 224 261 27 18		
Web	www.epsan.com.tr	www.epsan.com.tr		
E-mail	cra@epsan.com.tr	cra@epsan.com.tr		
1.4 Emergency telephone nur	nber Epsan: +90 224 26:	1 20 20		
ECTION 2. HAZARDS IDENT	FICATION			
2.1 Classification of the subst	ance or mixture			
Product Defini	tion Mixture			
Classification wa	s defined according to REGULATION (EC)	No 1272/2008.		
This product is r	ot classified as dangerous according to RE	GULATION (EC) No 1272/2008.		
2.2 Label elements				
	GULATION (EC) No 1272/2008 labelling is	not required.		
Signal word	Not available.			
Hazard statem	ent There is no known s	significant effect.		
Precautionary	statement Not applicable.			
2.3 Other hazards				

Persistent bioaccumulative and toxic (PBT) or very persistent very bioaccumulated (vPvB) evaluation is not availabe as chemical safety assessment is not required.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

3.2 Mixtures

CAS NO	CHEMICAL NAME	HAZARDS IDENTIFICATION
25038-54-4	Polyamide 6	Is not clasified as hazardous
65997-17-3	Glass Fiber	Is not clasified as hazardous

This product does not contain any additives or foreign substances required for product labeling and hazard classification according to REGULATION (EC) No 1272/2008, or includes quantities permitted in regulations.

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures

General;

Instantaneous penetration of granulated plastic into human organism is impossible.

The product is stable at normal conditions, not volatile.

Pre-intervention warning; contact with hot melt product may cause severe burns.

Inhalation of dust or powdered material, irritation may occur in the respiratory tract and eye irritation may occur.

Appropriate medical intervention should be done urgently if hot material contact with eye or skin.

Inhalation;

No hazard in normal use of product. Move any exposed person to fresh air at once.

Keep warm and at rest. If there is respiratory distress give oxygen.

If respiration stops or shows signs of failing, apply artificial respiration. Get medical attention.

In case the molten substance vapours penetrate the respiratory airways, do the following; Immediately move an exposed person to fresh air at once.

Keep warm and at rest. If there is respiratory distress give oxygen.

If respiration stops or shows signs of failing, apply artificial respiration. Get medical attention.

epsan

МАТ

According to Commission Regulation (EU) 2020/878 of 18 June 2020.

SAFETY DATA SHEET

TERIAL NAME EPLAMID 6 GFR 35 BK Q2D003 RELEASE DATE 15.10.2018 REVISION No./DATE 1/.24.04.2022				
			RELEASE DATE	15.10.2018
REVISION NO/DATE 1/24.04.2025			REVISION No/DATE	1 / 24.04.2023

Skin contact;

If molten material comes in contact with the skin, do not apply ice but cool under ice water or running stream of water. **DO NOT** attempt to remove the material from skin.Removal could result in severe tissue damage. Seek medical attention immediately.

Eye contact;

Rinse the eye immediately with plenty of water (low pressure) for at least 15 minutes. Remove contact lenses. Get medical attention.

Ingestion;

If swallowed, seek medical attention.

Do not induce vomiting unless directed to do so by medical personnel.

4.2 Most important symptoms and effects, both acute and delayed

There is no experience in humans that leads to acute or chronic damage.

4.3 Indication of any immediate medical attention and special treatment needed

No special treatment is required.

SECTION 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Water fog or fine spray, Dry chemical fire extinguishers, Carbon dioxide fire extinguishers, Foam. Use only fine spray or water fog for extinguishing plastic dust.

Unsuitable extinguishing media: Do not use water jets. Direct water jets on the burning product could cause a steam explosion and spread of the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

5.2 Special hazards arising from the substance or mixture

May be combustible at high temperature.

Combustion products: Carbon oxides (CO and CO2) and soot.

Combustion products may include thermo-oxidative degradation products: carbon oxides, formaldehyde, acetaltehyde, organic acids (acetic acid) and etc. Combustion products may be toxic and/or irritating.

5.3 Advice for firefighters

Soak thoroughly with water to cool and prevent re-ignition. If material is molten, do not apply direct water stream. Use fine water spray or foam. Cool surroundings with

water to localize fire zone. Hand held dry chemical or carbon dioxide extinguishers may be used for small fires.

Special protective equipments for firefighters: Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Take precautionary measures against static discharges.

Ensure adequate ventilation. Avoid dust generation. Avoid inhalation of dusts.

Spilled material may cause a slipping hazard.

In case of insufficient ventilation, wear suitable respiratory equipment.

6.2 Environmental precautions

Do not allow penetration of the product into water reservoirs, surface and ground water, sewer ducts and soil. Provide sealing of process equipment. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

Scattering of and its waste should be timely collected and disposed in specially designated areas.

Plastic wastes are non-toxic and are not to be neutralized.

6.3 Methods and material for containment and cleaning up

Collect in suitable and properly labelled containers. Minimize generation of dust during clean-up. Transfer to a container for disposal or recovery. Provide ventilation.

6.4 Reference to other sections

See section 8 for Personal Protective Equipment.

SDS Page No

2/4

epsan	SAFETY DATA SHEET	SDS Page No 3/4	
agile innovation for polymers According to Commission Regulation (EU) 2020/878 of 18 June 2020.			
According to commission Regulation (20) 2020/078 of 18 June 2020.			
MATERIAL NAME	EPLAMID 6 GFR 35 BK Q2D003	15.10.2018	
	REVISION No/DATE	1 / 24.04.2023	

SECTION 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition.

Take precautionary measures against static discharges. Provide thorough sealing and grounding of process equipment. Due to electrostatic properties of the material, grounding of silos and grounding of pneumatic transport equipment are obligatory.

Dust can be ignited by static discharge.

Pneumatic conveying and other mechanical handling operations can generate combustible dust.

Do not swallow. Avoid contact with eyes. Avoid prolonged or repeated contact with skin.

Workers should be protected from the possibility of contact with molten product.

Warning: Spilled granules will cause slipping and fall.

Do not eat, drink or smoke at the work place.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with good manufacturing practices. Keep away from heat, sparks and flame. Protect from direct sunlight. Store in a dry, well-ventilated area.

7.3 Specific end use(s)

Unknown.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Where engineering controls are indicated by use conditions or a potential for excessive exposure exists, the following traditional exposure control techniques may be used to effectively minimize employee exposures.

8.2 Exposure controls

Respiratory protection	Adequate ventilation at workplace is required.
Eye/face protection	Wear goggles giving complete protection to eyes (BS EN 166).
Skin Protection (Hand and Body)	Wear approved protective gloves (Nitrile rubber BS EN 374) If contact with hot product is anticipated, gloves should be heat-resistant and thermally insulated. Wear insulating gloves BS EN407 (heat). Wear apron or other protective clothing and antistatic boots.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties				
Form	Granules			
Colour	All colors			
Odour	Odourless			
15°C Water Solubillity	Non soluble			
Melting Temperature	220	°C		
Density at 23 °C	1,14 - 1,7	gr/cm ³		
Flame Retardency	> 300	°C		

9.2 Other information

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity

Stable under normal handling and storage conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Strong oxidant.

10.4 Conditions to avoid

There is no specific data.

10.5 Incompatible materials

There is no specific data.

10.6 Hazardous decomposition products

CO, HCN, NH3

epsan

MATERIAL NAME	EPLAMID 6 GFR 35 BK Q2D003	RELEASE DATE	15.10.2018
		REVISION No/DATE	1 / 24.04.2023

SAFETY DATA SHEET

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

The product is not toxic, is inert and	The product is not toxic, is inert and has no adverse affect on human health.			
Skin corrosion/irritation	Not classified.			
Skin corrosion/initation	Skin contact with melted/heated product may cause serious thermal burns.			
Serious eye damage/irritation	Not classified.			
Serious eye damage/ in nation	Solid or dust may cause irritation or corneal injury due to mechanical action.			
Respiratory sensitisation	Not classified.			
Respiratory sensitisation	Dust and/or thermal decomposition products inhalation may cause irritation of respiratory system.			
11.2 Information on other hazards				

No data available

SECTION 12. ECOLOGICAL INFORMATION

At normal conditions plastic is a very stable product.

Product does not form toxic compounds with other substances in air and water.

The product is poorly biodegradable but does not pose a hazard to the environment.

The product is virtually insoluble in water and can thus be seperated from water.

12.1 Toxicity

Not available.

12.2 Persistence and degradability

Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Not available.

12.5 Results of PBT and vPvB assessment

Persistent bioaccumulative and toxic (PBT) or very persistent very bioaccumulated (vPvB) evaluation is not availabe as chemical safety assessment is not required.

12.6 Endocrine distrupting properties

No data available

12.7 Other adverse effects

There is no known significant effect and critical hazards.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal according to the general rules of municipality. Product is suitable for recycled process.

SECTION 14. TRANSPORT INFORMATION

Not classified as a dangerous good under transportation regulations (IMDG, IATA, ADR/RID).

14.1 UN number

14.2 UN proper shipping name	-
14.3 Transport hazard class(es)	-
14.4 Packing group	-
14.5 Environmental hazards	-
14.6 Special precautions for user	-
14.7 Transport in bulk according to Annex II of	_

Marpol and the IBC Code

SECTION 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations; 2015/830/EC, 1272/2008/EC, 1907/2006/EC

Directives; 2006/8/EC, 2004/73/EC, 1999/45/EC, 67/548/EEC

15.2 Chemical safety assessment

Product is not classified as hazardous.

SECTION 16. OTHER INFORMATION

This safety data sheet informations includes our current knowledges and experiences at the publication date of the form, without any warranty. Informations in the content is given for guidance only and should not be perceived as a quality specification of the product only in creating design features. It is recommended that to our customers, test the product at their own process conditions for intended application and usage suitability. Users of the product are responsible for keeping up with current laws and local regulations.

SDS Page No

4/4