9885000 HYDROCARB 60-PT 74%



Version 1.4

(GHS_US)

Revision Date: 09/13/2024

SDS Number: PR98850-00

Date of last issue: 06/11/2020 Date of first issue: 12/23/2014

SECTION 1. IDENTIFICATION

Product name : HYDROCARB 60-PT 74%

Product code : 9885000

Manufacturer or supplier's details

Company name of supplier : Omya International AG

Address : 42 Baslerstrasse

Oftringen AG 4665

Telephone : +41627892929

Telefax : +41627892077

Emergency telephone : (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Filler or Pigment

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity (Inhalation) : Category 1A

GHS label elements

Hazard pictograms



Signal Word : Danger

Hazard Statements : H350 May cause cancer by inhalation.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

9885000 HYDROCARB 60-PT 74%



Version 1.4

(GHS_US)

Revision Date: 09/13/2024

SDS Number: PR98850-00

Date of last issue: 06/11/2020 Date of first issue: 12/23/2014

P202 Do not handle until all safety precautions have been read

and understood.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Typical composition (% w/w)
Ground calcium carbonate (GCC)	1317-65-3	>= 9.5 - <= 100
quartz (SiO2)	14808-60-7	0.6

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air in case of accidental inhalation of dust or

fumes from overheating or combustion. If symptoms persist, call a physician.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

May cause cancer by inhalation.

9885000 HYDROCARB 60-PT 74%



Version 1.4

Revision Date: 09/13/2024

SDS Number: PR98850-00

Date of last issue: 06/11/2020 Date of first issue: 12/23/2014

(GHS_US)

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

No hazardous combustion products are known

Further information Standard procedure for chemical fires.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Environmental precautions No special environmental precautions required.

Methods and materials for

containment and cleaning up

Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

For personal protection see section 8. Advice on safe handling

No special handling advice required.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Materials to avoid Do not store near acids.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
Ground calcium carbonate	1317-65-3	TWA (total	15 mg/m3	OSHA Z-1
(GCC)		dust)		
		TWA (respir-	5 mg/m3	OSHA Z-1
		able fraction)		

9885000 HYDROCARB 60-PT 74%



Version 1.4

Revision Date: 09/13/2024

SDS Number: PR98850-00

Date of last issue: 06/11/2020 Date of first issue: 12/23/2014

(GHS_US)

		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
quartz (SiO2)	14808-60-7	PEL (respir- able)	0.05 mg/m3	OSHA CARC
		PEL (respir- able)	0.05 mg/m3	OSHA CARC
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1

Personal protective equipment

Hand protection

Remarks : For prolonged or repeated contact use protective gloves.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : suspension

Color : white

Odor : characteristic

9885000 HYDROCARB 60-PT 74%



Version 1.4 (GHS_US) Revision Date: 09/13/2024

SDS Number: PR98850-00

Date of last issue: 06/11/2020 Date of first issue: 12/23/2014

pH : 8.5 - 11 (20 °C / 20 °C)

Concentration: 100 g/l Method: DIN-ISO 787/9

Melting point/freezing point : 0 °C / 0 °C

Boiling point : ca. 100 °C / 100 °C

Water

Flash point : Not applicable

Flammability (liquids) : Will not burn

Burning number : 1

Upper explosion limit / Upper

flammability limit

Not applicable

Lower explosion limit / Lower

flammability limit

Not applicable

Vapor pressure : 23.4 hPa (20 °C / 20 °C)

aqueous phase

Density : 1.8 - 2.1 g/cm3 (20 °C / 20 °C)

Method: DIN-ISO 787/10

Density depends on the solids content of the dispersion.

Solubility(ies)

Water solubility : 0.014 g/l (20 °C / 20 °C)

0.018 g/l (75 °C / 75 °C)

Partition coefficient: n-

octanol/water

Not applicable

Decomposition temperature : $> 400 \, ^{\circ}\text{C} \, / > 400 \, ^{\circ}\text{C}$

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

Stable under recommended storage conditions.

No decomposition if used as directed.

Reacts with acids. It forms carbon dioxide (CO2). This displaces the oxygen in the air in closed spaces. (danger of

suffocation)

9885000 HYDROCARB 60-PT 74%



Version 1.4

(GHS_US)

Revision Date: 09/13/2024

SDS Number: PR98850-00

Date of last issue: 06/11/2020 Date of first issue: 12/23/2014

Conditions to avoid : No data available

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Components:

Ground calcium carbonate (GCC):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

quartz (SiO2):

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC0 (Rat, male and female): > 0.69 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

Assessment: The substance or mixture has no acute

inhalation toxicity

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable

concentration.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

GLP: no

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

9885000 HYDROCARB 60-PT 74%



Version Revision Date: SDS Number: Date of last issue: 06/11/2020 1.4 09/13/2024 PR98850-00 Date of first issue: 12/23/2014

(GHS_US)

Product:

No data available

Components:

quartz (SiO2):

Assessment : not sensitizing

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

May cause cancer by inhalation.

Components:

quartz (SiO2):

Carcinogenicity - : Positive evidence from human epidemiological studies (inhala-

Assessment tion)

IARC Group 1: Carcinogenic to humans

quartz (SiO2) 14808-60-7

(Silica dust, crystalline)

NTP Known to be human carcinogen

quartz (SiO2) 14808-60-7

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Components:

quartz (SiO2):

Routes of exposure : Inhalation Target Organs : Lungs

Assessment : May cause damage to organs through prolonged or repeated

exposure.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

9885000 HYDROCARB 60-PT 74%



Version 1.4

(GHS_US)

Revision Date: 09/13/2024

SDS Number: PR98850-00

Date of last issue: 06/11/2020 Date of first issue: 12/23/2014

This product contains prismatic tremolite (e.g., cleavage fragments) as an impurity. Sufficient exposure to respirable prismatic tremolite dust may cause serious lung problems.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 10,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

NOEC (Desmodesmus subspicatus (green algae)): 75 mg/l

Exposure time: 72 h

EC50 (Desmodesmus subspicatus (green algae)): 289 mg/l

Exposure time: 72 h

Components:

Ground calcium carbonate (GCC):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 10,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 200 mg/l

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 75 mg/l

Exposure time: 72 h

quartz (SiO2):

Toxicity to fish : Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No toxicity at the limit of solubility.

Toxicity to algae/aquatic

plants

Remarks: No toxicity at the limit of solubility.

9885000 HYDROCARB 60-PT 74%



Version 1.4

(GHS_US)

Revision Date: 09/13/2024

SDS Number: PR98850-00

Date of last issue: 06/11/2020 Date of first issue: 12/23/2014

Toxicity to microorganisms

Remarks: No toxicity at the limit of solubility.

Persistence and degradability

Product:

Biodegradability : Remarks: Not applicable

Components:

quartz (SiO2):

Biodegradability : Result: Not biodegradable

Biochemical Oxygen De-

mand (BOD)

Remarks: Not applicable

Chemical Oxygen Demand

(COD)

Remarks: Not applicable

Bioaccumulative potential

Components:

Ground calcium carbonate (GCC):

Partition coefficient: n-

octanol/water

Remarks: Not applicable

quartz (SiO2):

Bioaccumulation : Remarks: Substance is not persistent, bioaccumulative, and

toxic (PBT).

Partition coefficient: n-

octanol/water

Remarks: Not applicable

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

In solid state these minerals are a major part of the rocks of

the earth's surface.

9885000 HYDROCARB 60-PT 74%



Version 1.4

(GHS_US)

Revision Date: 09/13/2024

SDS Number: PR98850-00

Date of last issue: 06/11/2020 Date of first issue: 12/23/2014

Components:

Results of PBT and vPvB

Results of PDT and VPVD

: Non-classified PBT substance Non-classified vPvB substance

assessment

SECTION 13. DISPOSAL CONSIDERATIONS

Ground calcium carbonate (GCC):

Disposal methods

Waste from residues : Offer surplus and non-recyclable solutions to a licensed

disposal company.

Contaminated packaging : Empty remaining contents.

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute/Chronic Health Hazard

Acute/Chronic Health Hazard

9885000 HYDROCARB 60-PT 74%



Version Revision Date: SDS Number: Date of last issue: 06/11/2020 1.4 09/13/2024 PR98850-00 Date of first issue: 12/23/2014

(GHS_US)

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

Ground calcium carbonate (GCC) 1317-65-3 quartz (SiO2) 14808-60-7

Pennsylvania Right To Know

Ground calcium carbonate (GCC) 1317-65-3

SECTION 16. OTHER INFORMATION

Further information

9885000 HYDROCARB 60-PT 74%




Version 1.4 (GHS_US) Revision Date: 09/13/2024

SDS Number: PR98850-00

Date of last issue: 06/11/2020 Date of first issue: 12/23/2014

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek Permissible exposure limit (PEL)

OSHA CARC / PEL : Permissible exposure limit (PE OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime

9885000 HYDROCARB 60-PT 74%



Version 1.4

Revision Date: 09/13/2024

SDS Number: PR98850-00

Date of last issue: 06/11/2020 Date of first issue: 12/23/2014

(GHS_US)

Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Sources of key data used to compile the Material Safety

: Information taken from reference works and the literature.

Data Sheet

Revision Date : 09/13/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8