

## Technical Data Sheet - KahlWax 7853 Micro

### Characteristics

KahlWax 7853 Micro is a white, high melting, hard wax of mainly branched hydrocarbons. It is mainly used for the modification of wax melts, oil pastes, and dispersions.

### Recommended for

- |  |   |
|--|---|
| <input checked="" type="checkbox"/> Industrial Application | <input checked="" type="checkbox"/> Personal Care |
| <input type="checkbox"/> Pharma                            | <input type="checkbox"/> Food                     |

### Compliance status

- |  |   |
|--|---|
| <input type="checkbox"/> Natural Cosmetics | <input type="checkbox"/> European Pharmacopoeia |
| <input type="checkbox"/> Organic Cosmetics | <input type="checkbox"/> USP/NF                 |

### General

Parameter		Unit
INCI (EU)	Cera Microcristallina	
CAS no.	63231-60-7	
Color	white	
Appearance	pellets	
Shelf life	1096	days
Storage temperature	max. 40	°C

Color and shape of the product may differ slightly within a production batch due to the production process.

This product information is indicative and does not include any guarantee. It does not relieve the purchaser from examining the product upon delivery and gives no assurance of stability of the product for any particular purpose.

## Technical Data Sheet - KahlWax 7853 Micro

### Specification

Parameter		Unit
Drop point	84 - 90	°C
Needle penetration	ca. 7 dmm	

Automatically generated and valid without signature  
04.09.2023 / 0000279742

Last amended on: 01.09.2023

This product information is indicative and does not include any guarantee. It does not relieve the purchaser from examining the product upon delivery and gives no assurance of stability of the product for any particular purpose.

Kahl GmbH Co. KG, Otto-Hahn-Str. 2, 22946 Trittau / Germany, Phone +49 4154 8431-0, Fax no + 49 4154 8431-10 – eMail: [info@kahlworld.com](mailto:info@kahlworld.com)