Rev.-Nr. 6: 2018-01-18





# LOXIOL<sup>®</sup> P 1206

## **Description**

LOXIOL® P 1206 is a neutral ester wax.

#### **General Appearance**

White, solid Available as beads

## **Specified Data**

Parameter	Value	Test Method
Acid value (mg KOH/g)	0 - 1.5	DIN EN ISO 2114
Dropping point (°C)	55 - 58	DIN ISO 2176
Hydroxyl value (mg KOH/g)	85 - 105	DIN 53240
lodine value (g I / 100 g)	0 - 2	DIN 53241
Saponification value (mg KOH/g)	185 - 192	DIN EN ISO 3681
Color Lovibond 1" yellow	0 - 1.5	DGF C-IV 4b
Color Lovibond 1" red	0 - 0.5	DGF C-IV 4b

## **Properties and Applications**

LOXIOL® P 1206 has a balanced internal und external lubricating effect.

LOXIOL® P 1206 is suitable for rigid PVC processing, especially extrusion and injection molding. It also can be used as a lubricant and release agent for engineering plastics such as POM and ABS.



Rev.-Nr. 6: 2018-01-18





## Recommended Dosage

0.5 - 1.5 phr

## **Certifications**

LOXIOL® P 1206 is registered in compliance with the EU REACH regulation. LOXIOL® P 1206 complies with indirect food contact directives. Further information is available upon request.

#### Health and Safety Information

Please review our Safety Data Sheet for best practices when using this material.

#### Packaging Sizes

Bags, 25 kg Big bags, 900 kg

#### **Storage and Handling**

It is recommended to store LOXIOL® P 1206 at room temperature and to protect the product against the effects of heat and frost. If stored in original sealed packaging, LOXIOL® P 1206 should be stable for at least 24 months from the date of manufacture.

Emery Oleochemicals GmbH T | +49 211 5611 2000 E | gp.europe@emeryoleo.com Emery Oleochemicals LLC T | +1 513 762 2500 E | gp.americas@emeryoleo.com Emery Oleochemicals (M) Sdn Bhd T | +603 3326 8686 E | gp.asia@emeryoleo.com

**Disclaimer:** The content in this document is provided on an "as is" and "as available" basis purely for informational purposes and, unless and to the extent specifically agreed otherwise for a sales transaction, does not constitute any warranty, whether express, implied or statutory, including but not limited to warranties or guarantees of merchantability, fitness or suitability for a particular purpose nor any representations of a binding nature. EMERY OLEOCHEMICALS EXPRESSLY DISCLAIMS ANY RESPONSI-BILITY FOR THE SUITABILITY OF THE PRODUCTS FOR ANY SPECIFIC OR PARTICULAR PURPOSES INTENDED BY THE USER. Suggestions for the use and application of the products and guide formulations are for informational purposes only and you are advised to carry out any necessary steps to test the suitability of the products for your intended processes and purposes. You are solely responsible for compliance with all applicable laws and regulations in use of the products including any third party intellectual express. All indications marked with a TM or ® symbol are trademarks belonging to legal entities within the Emery Oleochemicals group of companies.



Page 2 of 2