









LOXIOL® P 728

Lubricant

Description

LOXIOL® P 728 is a polyol partial ester.

General Appearance

Slight yellowish, practically odorless Delivery form as powder or beads

Specified Data

Parameter	Value	Test Method
Dropping point (°C)	49 - 52	DIN ISO 2176
Acid value (mg KOH/g)	0 - 1.0	DIN EN ISO 2114
Hydroxyl value (mg KOH/g)	145 - 158	DIN 53240
Color Lovibond 1" yellow	0 - 4.0	DGF C-IV 4b
Color Lovibond 1" red	0 - 2.0	DGF C-IV 4b
Water content (%)*	< 0.3	DIN 51777
Saponification value (mg KOH/g)*	174 - 184	DIN EN ISO 3681

^{*}Values remain within indicated bandwidth, but will not be measured with every batch.

Properties and Applications

LOXIOL® P 728 is suitable as an internal lubricant for rigid PVC, such as films and bottles and injection molded articles.

LOXIOL® P 728 shows a synergistic effect when used with CaIn stabilizers. It facilitates mold filling and mold release in injection molding. Additives such as pigments and fillers are best dispersed in the polymer melt.



Rev.-Nr. 7: 2018-01-17













Recommended Dosage

0.5 - 1.5 phr

Certifications

LOXIOL® P 728 is registered in compliance with the EU REACH regulation. LOXIOL® P 728 complies with indirect food contact directives. Further information is available upon request.

Health and Safety Information

Please review our Safety Data Sheet for best practices when using this material.

Packaging Sizes

Bags, 25 kg Big bags, 900 kg

Storage and Handling

It is recommended to store LOXIOL® P 728 at room temperature and to protect the product against the effects of heat and frost. If stored in original sealed packaging, LOXIOL® P 728 should be stable for at least 24 months from the date of manufacture.

Emery Oleochemicals GmbH T | +49 211 5611 2000 E | gp.europe@emeryoleo.com Emery Oleochemicals LLC T | +1 513 762 2500 E | gp.americas@emeryoleo.com Emery Oleochemicals (M) Sdn Bhd T | +603 3326 8686 E | gp.asia@emeryoleo.com

Disclaimer: The content in this document is provided on an "as is" and "as available" basis purely for informational purposes and, unless and to the extent specifically agreed otherwise for a sales transaction, does not constitute any warranty, whether express, implied or statutory, including but not limited to warranties or guarantees of merchantability, fitness or suitability for a particular purpose nor any representations of a binding nature. EMERY OLEOCHEMICALS EXPRESSLY DISCLAIMS ANY RESPONSI-BILITY FOR THE SUITABILITY OF THE PRODUCTS FOR ANY SPECIFIC OR PARTICULAR PURPOSES INTENDED BY THE USER. Suggestions for the use and application of the products and guide formulations are for informational purposes only and you are advised to carry out any necessary steps to test the suitability of the products for your intended processes and purposes. You are solely responsible for compliance with all applicable laws and regulations in use of the products including any third party intellectual property rights and shall bear all liability or risk arising from use of the products. All indications marked with a TM or ® symbol are trademarks belonging to legal entities within the Emery Oleochemicals group of companies.

