Product Information



Omya International AG P.O. Box CH-4665 Oftringen

+41 62 789 29 29 +41 62 789 20 77

www.omya.com

OMYACARB 3 - SY

PRODUCTION SITE:	SYLACAUGA, USA (certified ISO 9001, ISO 14001, ISO 45001)			
SHORT DESCRIPTION OF THE PRODUCT:	A high purity, very fine, wet ground natural calcium carbonate.			
CHEMICAL ANALYSIS:	Total Carbonate Content		99	%
SPECIFIC PRODUCT DATA:	Fineness:			
¹ Sedigraph	 Residue on a 45 µm sieve (ISO 787-7) Median particle size (d50%) (Omya GLS 041)¹ 		20 3.1	ppm µm
	Optical properties: • CIE L* (ISO 11664-4)		97.8	
	Moisture ex works (ISO 787-2)		0.05	%
GENERAL PRODUCT DATA:	Loose Bulk Density (Omya GLS 001) Packed Bulk Density (Omya GLS 002) Oil Absorption (ISO 787-5)	37 lbs./ft. ³ 69 lbs./ft. ³	0.60 1.10 10.5	g/ml g/ml g/100g
MAIN APPLICATIONS :	Decorative Paints Industrial Coatings Plasters, Renders, Joint Fillers Rigid PVC application Flexible PVC application Masterbatch and Compound			
REGULATORY APPROVALS :	This product may be used as an indirect food additive in food packaging applications under 21 CFR (FDA) 174.5, 175.300, and 178.3297. It does not qualify as a substance permitted for direct addition to human food. Additionally the dry form of this product is certified by NSF International under NSF/ANSI Standard 14 as a generic calcium carbonate ingredient in plastics piping system components and related material.			
STANDARD PACKAGING:	Bulk			

The information contained in this Product Information Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information provided herein is based on technical data that Omya believes to be reliable, however Omya makes no representation or warranty as to the completeness or accuracy thereof and Omya assumes no liability resulting from its use or for any claims, losses, or damages of any third party. Recipients receiving this information must exercise their own judgement as to the appropriateness of its use, and it is the user's responsibility to assess the material's suitability (including safety) for a particular purpose prior to such use.