



TECHNICAL DATA SHEET

P-1460

ISSUE DATE: 04/20/2012

PRODUCT DESCRIPTION	P-1460 is a vinyl acrylic terpolymer emulsion. It possesses good flexibility and paints formulated with this emulsion have outstanding durability.		
USES	Useful as a vehicle for Interior and exterior architectural paints including flats, semi-gloss & high gloss enamel paints. Other uses include adhesive compounding and textile finishing.		
FEATURES	<ul style="list-style-type: none">• Excellent scrub resistance• Superior stain resistance & wash ability• High binding efficiency• Outstanding associative thickener response• Good color retention and excellent low temperature touch up		
TYPICAL PROPERTIES	Viscosity (cps):	1,600	
	Solids (%):	54.0 - 56.0	
	Density (lbs/gal):	8.9	
	pH:	5.0 - 6.0	
PRODUCT APPLICATION	Useful as a vehicle for architectural paints.		
ADDITIONAL DATA	Particle Size: 0.3 μ m approx.	Borax Compatibility: Good	Tg: 18°C
	Particle Charge: Anionic	Appearance: White	MFFT: 9.4°C
	Molecular Weight: High	Water Resistance: Good	
PACK SIZES	450 lbs drum	2,400 lbs tote	
	45,000 lbs tanker	Weights may vary	
STORAGE CONDITIONS	Containers should be well sealed. Protect from direct sunlight and heat.		
LIMITATIONS	Shelf Life: Up to 6 months when stored as recommended.		

Any recommendations contained herein or any information given by any ONA Polymers representative is based on tests and information believed to be accurate. However, since we have no control over the conditions under which our products are transported, stored, handled, or used by purchasers, all recommendations and sales are made on condition that ONA Polymers will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision. It is the user's responsibility to ensure that this sheet is current prior to using the product.