

TECHNICAL DATA SHEET

P-4222

ISSUE DATE: 04/20/2012

PRODUCT DESCRIPTION	P-4222 is a vinyl acrylic copolymer.	
USES	Designed for use in interior and exterior architectural coatings application where high scrub resistance and durability are desired.	
FEATURES	<ul style="list-style-type: none"> • Superior pigment binding characteristics • Good hiding • Stain resistant • Excellent thickening efficiency and lower thickener loading • Compatible with most acrylic systems to meet additional performance requirements 	
TYPICAL PROPERTIES	Viscosity (cps):	400
	Solids (%):	54.0 - 56.0
	Density (lbs/gal):	8.9 - 9.0
	pH:	4.0 - 5.0
PRODUCT APPLICATION	Interior / exterior architectural paints.	
ADDITIONAL DATA	Particle Size: 0.3 µm approx. Tg: 7.2°C VOC Content: 1.31 g/L	Free Monomer Content: <0.1% MFFT: 16.5°C Appearance: White emulsion
PACK SIZES	450 lbs drum 45,000 lbs tanker	2,400 lbs tote Weights may vary
STORAGE CONDITIONS	Containers should be well sealed. Protect from direct sunlight and heat.	
LIMITATIONS	Shelf Life: Up to 6 months when stored as recommended.	

Any recommendations contained herein or any information given by any ONA Polymers representative is based on tests and information believed to be accurate. However, since we have no control over the conditions under which our products are transported, stored, handled, or used by purchasers, all recommendations and sales are made on condition that ONA Polymers will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision. It is the user's responsibility to ensure that this sheet is current prior to using the product.