



TECHNICAL DATA SHEET

P-4293

ISSUE DATE: 04/20/2012

PRODUCT DESCRIPTION	P-4293 is a next-generation vinyl acrylic latex that can be used to formulate remarkably durable low VOC and APEO free architectural coatings - displaying outstanding water resistance, block resistance, scrub resistance and color retention. It can be used in both interior and exterior coatings and can be formulated to a wide range of gloss levels.	
USES	Interior and exterior architectural coatings, including high PVC flat latex paints; semi-gloss and high gloss enamels. Also useful as a performance enhancer or as a base in other demanding coatings applications.	
FEATURES	<ul style="list-style-type: none">• APEO free, low VOC capable• Superior scrub, water and stain resistance• High binding efficiency• Excellent washability and color retention• Outstanding responsiveness to thickeners	
TYPICAL PROPERTIES	Viscosity (cps):	400 - 1,000
	Solids (%):	54.0 - 56.0
	Density (lbs/gal):	8.8
	pH:	4.0 - 5.0
PRODUCT APPLICATION	Used as a base or performance enhancer for interior and exterior architectural coatings.	
ADDITIONAL DATA	Particle Size: 0.2 - 0.3 μ m approx. MFFT: 5°C	Tg: 12° Color: White
PACK SIZES	450 lbs drum 45,000 lbs tanker	2,400 lbs tote Weights may vary
STORAGE CONDITIONS	Containers should be well sealed. Protect from direct sunlight and heat.	
LIMITATIONS	Shelf Life: Up to 6 months when stored as recommended.	

Any recommendations contained herein or any information given by any ONA Polymers representative is based on tests and information believed to be accurate. However, since we have no control over the conditions under which our products are transported, stored, handled, or used by purchasers, all recommendations and sales are made on condition that ONA Polymers will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision. It is the user's responsibility to ensure that this sheet is current prior to using the product.