

SPEEDCURE BDMB

1. PRODUCT AND COMPANY IDENTIFICATION

Company

Arkema Inc.
900 First Avenue
King of Prussia, Pennsylvania 19406

Sartomer

Customer Service Telephone Number: (800) SARTOMER
(Monday through Friday, 8:00 AM to 5:00 PM EST)

Emergency Information

Transportation: CHEMTREC: (800) 424-9300
(24 hrs., 7 days a week)
Medical: Rocky Mountain Poison Center: (866) 767-5089
(24 hrs., 7 days a week)

Product Information

Product name: SPEEDCURE BDMB
Synonyms: 2-Benzyl-2-dimethylamino-4-morpholinobutyrophenone
Molecular formula: Complex mixture
Chemical family: Aminoacetophenones
Product use: Process regulators, used in vulcanization or polymerization processes

SECTION 2: HAZARDS IDENTIFICATION

Emergency Overview

Color: light yellow
Physical state: solid
Form: powder
Odor: odourless

*Classification of the substance or mixture:

Reproductive toxicity, Category 2, H361
Acute aquatic toxicity, Category 1, H400
Chronic aquatic toxicity, Category 1, H410

*For the full text of the H-Statements mentioned in this Section, see Section 16.

SPEEDCURE BDMB

GHS-Labeling

Hazard pictograms:



Signal word:

Warning

Hazard statements:

H361 : Suspected of damaging fertility or the unborn child.

H410 : Very toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements:

May form combustible dust concentrations in air.

Precautionary statements:

Prevention:

P201 : Obtain special instructions before use.

P202 : Do not handle until all safety precautions have been read and understood.

P273 : Avoid release to the environment.

P281 : Use personal protective equipment as required.

Response:

P308 + P313 : IF exposed or concerned: Get medical advice/ attention.

P391 : Collect spillage.

Storage:

P405 : Store locked up.

Disposal:

P501 : Dispose of contents or container to an approved waste disposal plant.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product code: LAM300

Version 2.0

Issued on: 07/22/2021

Page: 2 / 12

SPEEDCURE BDMB

Chemical Name	CAS-No.	Wt/Wt	GHS Classification**
2-benzyl-2-dimethylamino-4'-morpholinobutyrophenone	119313-12-1	> 98 %	H361, H400, H410

**For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of necessary first-aid measures:

Inhalation:

If inhaled, remove victim to fresh air.

Skin:

In case of contact, immediately flush skin with plenty of water. Thoroughly clean shoes before reuse. Remove contaminated clothing and shoes. Wash clothing before reuse.

Eyes:

Immediately flush eye(s) with plenty of water.

Ingestion:

If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed:

For most important symptoms and effects (acute and delayed), see Section 2 (Hazard Statements and Supplemental Information if applicable) and Section 11 (Toxicology Information) of this SDS.

4.3. Indication of any immediate medical attention and special treatment needed:

Unless otherwise noted in Notes to Physician, no specific treatment noted; treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media (suitable):

Carbon dioxide (CO₂), Foam, Dry chemical

Extinguishing media (unsuitable):

Product code: LAM300

Version 2.0

Issued on: 07/22/2021

Page: 3 / 12

SPEEDCURE BDMB

High volume water jet

Protective equipment:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

Further firefighting advice:

Do not use a solid stream of water.

A solid stream of water can cause a dust explosion.

Do not allow run-off from fire fighting to enter drains or water courses.

Fire fighting equipment should be thoroughly decontaminated after use.

Fire and explosion hazards:

Dust clouds generated during handling and/or storage can form explosive mixtures with air. Dust explosion characteristics vary with the particle size, particle shape, moisture content, contaminants, and other variables.

Note: Check that all equipment is properly grounded and installed to satisfy electrical classification requirements. As with any dry material, pouring this material or allowing it to free-fall or to be conveyed through chutes or pipes can accumulate and generate electrostatic sparks, potentially causing ignition of the material itself, or of any flammable materials which may come into contact with the material or its container.

When burned, the following hazardous products of combustion can occur:

Carbon oxides

Hazardous organic compounds

Nitrogen oxides

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, Emergency procedures, Methods and materials for containment/clean-up:

Prevent further leakage or spillage if you can do so without risk. Evacuate area of all unnecessary personnel. Ventilate the area. Eliminate all ignition sources. Avoid dust formation and dispersal of dust in the air. Wet down (dampen) the spilled material with water. Sweep or scoop up using non-sparking tools and place into suitable properly labeled containers for prompt disposal. The sweepings should be wetted down further with water. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Implement workplace practices such that dusts are not allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

Protective equipment:

Appropriate personal protective equipment is set forth in Section 8.

SPEEDCURE BDMB

SECTION 7: HANDLING AND STORAGE

Handling

General information on handling:

Do not taste or swallow.
 Avoid breathing dust.
 Avoid contact with skin, eyes and clothing.
 Keep away from heat, sparks and flames.
 Keep container closed.
 Use only with adequate ventilation.
 Wash thoroughly after handling.
 Avoid creating dust in handling, transfer or clean up.
 Prevent dust accumulation.
 Implement routine housekeeping practices to ensure that dusts do not accumulate on surfaces.
 Check that all equipment is properly grounded and installed to satisfy electrical classification requirements.
 Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations.
 Container hazardous when empty.
 Follow label warnings even after container is emptied.
RESIDUAL DUSTS MAY EXPLODE ON IGNITION.
DO NOT CUT, DRILL, GRIND, OR WELD ON OR NEAR THIS CONTAINER.
 Improper disposal or reuse of this container may be dangerous and/or illegal.
 Emptied container retains product residue.

Storage

General information on storage conditions:

Keep in a dry, cool place. Store in closed containers, in a secure area to prevent container damage and subsequent spillage. Store in well ventilated area away from heat and sources of ignition such as flame, sparks and static electricity. Ensure that all storage and handling equipment is properly grounded and installed to satisfy electrical classification requirements. Store out of direct sunlight in a cool well-ventilated place. Static electricity may accumulate when transferring material. All metal and groundable storage containers, including but not limited to drums, cylinders, Returnable Intermodal Bulk Containers (RIBCs) and Class C Flexible Intermodal Bulk Containers (FIBCs) must be bonded and grounded during filling and emptying operations. Observe all federal, state and local regulations and National Fire Protection Association (NFPA) Codes, which pertain to the specific local conditions of storage and use, including NFPA 654.

Storage stability – Remarks:

Stable under recommended storage conditions.

Storage incompatibility – General:

Store separate from:
 Strong oxidizing agents
 Strong reducing agents
 Strong acids
 Strong alkalies

SPEEDCURE BDMB

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Airborne Exposure Guidelines:

Engineering controls:

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Check that all dust control equipment such as local exhaust ventilation, material transport systems, and air-material separation devices involved in handling this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Isolation devices may be appropriate to prevent propagation from one unit to another. Ensure that dust-handling systems are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Consult ACGIH ventilation manual, NFPA Standard 91 and NFPA Standard 654 for design of exhaust system and safe handling.

Respiratory protection:

Avoid breathing dust. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components (full facepiece recommended). Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Skin protection:

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Consult glove manufacturer to determine appropriate type glove material for given application. Rinse immediately if skin is contaminated. Wash contaminated clothing and clean protective equipment before reuse. Wash thoroughly after handling.

Eye protection:

Where eye contact may be likely, wear chemical goggles and have eye flushing equipment available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Color:	light yellow
Physical state:	solid
Form:	powder
Odor:	odourless
Odor threshold:	No data available.
Flash point	No data available

SPEEDCURE BDMB

Auto-ignition temperature:	No data available.
Lower flammable limit (LFL):	No data available.
Upper flammable limit (UFL):	No data available.
pH:	No data available.
Density:	1.21 g/cm ³ (68 °F (20 °C))
Specific Gravity (Relative density):	1.21 68 °F 20 °C
Vapor pressure:	No data available.
Vapor density:	No data available.
Boiling point/boiling range:	> 752 °F (400 °C) 759.8 mmHg
Melting point/range:	235.8 °F (113.2 °C)
Freezing point:	No data available.
Evaporation rate:	No data available.
Solubility in water:	negligible
Viscosity, dynamic:	No data available.
Particle size:	> 20 - < 400 µm
Oil/water partition coefficient:	log Pow: 3.66
Thermal decomposition:	No data available.
Flammability:	See GHS Classification in Section 2 if applicable

SECTION 10: STABILITY AND REACTIVITY

Stability:

The product is stable under normal handling and storage conditions.

Hazardous reactions:

Hazardous polymerisation does not occur.

Materials to avoid:

Product code: LAM300

Version 2.0

Issued on: 07/22/2021

Page: 7 / 12

SPEEDCURE BDMB

Strong reducing agents
Strong oxidizing agents
Strong alkalies
Strong acids

Conditions / hazards to avoid:

Avoid exposure to high temperatures or direct sunlight.

Hazardous decomposition products:

Thermal decomposition giving flammable and toxic products :
Carbon oxides
Hazardous organic compounds
Nitrogen oxides

SECTION 11: TOXICOLOGICAL INFORMATION

Data on this material and/or its components are summarized below.

Data for SPEEDCURE BDMB**Acute toxicity****Oral:**

No deaths occurred. (rat) LD₀ = 5,000 mg/kg.

Dermal:

No deaths occurred. (rat) LD₀ = 2,000 mg/kg.

Skin Irritation:

Not irritating. (rabbit) OECD Test Guideline 404 (4 h)

Eye Irritation:

Causes mild eye irritation. (rabbit)

Skin Sensitization:

Not a sensitizer. Guinea pig maximization test. No skin allergy was observed.

Repeated dose toxicity

Repeated oral administration to rat / affected organ(s): liver / signs: changes in organ weights, clinical chemistry changes / No adverse systemic effects reported.

Genotoxicity**Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, animal cells

Assessment in Vivo:

No genetic changes were observed in a laboratory test using: hamster

Reproductive effects

SPEEDCURE BDMB

Reproduction test. Oral (rat) / Effects on embryofoetal and postnatal development / (increased mortality in the offspring, reduced body weight, smaller litter sizes)

SECTION 12: ECOLOGICAL INFORMATION

Chemical Fate and Pathway

Data on this material and/or its components are summarized below.

Data for SPEEDCURE BDMB

Biodegradation:

Not readily biodegradable. (28 d) biodegradation 3 %

Octanol Water Partition Coefficient:

log Pow: = 2.91

Ecotoxicology

Data on this material and/or its components are summarized below.

Data for SPEEDCURE BDMB

Aquatic toxicity data:

Very toxic. Danio rerio (zebra fish) 96 h LC50 = 0.46 mg/l

Aquatic invertebrates:

No effect up to the limit of solubility. Daphnia magna (Water flea) 24 h EC50 > 0.8 mg/l

Algae:

No effect up to the limit of solubility. Pseudokirchneriella subcapitata (green algae) 72 h ErC50 > 2 mg/l

Microorganisms:

Respiration inhibition / Activated sludge 30 min EC50 > 100 mg/l

Chronic toxicity to aquatic invertebrates:

No effect up to the limit of solubility. Reproduction Test / Daphnia magna (Water flea) 21 d NOEC > 0.21 mg/l (Water accommodated fraction was tested.)

SECTION 13: DISPOSAL CONSIDERATIONS

Waste disposal:

Disposal via incineration is recommended. Dispose of in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

Take appropriate measures to prevent release to the environment.

SPEEDCURE BDMB

SECTION 14: TRANSPORT INFORMATION

US Department of Transportation (DOT)

UN Number : 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
Technical name : (2-benzyl-2-dimethylamino-4'-morpholinobutyrophenone)
Class : 9
Packaging group : III
Marine pollutant : yes

International Maritime Dangerous Goods Code (IMDG)

UN Number : 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Technical name : (2-BENZYL-2-DIMETHYLAMINO-4'-MORPHOLINO BUTYROPHENONE)
Class : 9
Packaging group : III
Marine pollutant : yes

SECTION 15: REGULATORY INFORMATION

Chemical Inventory Status

US. Toxic Substances Control Act	TSCA	The components of this product are all on the Active TSCA Inventory.
Canadian Domestic Substances List (DSL)	DSL	All components of this product are on the Canadian DSL
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Conforms to
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Does not conform
Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	Conforms to
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	Conforms to
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	Conforms to
Australia Inventory of Chemical Substances (AICS)	AICS	Conforms to

SPEEDCURE BDMB

United States – Federal Regulations

SARA Title III – Section 302 Extremely Hazardous Chemicals:

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

SARA Title III - Section 311/312 Hazard Categories:

Fire Hazard, Chronic Health Hazard

SARA Title III – Section 313 Toxic Chemicals:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):

The components in this product are either not CERCLA regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

United States – State Regulations

New Jersey Right to Know

No components are subject to the New Jersey Right to Know Act.

Pennsylvania Right to Know

Chemical name

2-benzyl-2-dimethylamino-4'-morpholinobutyrophenone

CAS-No.

119313-12-1

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Miscellaneous:

Other information:

Refer to National Fire Protection Association (NFPA) Code 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

Product code: LAM300

Version 2.0

Issued on: 07/22/2021

Page: 11 / 12

SPEEDCURE BDMB

Latest Revision(s):

Reference number: 200018852
Date of Revision: 07/22/2021
Date Printed: 07/22/2021

LAMBSON® is a registered trademark of Arkema Inc.

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, ARKEMA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information;

NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations.

Arkema has implemented a Medical Policy regarding the use of Arkema products in Medical Devices applications that are in contact with the body or circulating bodily fluids (<http://www.arkema.com/en/social-responsibility/responsible-product-management/medical-device-policy/index.html>) Arkema has designated Medical grades to be used for such Medical Device applications. Products that have not been designated as Medical grades are not authorized by Arkema for use in Medical Device applications that are in contact with the body or circulating bodily fluids. In addition, Arkema strictly prohibits the use of any Arkema products in Medical Device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Arkema trademarks and the Arkema name shall not be used in conjunction with customers' medical devices, including without limitation, permanent or temporary implantable devices, and customers shall not represent to anyone else, that Arkema allows, endorses or permits the use of Arkema products in such medical devices.

It is the sole responsibility of the manufacturer of the medical device to determine the suitability (including biocompatibility) of all raw materials, products and components, including any medical grade Arkema products, in order to ensure that the final end-use product is safe for its end use; performs or functions as intended; and complies with all applicable legal and regulatory requirements (FDA or other national drug agencies) It is the sole responsibility of the manufacturer of the medical device to conduct all necessary tests and inspections and to evaluate the medical device under actual end-use requirements and to adequately advise and warn purchasers, users, and/or learned intermediaries (such as physicians) of pertinent risks and fulfill any postmarket surveillance obligations. Any decision regarding the appropriateness of a particular Arkema material in a particular medical device should be based on the judgment of the manufacturer, seller, the competent authority, and the treating physician.

Product code: LAM300

Version 2.0

Issued on: 07/22/2021

Page: 12 / 12