



Specialists in Tackifier Resins and Acrylic Monomers

Teckros® Q27

High Solids, Water Dispersible Rosin Ester

TECHNICAL DATA SHEET- US

Teckros® Q27 is a low Tg, water dispersible rosin ester for adhesives requiring adhesion to difficult-to-bond substrates and improved cold temperature properties while maintaining shear strength. It is recommended for acrylic, SB and natural latex pressure sensitives, product assembly, and other aqueous adhesive applications.

	Typical Properties	Specifications
Color, Gardner, 50T	6	10 max
Acid Value	45	40-50
Softening Point, R & B, Resin	27°C	--
% Solids	90%	89.8-90.2%
Viscosity, cps @57°C	4,000	3,000-5,000
pH	9.2	--
Specific Gravity, re: water	1.07	--
Density, lbs/gallon @25°C	8.9	--

Compatibility with the following latex polymers: Acrylic, Styrene Butadiene (SB), Vinyl Acetate Ethylene (VA-E), Poly Vinyl Acetate, Natural (NR), Polychloroprene, and others.

Packaging 450 lb. open-head steel drums and IBC's

Statements and recommendations are for guidance purposes only. Teckrez, Inc. makes no guarantees regarding performance in actual adhesive or other formulated products. Responsibility for performance of formulated products is solely that of the user.