

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

Version 4.1 Revision Date: 09/24/2018 SDS Number: 1560802-00008 Date of last issue: 06/05/2018
Date of first issue: 04/21/2017

SECTION 1. IDENTIFICATION

Product name : Ti-Pure™ R-350 Titanium Dioxide Pigment

SDS-Identcode : 130000030909

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19899 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Coloring agent
Pigment

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Titanium dioxide	13463-67-7	$\geq 90 - \leq 100$
Silicon dioxide	7631-86-9	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 06/05/2018
4.1	09/24/2018	1560802-00008	Date of first issue: 04/21/2017

In case of skin contact	:	Wash with water and soap as a precaution. Get medical attention if symptoms occur.
In case of eye contact	:	Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	:	irritant effects
Protection of first-aiders	:	No special precautions are necessary for first aid responders.
Notes to physician	:	Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Not applicable Will not burn
Unsuitable extinguishing media	:	Not applicable Will not burn
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion products	:	No hazardous combustion products are known
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Follow safe handling advice and personal protective equipment recommendations.
Environmental precautions	:	Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

Version 4.1 Revision Date: 09/24/2018 SDS Number: 1560802-00008 Date of last issue: 06/05/2018
Date of first issue: 04/21/2017

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³ (Silica)	NIOSH REL

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 06/05/2018
4.1	09/24/2018	1560802-00008	Date of first issue: 04/21/2017

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: crystalline
Color	: white
Odor	: odorless
Odor Threshold	: No data available
pH	: No data available
Melting point/freezing point	: 3,349 °F / 1,843 °C
Initial boiling point and boiling range	: 5,432 °F / 3,000 °C
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Will not burn

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 06/05/2018
4.1	09/24/2018	1560802-00008	Date of first issue: 04/21/2017

	Not expected to form explosive dust-air mixtures.
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: Not applicable
Relative vapor density	: Not applicable
Relative density	: 3.6 - 4.3
Solubility(ies) Water solubility	: insoluble
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: No data available
Decomposition temperature	: The substance or mixture is not classified self-reactive.
Viscosity Viscosity, kinematic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle size	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: None known.
Conditions to avoid	: None known.
Incompatible materials	: None.
Hazardous decomposition products	: No hazardous decomposition products are known.

Ti-Pure™ R-350 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 06/05/2018
4.1	09/24/2018	1560802-00008	Date of first issue: 04/21/2017

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Titanium dioxide:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 425
Acute inhalation toxicity	: LC50 (Rat): > 6.82 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rabbit): > 10,000 mg/kg

Silicon dioxide:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	: LC50 (Rat): > 2.08 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**Titanium dioxide:**

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Silicon dioxide:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Ti-Pure™ R-350 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 06/05/2018
4.1	09/24/2018	1560802-00008	Date of first issue: 04/21/2017

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Titanium dioxide:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Silicon dioxide:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Titanium dioxide:**

Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Titanium dioxide:**

Germ cell mutagenicity - Assessment	:	Weight of evidence does not support classification as a germ cell mutagen.
-------------------------------------	---	--

Silicon dioxide:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	---	---

Genotoxicity in vivo	:	Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: Ingestion Result: negative
----------------------	---	--

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 06/05/2018
4.1	09/24/2018	1560802-00008	Date of first issue: 04/21/2017

Product:

Remarks :

In lifetime inhalation studies rats were exposed for 2 years to respectively 10, 50 and 250 mg/m³ of respirable TiO₂. Slight lung fibrosis was observed at 50 and 250 mg/m³ levels. Microscopic lung tumours were also observed in 13 percent of the rats exposed to 250 mg/m³, an exposure level that caused lung overloading and impairment of rat lungs clearance mechanisms.

In further studies, these tumours were found to occur only under particle overload conditions in a uniquely sensitive species, the rat, and have little or no relevance for humans. The pulmonary inflammatory response to TiO₂ particles exposure was also found to be much more severe in rats than in other rodent species.

In February 2006, IARC has re-evaluated Titanium dioxide as pertaining to Group 2B: "possibly carcinogenic to humans", based upon inadequate evidence in humans and sufficient evidence in experimental animals for the carcinogenicity of titanium dioxide. IARC evaluation guidelines consider the generation of tumours, in 2 different studies within the same animal species, to be adequate criteria for an assessment of sufficient evidence.

The conclusions of several epidemiology studies on more than 20000 TiO₂ industry workers in Europe and the USA did not suggest a carcinogenic effect of TiO₂ dust on the human lung. Mortality from other chronic diseases, including other respiratory diseases, was also not associated with exposure to TiO₂ dust.

Based upon all available study results, Chemours scientists conclude that titanium dioxide will not cause lung cancer or chronic respiratory diseases in humans at concentrations experienced in the workplace.

Components:

Titanium dioxide:

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Silicon dioxide:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

IARC Group 2B: Possibly carcinogenic to humans
Titanium dioxide 13463-67-7

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Ti-Pure™ R-350 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 06/05/2018
4.1	09/24/2018	1560802-00008	Date of first issue: 04/21/2017

Reproductive toxicity

Not classified based on available information.

Components:**Titanium dioxide:**

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

Silicon dioxide:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:**Titanium dioxide:**

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Repeated dose toxicity**Components:****Titanium dioxide:**

Species : Rat
NOAEL : 24,000 mg/kg
LOAEL : > 24,000 mg/kg
Application Route : Ingestion
Exposure time : 28 d
Remarks : No significant adverse effects were reported

Species : Rat
NOAEL : 0.01 mg/l
LOAEL : 0.05 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 730 d

Silicon dioxide:

Species : Rat
NOAEL : 1.3 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 13 Weeks

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 06/05/2018
4.1	09/24/2018	1560802-00008	Date of first issue: 04/21/2017

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Titanium dioxide:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h NOEC (algae): 5,600 mg/l Exposure time: 72 h

Silicon dioxide:

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 10,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 24 h Method: OECD Test Guideline 202
Toxicity to algae	:	EC50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 06/05/2018
4.1	09/24/2018	1560802-00008	Date of first issue: 04/21/2017

Results of PBT and vPvB assessment : Non-classified PBT substance Non-classified vPvB substance

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 06/05/2018
4.1	09/24/2018	1560802-00008	Date of first issue: 04/21/2017

US State Regulations

Pennsylvania Right To Know

Titanium dioxide	13463-67-7
Silicon dioxide	7631-86-9
Inorganic metal oxide	Trade secret

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Silicon dioxide	7631-86-9
-----------------	-----------


California Permissible Exposure Limits for Chemical Contaminants

Titanium dioxide	13463-67-7
Silicon dioxide	7631-86-9

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	0
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Ti-Pure™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

These products may not be directly added to food, pharmaceuticals, cosmetics, or cigarette papers/filters for tobacco products.

Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

An electrostatic charge can potentially build up when pouring or conveying product from plastic bags. Do not use plastic bags in the presence of flammable or explosive vapors.

Ti-Pure™ R-350 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 06/05/2018
4.1	09/24/2018	1560802-00008	Date of first issue: 04/21/2017

In the manufacture of titanium dioxide, product is packaged at temperatures of approximately 100 to 120°C (212 to 248°F). When pigment is shipped shortly after manufacture, it may stay hot for a very long time depending on ambient temperatures and inventory storage practices. Use caution while handling hot pigment to prevent burns to personnel. Use caution in solvent applications to prevent ignition of solvent.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 06/05/2018
4.1	09/24/2018	1560802-00008	Date of first issue: 04/21/2017

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/24/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8