

Technical Data Sheet

Zano® 10

Zano® 10 is manufactured and tested in compliance with GMP Part II / ICH Q7 requirements. Testing is done using EP/USP analytical methods or validated in-house analytical methods and is compliant to below mentioned specifications.

General characters (EP) for Zano® 10

Appearance: soft, white or faintly yellowish-white, amorphous powder, free from gritty particles.

Solubility: practically insoluble in water and in ethanol (96 per cent). It dissolves in dilute mineral acids.

Zinc oxide EP/USP product specifications for Zano® 10

	Specification	Method
Identification A, B	PASS	EP/USP
Zinc Oxide	99,0 – 100,5 %	EP/USP
Lead	≤0,0010 %	ICP-AES
Cadmium	≤0,0005 %	ICP-AES
Iron	≤0,0050 %	ICP-AES
Arsenic	≤0,0002 %	ICP-AES
Thallium	≤0,0005 %	ICP-AES
Iron and other heavy metals	PASS	USP
Alkalinity	PASS	EP/USP
Loss on Ignition	≤1,0 %	EP/USP
Carbonates and color of solution	PASS	USP
Carbonates and substances insoluble in acids	PASS	EP

Additional specifications for Zano® 10

	Specification	Method
Aluminium	≤0,0050 %	ICP-AES
Nickel	≤0,0010 %	ICP-AES
Chromium	≤0,0002 %	ICP-AES
Specific Surface Area after production	≥25 m ² /g	BET

Packaging: 12.5 -20 kg bags in cardboard box



SPEC-0453 Revision : 11 Date : 27-Sep-2022