

SECTION 1: Identification

1.1. GHS Product identifier

Product form	: Substance
Substance type	: UVCB
Trade name	: Braskem Ezolem™ 6-13
Chemical name	: Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha
CAS-No.	: 64741-84-0
Product code	: P488B, P488BB1, P488C, P488

1.2. Other means of identification

Synonyms	: Textile spirits/Naphtha, solvent-refined light (petroleum)/Ligroine (petroleum), solvent-refined light/Naphtha (petroleum), solvent-refined light/Naphtha, petroleum, solvent-refined light/Naphtha (petroleum), solvent-refined light - low boiling point modified naphtha/Naphtha (petroleum) solvent-refined light/Naphtha, (petroleum), solvent-refined light/Naphtha, petroleum, solvent refined light/Naphtha (petroleum), solvent-refined light
EC Index-No.	: 649-278-00-0
EC-No.	: 265-086-6

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Industrial, Professional use, Adhesives, Paints
Restrictions on use	: No additional information available

1.4. Supplier's details

Braskem S.A.
 Rua Eteno, 1561, Polo Petroquímico de Camaçari
 Camaçari, BA, CEP: 42810-000, Brasil
 Telephone: +55 (71) 3413-3600
productsafety@braskem.com

1.5. Emergency phone number

Emergency number	: CHEMTREC Brazil (Rio De Janeiro): +(55)-2139581449 Portuguese CHEMTREC Brazil (São Paulo): +(55)-1143491359 Portuguese CHEMTREC Brazil: 0800 892 0479 Portuguese CHEMTREC+1 703-741-5970 (International – 24h)
------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Flammable liquids, Category 2
 Acute toxicity (dermal), Category 5
 Skin corrosion/irritation, Category 2
 Reproductive toxicity, Category 2
 Specific target organ toxicity — Single exposure, Category 3, Narcosis
 Aspiration hazard, Category 1
 Hazardous to the aquatic environment - Acute Hazard, Category 2
 Hazardous to the aquatic environment - Chronic Hazard, Category 1

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)	: 
Signal word (GHS BR)	: Danger
Hazard statements (GHS BR)	: H225 - Highly flammable liquid and vapour H304 - May be fatal if swallowed and enters airways

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023

Precautionary statements (GHS BR)

H313 - May be harmful in contact with skin
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child.
H401 - Toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing mist, vapours.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective gloves, protective clothing.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or a doctor.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - IF exposed or concerned: Get medical attention.
P312 - Call a POISON CENTER or a doctor if you feel unwell.
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use foam, dry extinguishing powder, carbon dioxide (CO₂), sand, Water spray to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

Handling this product may result in electrostatic accumulation. Use proper grounding procedures

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance type : UVCB
Name : Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha
CAS-No. : 64741-84-0
EC-No. : 265-086-6
EC Index-No. : 649-278-00-0
Synonyms : Textile spirits/Naphtha, solvent-refined light (petroleum)/Ligroine (petroleum), solvent-refined light/Naphtha (petroleum), solvent-refined light/Naphtha, petroleum, solvent-refined light/Naphtha (petroleum), solvent-refined light - low boiling point modified naphtha/Naphtha (petroleum) solvent-refined light/Naphtha, (petroleum), solvent-refined light/Naphtha, petroleum, solvent refined light/Naphtha (petroleum), solvent-refined light

Name	GHS Product identifier	%
Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha	CAS-No.: 64741-84-0	100
Heptane, isomers (Isomer mixture)	CAS-No.: Not assigned	25 - 60
Octane, isomers (Isomer mixture)	CAS-No.: Not assigned	5 - 38

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023

Name	GHS Product identifier	%
Hexane, isomers (Isomer mixture)	CAS-No.: Not assigned	5 - 20
n-hexane	CAS-No.: 110-54-3	4 – 9
Methylcyclopentane	CAS-No.: 96-37-7	0 – 4
2,4-dimethylhexane	CAS-No.: 589-43-5	0 - 3
Cyclopentane, 1,2,3-trimethyl-, (1.alpha.,2.alpha.,3.beta.)-	CAS-No.: 15890-40-1	0 – 2
Pentane, 2,2,3-trimethyl-	CAS-No.: 564-02-3	0 – 2
cyclohexane	CAS-No.: 110-82-7	0 – 0.5
Heptane, 2,5-dimethyl-	CAS-No.: 2216-30-0	0 – 0.5
Toluene	CAS-No.: 108-88-3	0 – 0.3

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Do not apply mouth-to-mouth resuscitation. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Continue to rinse for at least 15 minutes. Wash contaminated clothing before reuse. Get medical advice if skin irritation persists.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Seek medical attention if ill effect or irritation develops.
First-aid measures after ingestion	: Do not induce vomiting. Rinse mouth. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects	: Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Note to physician :	: Treat symptomatically.
---------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.
Explosion hazard	: Vapour heavier than air may travel considerable distance to a source of ignition and flash back. May explode or ignite :
Hazardous decomposition products in case of fire	: Thermal decomposition can lead to the release of irritating gases and vapours.

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023

5.3. Special protective actions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
- Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Avoid contact with spilled material. Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Avoid contact with skin. Do not breathe mist, spray, vapours.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Ventilate area. Approach from upwind. Stop leak if safe to do so. No open flames, no sparks, and no smoking. Avoid contact with skin. Avoid breathing mist or vapour.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leaks if it can be done without personal risk. Control the vapours with a fine water spray. Collect spillage.
- Methods for cleaning up : Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Use only non-sparking tools. Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of in a safe manner in accordance with local/national regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Handle empty containers with care because residual vapours are flammable.
- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid ignition sources. Product can accumulate electrostatic charges that may cause fire by electrical discharges. Use only non-sparking tools. Use grounded electrical/mechanical equipment. Spilled product must never be returned to the original container for recycling. No open flames. No smoking. Wash contaminated clothing before reuse. Avoid contact with skin. Do not breathe mist, spray, vapours.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep away from sources of ignition. Use only in well ventilated areas. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical/ventilating/lighting equipment.

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023

Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Heat. Keep container closed when not in use. Keep away from ignition sources. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.
Incompatible materials	: Strong oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Heptane, isomers	
Brazil - Occupational Exposure Limits	
OEL TWA	400 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	400 ppm
ACGIH OEL STEL	500 ppm (Heptane, all isomers)
Remark (ACGIH)	TLV® Basis: CNS impair; URT irr
Regulatory reference	ACGIH 2024
Hexane, isomers	
Brazil - Occupational Exposure Limits	
OEL TWA	200 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	200 ppm
Remark (ACGIH)	TLV® Basis: URT irr; lung dam. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024
Octane, isomers	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1400 mg/m ³
	300 ppm
Remark (ACGIH)	TLV® Basis: URT irr
Regulatory reference	ACGIH 2024
n-hexane (110-54-3)	
Brazil - Occupational Exposure Limits	
OEL TWA	50 ppm
Brazil - Biological limit values	
Local name	n-hexano
BEI	0.5 mg/l Parâmetro: 2,5 hexanodiona (2,5HD) - Meio: Urina - Momento de amostragem: Final de jornada de trabalho - Observações: O método analítico deve ser realizado sem hidrólise para este IBE/EE.
Remark	Interpretação: IBE/EE - Indicadores Biológicos de Exposição Excessiva.
Regulatory reference	NR 7 - PCMSO
USA - ACGIH - Occupational Exposure Limits	
Local name	n-Hexane
ACGIH OEL TWA	50 ppm

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023

n-hexane (110-54-3)	
Remark (ACGIH)	TLV® Basis: CNS impair; peripheral neuropathy; eye irr. Notations: Skin; BEI
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	n-Hexane
BEI	0.5 mg/l Parameter: 2,5-Hexanedione (without hydrolysis) - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2024
cyclohexane (110-82-7)	
Brazil - Occupational Exposure Limits	
Local name	Ciclohexano
OEL TWA	820 mg/m ³
	235 ppm
Regulatory reference	Norma Regulamentadora Nº 15 - Atividades e Operações Insalubres
USA - ACGIH - Occupational Exposure Limits	
Local name	Cyclohexane
ACGIH OEL TWA	100 ppm
Remark (ACGIH)	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	Cyclohexane
BEI	50 mg/g creatinine Parameter: 1,2-Cyclohexanediol - Medium: urine - Sampling time: End of shift, end of workweek - Notations: Ns
Regulatory reference	ACGIH 2024
Toluene (108-88-3)	
Brazil - Occupational Exposure Limits	
Local name	Tolueno (toluol)
OEL TWA	290 mg/m ³
	78 ppm
Remark (NR-15)	Absorção também p/pele
Chemical category	skin designation{0}
Regulatory reference	Norma Regulamentadora Nº 15 - Atividades e Operações Insalubres
Brazil - Biological limit values	
Local name	Tolueno
BEI	0.02 mg/l Parâmetro: Tolueno - Meio: Sangue - Momento de amostragem: Início da última jornada de trabalho da semana. 0.03 mg/l Parâmetro: Tolueno - Meio: Urina - Momento de amostragem: Final de jornada de trabalho. 0.3 mg/g creatinine Parâmetro: Orto-cresol - Meio: Urina - Momento de amostragem: Final de jornada de trabalho - Observações: Encontrado em populações não expostas ocupacionalmente. Método analítico exige hidrólise para este IBE/EE.

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023

Toluene (108-88-3)	
Remark	Interpretação: IBE/EE - Indicadores Biológicos de Exposição Excessiva.
Regulatory reference	NR 7 - PCMSO
USA - ACGIH - Occupational Exposure Limits	
Local name	Toluene
ACGIH OEL TWA	20 ppm
Remark (ACGIH)	TLV® Basis: CNS, visual & hearing impair; female repro system eff; pregnancy loss. Notations: OTO; A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	Toluene
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)
Regulatory reference	ACGIH 2024

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency safety showers should be available in the immediate vicinity of any potential exposure. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Use spark-/explosionproof appliances and lighting system.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures

Personal protective equipment:

Antistatic clothing including shoes are recommended. Wear fire/flame resistant/retardant clothing.

Materials for protective clothing:

Flame retardant antistatic protective clothing

Hand protection:

Protective gloves made of PVC. Nitrile rubber. Polyvinylalcohol (PVA). ISO 374-1. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer

Eye protection:

Chemical goggles or safety glasses. ISO 16321-1

Skin and body protection:

Long sleeved protective clothing. Antistatic clothing

Respiratory protection:

Wear suitable respiratory equipment in case of insufficient ventilation. An approved organic vapour respirator/supplied air or self-contained breathing apparatus must be used when vapour concentration exceeds applicable exposure limits

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Colour	: Colourless to slightly yellow
Odour	: gasoline-like
Odour threshold	: Not available
pH	: Not available
Melting point	: -45 – -38 °C
Freezing point	: Not available
Boiling point	: 60 – 135 °C
Flash point	: -45 – -38 °C
Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: 1.4 – 7.6 vol %
Vapour pressure	: 3.13 psi @ 20°C
Relative vapour density at 20°C	: 3 – 4
Relative density	: 0.67 – 0.7 g/cm ³ @ 20°C
Density	: Not available
Solubility	: organic solvent.
Partition coefficient n-octanol/water (Log Pow)	: 2.723
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: 280 – 465 °C
Decomposition temperature	: Not available
Viscosity, kinematic	: 0.35 – 0.45 mm ² /s
Viscosity, dynamic	: 0.5 – 0.65 mPa·s
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle specific surface area	: Not applicable

9.2. Data relevant with regard to physical hazard classes

No additional information available

9.3. Further safety characteristics

No additional information available

SECTION 10: Stability and reactivity

Chemical stability	: The product is stable at normal handling and storage conditions.
Conditions to avoid	: Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition can lead to the release of irritating gases and vapours.
Incompatible materials	: Strong oxidizing agents.
Possibility of hazardous reactions	: Static-accumulating.
Reactivity	: Highly flammable liquid and vapour.
Handling temperature	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met).
Acute toxicity (dermal)	: May be harmful in contact with skin.
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met).

Naphtha (petroleum), solvent-refined light (64741-84-0)	
LD50 oral rat	> 7000 mg/kg (Source: IUCLID)
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023

Naphtha (petroleum), solvent-refined light (64741-84-0)	
LC50 Inhalation - Rat	43767 mg/m ³ (Exposure time: 4 h Source: ECHA_API)
Hexane, isomers	
LC50 Inhalation - Rat (Vapours)	> 20 mg/l
Octane, isomers	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 24.88 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	118 mg/l/4h
LC50 Inhalation - Rat (Vapours)	> 24.88 mg/l Source: ECHA
n-hexane (110-54-3)	
LD50 oral rat	25 g/kg (Source: NLM_CIP)
LD50 dermal rabbit	3000 mg/kg (Source: NLM_CIP)
LC50 Inhalation - Rat [ppm]	48000 ppm/4h
ATE BR (oral)	25000 mg/kg bodyweight
ATE BR (dermal)	3000 mg/kg bodyweight
ATE BR (gases)	48000 ppmv/4h
cyclohexane (110-82-7)	
LD50 oral rat	12705 mg/kg (Source: NLM_CIP)
LD50 oral	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg (Source: EU_RAR)
LD50 dermal	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat	> 32.88 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat [ppm]	> 5540 ppm Source: ECHA
ATE BR (oral)	12705 mg/kg bodyweight
Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg (Source: JAPAN_GHS)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)
LD50 dermal	12124 mg/kg bodyweight
LC50 Inhalation - Rat	12.5 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	28100 mg/l
LC50 Inhalation - Rat (Vapours)	12.5 mg/l/4h
ATE BR (oral)	2600 mg/kg bodyweight
ATE BR (dermal)	12000 mg/kg bodyweight
ATE BR (vapours)	12.5 mg/l/4h
ATE BR (dust,mist)	12.5 mg/l/4h

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023

Cyclopentane, 1,2,3-trimethyl-, (1.alpha.,2.alpha.,3.beta.)- (15890-40-1)	
ATE BR (oral)	500 mg/kg bodyweight
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not available
Respiratory or skin sensitisation	: Not available
Germ cell mutagenicity	: Not available
Carcinogenicity	: Not available
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
Heptane, isomers	
STOT-single exposure	May cause drowsiness or dizziness.
Hexane, isomers	
STOT-single exposure	May cause drowsiness or dizziness.
Octane, isomers	
STOT-single exposure	May cause drowsiness or dizziness.
n-hexane (110-54-3)	
STOT-single exposure	May cause drowsiness or dizziness.
Methylcyclopentane (96-37-7)	
STOT-single exposure	May cause drowsiness or dizziness.
2,4-dimethylhexane (589-43-5)	
STOT-single exposure	May cause drowsiness or dizziness.
cyclohexane (110-82-7)	
STOT-single exposure	May cause drowsiness or dizziness.
Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
Cyclopentane, 1,2,3-trimethyl-, (1.alpha.,2.alpha.,3.beta.)- (15890-40-1)	
STOT-single exposure	May cause respiratory irritation.
Pentane, 2,2,3-trimethyl- (564-02-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not available
Octane, isomers	
NOAEC (inhalation, rat, vapour, 90 days)	24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
n-hexane (110-54-3)	
STOT-repeated exposure	May cause damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled).
Toluene (108-88-3)	
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023

Toluene (108-88-3)	
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
STOT-repeated exposure	May cause damage to organs (central nervous system, hearing organs, eyes) through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.
Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

Naphtha (petroleum), solvent-refined light (64741-84-0)	
Viscosity, kinematic	0.35 – 0.45 mm ² /s

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic) : Very toxic to aquatic life with long lasting effects.
Other information : Avoid release to the environment.

Naphtha (petroleum), solvent-refined light(64741-84-0)	
LC50 - Fish [1]	4.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: ECHA)
EC50 - Crustacea [1]	9.74 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	8.41 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static, closed] Source: ECHA)

Octane, isomers	
LC50 - Fish [1]	0.885 mg/l
EC50 - Crustacea [1]	0.3 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	0.9 mg/l Source: ECHA
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.028 mg/l

n-hexane (110-54-3)	
LC50 - Fish [1]	2.5 mg/l
EC50 - Other aquatic organisms [1]	50 mg/l waterflea

cyclohexane (110-82-7)	
LC50 - Fish [1]	3.96 – 5.18 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	23.03 – 42.07 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023

cyclohexane (110-82-7)	
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)
EC50 72h - Algae [2]	9.317 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
Toluene (108-88-3)	
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Other aquatic organisms [1]	3.78 mg/l waterflea
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'
NOEC chronic crustacea	0.74 mg/l

12.2. Persistence and degradability

Naphtha (petroleum), solvent-refined light (64741-84-0)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Naphtha (petroleum), solvent-refined light (64741-84-0)	
Partition coefficient n-octanol/water (Log Pow)	2.723
Bioaccumulative potential	Not established.

Octane, isomers	
Partition coefficient n-octanol/water (Log Pow)	5.18 Source: HSDB

n-hexane (110-54-3)	
Partition coefficient n-octanol/water (Log Pow)	3.9

cyclohexane (110-82-7)	
Partition coefficient n-octanol/water (Log Pow)	3.44 (at 25 °C (at pH 7))

Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7))

12.4. Mobility in soil

n-hexane (110-54-3)	
Mobility in soil	2187.76 Source: ECHA

12.5. Other adverse effects

Hazardous to the ozone layer : Not available
Other information : Avoid release to the environment.

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023




SECTION 13: Disposal considerations

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose of in a safe manner in accordance with local/national regulations.
Ecological waste information	: Avoid release to the environment.

SECTION 14: Transport information

14.1 National and international Regulations

In accordance with IMDG / IATA / ANTT

ANTT	IMDG	IATA
UN number		
1268	1268	1268
UN Proper Shipping Name		
PETROLEUM DISTILLATES, N.O.S. (Naphtha (petroleum), solvent-refined light)	PETROLEUM DISTILLATES, N.O.S. (Naphtha (petroleum), solvent-refined light)	Petroleum distillates, n.o.s. (Naphtha (petroleum), solvent-refined light)
Primary risk class/subclass		
3	3	3
Subsidiary risk class/subclass		
Not applicable	Not applicable	Not applicable
Hazard labels		
3	3	3
		
Risk Identification Number		
33	Not applicable	Not applicable
Packing group		
II	II	II
Environmental hazards		
Yes	Yes Marine pollutant: Yes	Yes
Transport in bulk according to MARPOL 73/78 and IBC Code		
Not applicable	Product name: Not listed Consult IMO instructions prior to transport	Not applicable

14.2 Other informations

This information does not intend to convey all specific regulatory or operational requirements/information with regards to the product, therefore it cannot be considered exhaustive. Consult ANTT, IMO and ICAO instructions before transporting the product. The carrier is responsible for following all applicable laws, regulations and rules related to the product transportation.

Braskem Ezolem™ 6-13

Safety Data Sheet

According to ABNT NBR 14725: 2023

SECTION 15: Regulatory information

15.1. National regulations

Regulatory reference : Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on the Canadian DSL (Domestic Substances List)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Listed on the NCI (Vietnam - National Chemical Inventory)
Listed on Thailand Existing Chemicals Inventory (DIW)

SECTION 16: Other information

Other information : None.

Safety Data Sheet (SDS), Brazil - Braskem

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. It warns that the handling of any chemical substance requires the previous knowledge of its hazards for the user. It is up to the user of the product company providing this SDS to and promote the training of its employees about possible risks come upon of the product. The information contained herein is not absolute, but only general information on the use of the chemical and indication of safety and security measures.