

AL FS-800; FS-801 Hydrophobic Fumed Silica SDS

Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Name: AL FS-800 Silicon Dioxide powder, silicone oil surface treated fumed silica, SiO₂

Other Names: silica, fumed silica, amorphous silica, hydrophobic fumed silica, pyrogenic silica

Supplier: **AL₂Chem LLC**
649 Route 206 Suite 9-132
Hillsborough, NJ 08844

For Emergency Call: CHEMTREC® US 800-424-9300 International +1-703-527-3887

2. HAZARDS IDENTIFICATION

Indication of danger: Not a hazardous substance or preparation according to the Global Harmonized System (GHS)

EMERGENCY OVERVIEW - CAUTION:

White powder. Odorless. Dust may be irritating to eyes and respiratory tract.

Repeated exposure may cause skin dryness or cracking. Take precautionary measures against static discharges. All metal parts of the mixing and processing equipment must be earthed/grounded. Ensure all equipment is electrically earthed/grounded before beginning transfer operations.

Principle Routes of Exposure: Inhalation, Skin contact, Eye contact

POTENTIAL HEALTH EFFECTS

Eye Contact: May cause mechanical irritation.

Skin Contact: Repeated exposure may cause skin dryness or cracking

Inhalation: Dust may be irritating to respiratory tract. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated. See also Section 8.

Ingestion: According to experience not expected.

Carcinogenic Effects: Does not contain any substances greater than 0.1% listed by IARC (International Agency for Research on Cancer), NTP (National Toxicology Program), OSHA (Occupational Safety and Health Administration), ACGIH (American Conference for Governmental Industrial Hygienists) or EU (European Union). See also Section 11.

Target Organ Effects: Lungs

Medical Conditions Aggravated by Exposure: Asthma, Respiratory disorder

Potential Environmental Effects: No special environmental precautions required.

AL FS-800; FS-801 Hydrophobic Fumed Silica SDS

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	EINECS/ELINCS Number	Weight %	EU Classification
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	*	100	None

* Exempt

4. FIRST AID MEASURES

Skin Contact: Wash thoroughly with soap and water. Seek medical attention if redness, swelling, itching, or burning occurs.

Eye Contact: Flush eyes immediately with large amounts of water for 15 minutes. Seek medical attention if redness, swelling, itching, burning or visual disturbances occur.

Inhalation: If cough, shortness of breath or other breathing problems occur, move to fresh air.

Seek medical attention if symptoms persist. If necessary, restore normal breathing through standard first aid measures.

Ingestion: Do not induce vomiting. If conscious, give several glasses of water. Never give anything by mouth to an unconscious person.

Notes to Physician: Treat symptomatically.

5. FIRE AND IGNITION INFORMATION

Flash Point: Not applicable

Explosion Limits in Air - Upper (g/m³): Not applicable

Explosion Limits in Air - Lower (g/m³): Not applicable

OSHA Flammability Classification: Not applicable

Autoignition Temperature: Not applicable

Method: Not applicable

Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special Protective Equipment for Firefighters:

Wear suitable protective equipment. In the event of fire, wear self-contained breathing apparatus.

Specific Hazards: Product resists ignition and does not promote flame spread. May release formaldehyde when heated to high temperatures in the presence of air. Formaldehyde is a known skin and lung sensitizer and is regulated as a carcinogen.

Hazardous Decomposition and/or Combustion Products:

Carbon monoxide, Carbon dioxide, Formaldehyde.

AL FS-800; FS-801 Hydrophobic Fumed Silica SDS

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid dust formation. Ensure adequate ventilation. Use personal protective equipment. See also Section 8.

Methods for Cleaning Up: Clean up promptly by vacuum. Use a suitable vacuum cleaner. Do not create a dust cloud by using a brush or compressed air. Pick up and transfer to properly labeled containers. See Section 13.

Environmental Precautions: No special environmental precautions required. Local authorities should be advised if significant spillages cannot be contained.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. Avoid dust formation. Do not breathe dust. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated. Do not create a dust cloud by using a brush or compressed air. Take precautionary measures against static discharge. All metal parts of the mixing and processing equipment must be earthed/grounded. Ensure all equipment is electrically earthed/grounded before beginning transfer operations.

Storage: Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store together with volatile chemicals as they may be adsorbed onto product. Keep at ambient temperatures.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS

Amorphous Silica, The regulatory exposure limits are found under the general silica, CAS RN 7631-86-9:

Australia:	2 mg/m ³ , TWA, Respirable
Austria MAK:	4 mg/m ³ , TWA, Inhalable fraction
Finland:	5 mg/m ³
Germany TRGS 900:	4 mg/m ³ , TWA, Inhalable fraction
India:	10 mg/m ³ , TWA
Ireland:	2.4 mg/m ³ , TWA, Respirable dust
Norway:	1.5 mg/m ³ , TWA, Respirable dust
Switzerland:	4 mg/m ³ , TWA
UK WEL:	6 mg/m ³ , TWA, Total inhalable fraction 2.4 mg/m ³ , TWA, Respirable fraction
US OSHA PEL:	6 mg/m ³

Dust, or Particulates Not Otherwise Specified:

US ACGIH - TLV:	10 mg/m ³ , TWA, Inhalable 3 mg/m ³ , TWA, Respirable
Belgium:	10 mg/m ³ , TWA, Inhalable 3 mg/m ³ , TWA, Respirable
China:	8 mg/m ³ , TWA 10 mg/m ³ , STEL
France:	10 mg/m ³ , TWA Inhalable dust 5 mg/m ³ , TWA Respirable dust
Italy:	10 mg/m ³ , TWA, Inhalable 3 mg/m ³ , TWA, Respirable

AL FS-800; FS-801 Hydrophobic Fumed Silica SDS

Malaysia:	10 mg/m ³ , TWA, Inhalable 3 mg/m ³ , TWA, Respirable
Spain:	10 mg/m ³ , VLA, Inhalable 3 mg/m ³ , VLA, Respirable

MAK: Maximale Arbeitsplatzkonzentration (Maximum Workplace Concentration)

OEL: Occupational Exposure Limit

PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit

TLV: Threshold Limit Value

TRGS: Technische Regeln für Gefahrstoffe (Technical Rule for Hazardous Materials)

TWA: Time Weighted Average

US ACGIH: United States American Conference of Governmental Industrial Hygienists

US OSHA: United States Occupational Safety and Health Administration

VLA: Valore Límite Ambientales (Environmental Limit Value)

WEL: Workplace Exposure Limit

ENGINEERING CONTROLS Ensure adequate ventilation to maintain exposures below occupational limits. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection: Approved respirator may be necessary if local exhaust ventilation is not adequate.

Hand Protection: Repeated exposure may cause skin dryness or cracking. Use appropriate protective barrier before handling.

Eye Protection: Wear eye/face protection.

Skin and Body Protection: Wear suitable protective clothing.

Other: Handle in accordance with good industrial hygiene and safety practice. Emergency eyewash and safety shower should be located nearby.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White Powder
Odor:	None, under normal use, may exhibit odor at high temperature.
pH:	Not determined
Vapor Pressure:	Not applicable
Boiling Point/Range:	2230°C
Melting Point/Range:	1700°C
Water Solubility:	Insoluble
Density:	2.2 g/cm ³ @ 20°C
% Volatile (by Volume):	Not applicable
Evaporation Rate:	Not determined
Viscosity:	Not determined
Partition Coefficient (n-octanol/water):	Not applicable

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous Polymerization:	Hazardous polymerization does not occur.
Mechanical Sensitivity (shock):	Not sensitive to mechanical impact.
Conditions to Avoid:	Avoid dust formation. Thermal decomposition can take place above 150°C. May release formaldehyde when heated to high temperatures in the presence of air. Formaldehyde is a known skin and lung sensitizer and is regulated as a carcinogen. Keep away from heat and sources of ignition. Avoid dust formation. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Product resists ignition and does not promote flame spread.
Hazardous Decomposition and/or Combustion Products:	Carbon monoxide, Carbon dioxide, Formaldehyde.
Static Discharge Effects:	Take precautionary measures against static discharges. Avoid dust formation. All metal parts of the mixing and processing equipment must be earthed/grounded. Ensure all equipment is electrically earthed/grounded before beginning transfer operations. This material is an inorganic dust and will not create nor support conditions that would result in a dust explosion or fire.

11. TOXICOLOGICAL INFORMATION

Information given is based on data obtained from this substance or from similar substances.

ACUTE TOXICITY

Oral LD50: LD50/oral/rat = > 5000 mg/kg.

Inhalation LC50: Due to the product's physical characteristics, no suitable testing procedure is available.

Dermal LD50: LD50/dermal/rabbit = > 2000 mg/kg.

Eye Irritation: Draize score 1.0/110 @ 24 hr.

Skin Irritation: 0/8 @ 24 hr.

SUBCHRONIC TOXICITY

No significant treatment-related adverse effects were observed in rats administered silica at doses of up to 8% silica in their diet for a duration of 2 weeks to 6 months.

CHRONIC TOXICITY

Carcinogenic Effects: Does not contain any substances greater than 0.1% listed by IARC (International Agency for Research on Cancer), NTP (National Toxicology Program), OSHA (Occupational Safety and Health Administration), ACGIH (American Conference for Governmental Industrial Hygienists) or EU (European Union).

Mutagenic Effects: Not mutagenic in AMES Test, Negative in the unscheduled DNA synthesis assay, Negative in the chromosome aberration test in Chinese hamster ovary (CHO) cells.

AL FS-800; FS-801 Hydrophobic Fumed Silica SDS

Reproductive Toxicity:	Did not show teratogenic effects in animal experiments. According to experience not expected.
Sensitizing Effects:	According to experience, sensitization is not expected.
Synergistic Materials:	None reasonably foreseeable.

12. ECOLOGICAL INFORMATION

Aquatic Toxicity:	Fish (Brachydanio rerio) NOEC (96 hours): = 10,000 mg/l; (Method: OECD 203) Daphnia magna NOEC(24 hours): = 10,000 mg/l; (Method: OECD 202) Algae EC50 (72 hour growth inhibition) = > 10,000 mg/l (Method: OECD201)
--------------------------	--

ENVIRONMENTAL FATE

Mobility:	Not expected to migrate.
Bioaccumulation:	Not expected due to physicochemical properties of the substance.
Persistence / Degradability:	The methods for determining biodegradability are not applicable to inorganic substances
Distribution to Environmental Compartments:	Not determined.

13. DISPOSAL CONSIDERATIONS

Disclaimer: Information in this section pertains to the product as shipped in its intended composition as described in Section 3 of this MSDS. Contamination or processing may change waste characteristics and requirements. Regulations may also apply to empty containers, liners or rinsate. State/provincial and local regulations may be different from federal regulations

RCRA Classification (40 CFR 261): Not a hazardous waste.

Unused and Uncontaminated Product: Product, as supplied, should be disposed of in accordance with the regulations issued by the appropriate federal, state and local authorities. Same consideration should be given to containers and packaging.

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

- US Department of Transportation
- Canadian Transport of Dangerous Goods Regulation
- European Transport of Dangerous Goods Regulation
- GGVS, GGVE, RID, ADR, IMDG Code, ICAO-TI
- United Nations (no UN number)

AL FS-800; FS-801 Hydrophobic Fumed Silica SDS

15. REGULATORY INFORMATION

Hazard Classification

United States - OSHA (29 CFR 1910.1200): Hazardous.

Mexico - NOM-018-STPS-2000: Refer to HMIS Rating in Section 16.

Canada - WHMIS Classification (CPR, SOR/88-66): Not controlled.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International Inventories

All components of this product are listed on or exempt from the following inventories:

YES - Australian Inventory of Chemical Substances (AICS)

YES - Canadian Domestic Substances List (DSL)

YES - Chinese Inventory

YES - European Inventory of Existing Commercial Chemical Substances (EINECS)

YES - Japanese Existing and New Chemical Substances (ENCS)

YES - Korean Existing Chemicals List (KECL)

YES - New Zealand Hazardous Substances and New Organisms Act (HSNO)

YES - Philippine Inventory of Chemicals and Chemical Substances (PICCS)

YES - United States Toxic Substances Control Act (TSCA) Inventory

U.S. Federal Regulations

TSCA 12(b) Export Notification: This product does not contain any components that are subject to TSCA 12(b) Export Notification.

Clean Air Act Amendments of 1990 (CAA, Section 112, 40 CFR 82): This product does not contain any components listed as a Hazardous Air Pollutant, Flammable Substance, Toxic Substance, or Class 1 or 2 Ozone Depletor.

Clean Water Act (CWA, 40 CFR 116) Priority Pollutants: This product does not contain any listed Priority Pollutants.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA, 40 CFR 302): This product does not contain any listed Hazardous Substances.

Superfund Amendments and Reauthorization Act, Title III (SARA):

SARA Section 302 (40 CFR 355) Extremely Hazardous Substances: No components are listed as extremely hazardous chemicals under SARA Section 302.

SARA Sections 311/312 (40 CFR 370) Hazard Category: This product does not meet any of the MSDS Requirement definitions for a hazardous material under SARA Sections 311/312. Reporting may be required if the material is present at any one time in amounts equal to or greater than 10,000 pounds.

SARA Section 313 (40 CFR 372) Toxics Release Inventory: Does not contain any of the substances identified under Section 313 as toxic chemicals in excess of the de minimis concentrations necessary to be subject to the supplier notification requirements.

Pharmaceutical Information: Not permitted

U.S. State Regulations

AL FS-800; FS-801 Hydrophobic Fumed Silica SDS

California Proposition 65: This product does not contain any components listed on California Proposition 65.

This product is not listed on California Proposition 65.

US Coalition of Northeastern Governors (CONEG) Metals List: This product meets the CONEG Source Reduction Council limits for the sum of the levels of lead, cadmium, mercury and hexavalent chromium of less than 100 parts per million by weight.

16. OTHER INFORMATION

HMIS Rating

HMIS Index: * - chronic, 0 - minimal, 1 - slight, 2 - moderate, 3 - serious, 4 - severe

Health: 1

Flammability: 0

Physical Hazard: 0

Revised: 2015-June-01

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall AL₂Chem LLC be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if AL₂Chem LLC has been advised of the possibility of such damages.