

TECKREZ C940

SAFETY DATA SHEET

1. Identification

Product Identifier/Code Teckrez C940, Aromatic Hydrocarbon Resin
Recommended use Adhesives, Sealants, Coatings, Wax, and other formulations
Recommended restrictions None known
Manufacturer Teckrez, Inc.
Company address 4209 Baymeadows Rd, Suite 3
Jacksonville, FL 32217 USA
Office: 1-904-215-7885
Fax: 1-904-215-7797
Emergency: Within USA and Canada: +1 800-424-9300
Outside USA and Canada: +1 703-527-3887

2. Hazards Identification

Physical hazards Not classified; molten material will cause thermal burns.
Health hazards Carcinogenic Category 2
OSHA defined hazards Combustible dust
Label elements



Hazard Symbol
Signal word Warning
Hazard statement May form combustible dust concentrations in air. Naphthalene is suspected of causing cancer.
Precautionary statement Practice good industrial hygiene. Store in protective environment, away from incompatible materials and elevated temperature equipment. Wash hands and other exposed areas after handling. Waste disposal in accordance with local requirements.
Storage Store away from incompatible materials.
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazards not otherwise classified (HNOC) Dust or particulates may cause mild respiratory tract and eye irritation. Repeated or prolonged contact may cause slight irritation to the skin. Vapors form when material is processed at high temperatures may be irritating to the eyes and upper respiratory tract.

3. Composition/Information on Ingredients

Chemical Name	CAS number	%
Aromatic Hydrocarbon Resin	64742-16-1	>99.8%
Naphthalene	91-20-3	< 0.1%

4. First-aid Measures

Inhalation	Move exposed person to fresh air. Keep person warm and at rest. Get medical attention if symptoms persist.
Skin contact	Flush contaminated skin with soap and water. Remove contaminated clothing and shoes. Cool as quickly as possible if exposed to molten material. Do not attempt to remove adhered material from skin; material will come off as healing occurs. Get medical attention if symptoms occur.
Eye contact	Immediately flush eyes with water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Get medical attention if irritation occurs and persists.
Ingestion	Seek medical attention.
Most important symptoms/ effects, acute and delayed	Dust may irritate intestinal track.
Indication of immediate medical attention and special treatment needed	Burns should be treated as thermal burns; material will come off as healing occurs.

5. Fire-fighting Measures

Suitable extinguishing media	Water spray, dry chemical, carbon dioxide
Unsuitable extinguishing media	Avoid high pressure extinguisher application which could spread fire.
Specific hazards arising from the chemical	Powdered material may cause explosive dust-air combinations, particularly in presence of static electricity. Hazardous decomposition products in the case of a fire includes: CO ₂ , carbon monoxide, smoke.
Specific protective equipment and precautions Specific methods	Appropriate protective clothing and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode. Use standard firefighting procedures and consider hazards of other materials.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Use suitable protective equipment. Keep unnecessary personnel away from material.
Methods and materials for containment and cleaning up	Vacuum or carefully contain and collect material and place in an appropriate container for disposal. Avoid creating dusty conditions and prevent wind dispersal.
Environmental precautions	Keep from drains; prevent uncontrolled run-offs. Avoid disposal into sewage or drainage systems.

7. Handling and Storage

Precautions for safe handling	Wash thoroughly after handling. Prevent contact with molten material.
Conditions for safe storage, including any incompatibilities	Keep container tightly closed in a cool, well-ventilated area. Keep away from ignition sources and static electricity. Employ good housekeeping practices to prevent build-up of dust and residue.

8. Exposure Controls/Personal

8.1 Occupational exposure limits

USA ACGIH	ACGIH (mg/m ³)	10 mg/m ³ (inhalable dust)
USA ACGIH	Remark (ACGIH)	Particulates, not otherwise classified
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	Remark (US OSHA)	Particulates, not otherwise classified

Naphthalene (91-20-3)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	Remark STEL (ppm)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	50 mg/m ³
USA OSHA	Remark PEL (TWA) (ppm)	10 ppm

8.2 Exposure controls

Appropriate engineering controls	Ensure good ventilation of the work station. Consider explosion proof ventilation equipment.
Hand protection	Protective chemical resistant gloves
Eye protection	Safety glasses with side shields (or goggles)
Skin and body protection	Wear suitable protective clothing, including appropriate clothing for exposure to molten material.
Respiratory protection	Where exposure through inhalation may occur from use, respiratory protection equipment of approved standard is recommended. Wear appropriate respiratory protection, if occupational exposure limits are exceeded or irritation/sensitivity is experienced.

9. Physical and Chemical Properties

Appearance

Physical state	Solid
Form	Solid
Color	Yellow
Odor	Slight Hydrocarbon
pH	Not available
Melting point	135-145°C
Initial boiling point	>260°C (500°F)
Flash point	> 260°C
Evaporation rate	Not determined; considered negligible
Auto ignition temperature	Not determined
Flammability (solid, gas)	Not determined
Decomposition temperature	Not established. Very low hazard expected at normal operating conditions.
Density	1.07 g/cm ³ (8.549 lb(s)/gal)
Solubility	Insoluble in water. Good solubility in aliphatic and aromatic hydrocarbons. Minimal solubility in alcohols.
Viscosity	100,000 cps @ 177°C
Vapor pressure	22.5 mm Hg (approx.)

10. Stability and Reactivity

Reactivity and chemical stability	Non-reactive and stable under normal operating conditions. Decomposition can occur at elevated temperatures.
Possibility of hazardous reactions	None known under normal operating conditions.
Conditions to avoid	Open flame, static electricity, dusty conditions
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Smoke, carbon dioxide, carbon monoxide

11. Toxicology Information

Information on likely routes of exposure

Inhalation	Dust and vapor. Fumes may irritate respiratory system.
Skin Contact	Molten material causes thermal burns.
Eye Contact	Direct contact with eyes may cause temporary irritation

Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.
-----------------------	---

Naphthalene (91-20-3)	
LD50 oral rat	490 mg/kg
LD50 dermal rabbit	>20 g/kg
LC50 inhalation rat	> 340 mg/m ³
ATE (oral)	500

Skin corrosion/irritation	No data available
Serious eye damage/irritation	No data available
Respiratory sensitization	No data available
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product contains trace quantities of Naphthalene which is considered to be a carcinogen.

Naphthalene (91-20-3)	
IARC group	2B-possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be human carcinogen

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity-single exposure	Not classified
Specific target organ toxicity-repeated exposure	Not classified
Aspiration hazard	Not available
Potential adverse human health effects and symptoms	Dust or particles may cause mild respiratory tract and eye irritation. Product may cause mild skin irritation.

12. Ecological Information

Ecological impact statement

This product is not classified as environmentally hazardous. This does not exclude the possibility that large or frequent spills could be environmentally damaging. This product is not readily biodegradable.

Naphthalene (91-20-3)	
LC50 fish 1	5.74-6.44 mg/l (Exposure time: 96 h- Species: Pimephales promelas {flow through})
EC50 Daphnia 1	2.16 mg/l (Exposure time: 48 h- Species: Daphnia magna)
EC50 other aquatic organisms 1	0.4 mg/l (Exposure time: 72 h-Species: Skeletonema costatum)
LC50 fish 2	1.6 mg/l (Exposure time: 96 h-Species: Oncorhynchus mykiss [(flow-through)])
EC50 Daphnia 2	1.96 mg/l (Exposure time: 48 h- Species: Daphnia magna [(Flow-through)])

Bioaccumulative potential

Naphthalene (91-20-3)	
BCF fish 1	30-430
Log Pow	3.3 (at 20°C)

13. Disposal Considerations

Disposal instructions

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

14. Transport Information

DOT

Not regulated as dangerous goods

IATA

Not regulated as dangerous goods

IMDG

Not regulated as dangerous goods

15. Regulatory Information

15.1. US Federal regulations

TSCA Section 12(b) Export Notification (40 CFR 707, subpoint D)

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Reauthorization Act 1986 (SARA)

SARA 311/312 Hazardous Chemical

Chronic health hazard

Fire hazard

SARA 313 TRI Reporting This product contains chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372:

Naphthalene	CAS No: 91-20-3	Concentration: <0.5%
--------------------	------------------------	--------------------------------

Export Control Classification Number (ECCN) EAR99 (No License Required)

15.2 International Regulation

Canada DSL Yes

15.3 US State regulations

California Controlled Substances, Dept. of Justice (CA Health and Safety Code Section 11100) Not listed

California Proposition 65 Trace quantities of naphthalene (<100 ppm) which is considered by the State of California to cause cancer and/or reproductive toxicity.

Naphthalene (91-20-3)	
U.S.- California- Proposition 65- Carcinogens List	Yes
No Significance Risk Level (NSRL)	5.8 mg/day

Massachusetts RTK-Substance List Not regulated

New Jersey Worker and Community RTK Act Not listed

Pennsylvania Worker and Community RTK Law Not listed

Rhode Island RTK Not listed

16. Other Information, including date of preparation or last revision

NFPA health hazard 2

NFPA fire hazard 1

NFPA reactivity 0

HMIS III Rating

Health 2

Flammability 1

Physical hazard 0

Personal protection See section 8 of SDS

Version 3.0

Date of issue January 10, 2022

Teckrez Disclaimer

NO WARRANTIES OF USE OR OTHERWISE ARE EXPRESSLY MADE OR IMPLIED FROM THIS INFORMATION. The information contained here is believed to be accurate and reliable by Teckrez and is provided only to enable the safe use, processing, handling, storage, transportation of this material in considering good health standards and in an environmentally sound manner according to OSHA and other pertinent regulations including GHS (Globally Harmonized System of Classifications and Labelling). It provides guidance on health, safety, and environmental aspects of product and should not be construed as any guarantee of technical performance or suitability for particular applications.

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best knowledge of TECKREZ, INC., or obtained from sources believed by TECKREZ, INC. to be accurate. TECKREZ, INC. does not assume any legal responsibility for use or reliance upon same. Customers are encouraged to conduct their own tests before using any product and carefully review technical and safety data information. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. TECKREZ, INC. makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.