

APPLICATION EQUIPMENT

# Millennium Cyclone System Solution



## DESCRIPTION

Millennium Cyclone System Solution is a specially formulated flushing solution developed for use with the Patented Millennium Cyclone\* (by Garlock). The convenient 1 gallon packaging with quick connect fittings makes it quick and easy to use.

## BASIC USE

Millennium Cyclone System Solution is used to flush residual adhesive component from the Cyclone pump and hose in preparation for long-term equipment storage. The Cyclone adhesive pump cart should be flushed with Millennium Cyclone System Solution immediately after use whenever the anticipated idle time for the pump is greater than two weeks.

## APPLICATION

1. Ensure that power to the Cyclone pump is off.
2. Remove Millennium PG-1 adhesive bags from Cyclone by disconnecting the quick connect fittings.
3. Install box labeled Millennium Cyclone System Solution Part 1 (color coded white) onto the Cyclone tray labeled Part 1 (white) and connect black fittings.
4. Install box labeled Millennium Cyclone System Solution Part 2 (color coded blue) onto the Cyclone tray labeled Part 2 (blue) and connect gray fittings.
5. Restore power to the Cyclone pump. Place an approved waste container under the gun and remove the mixing nozzle.
6. Slowly open the gun valves and pump entire contents of Millennium Cyclone System Solution into the waste container.  
**To ensure all adhesive component material is properly flushed out of the pump, hoses, and gun all solution in Part 1 and Part 2 boxes must be used.**

 **WARNING!** This product can expose you to Diisodecyl phthalate (DIDP) which is known to the State of California to cause reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SAFETY

Prior to working with this or any adhesive product consult product label and Safety Data Sheet (SDS) for necessary health and safety precautions.

## LIMITATIONS

- Not to be used as an adhesive
- For use in Cyclone 1 and Cyclone 5/15 pump machine only.

## STORAGE

Keep temperature of contents between 45°F-95°F (7°C-35°C). Bring temperature of material to approximately 70°F (22°C) just before use. Do not store in direct sunlight or above 95°F (35°C). Store boxes valve side up.

## PACKAGING AND COVERAGE

Millennium Cyclone System Solution is available in the following package:

Size	Part #	Sets/Pallet
1 gal (3.79L) box, Part 1 (A)	EQ-CSS1B-A01	20
1 gal (3.79L) box, Part 2 (B)	EQ-CSS1B-B01	20

## FEATURES

## BENEFITS

Quick connect fittings

Fast, easy hook up

Cleans/removes residual material for long term storage

Helps prevent cured adhesive from damaging pump and hose

One gallon packaging

Easy to handle

Specially designed for use in the Cyclone 1 & Cyclone 5/15

Will not damage pump or components

\*US 9,573,150 B2; US 9,566,594 B2

\*US 9,381,536 B2

\*\*US 7,056,556 B2; US D501,855 S; CA 2,493,739 C



For more information about our company, visit [www.hbfuller.com/roofing](http://www.hbfuller.com/roofing).



Join the Conversation | [www.hbfuller.com/connect](http://www.hbfuller.com/connect)

WARRANTY: H.B. Fuller warrants its products to conform to H.B. Fuller's specifications at the time of sale when tested according to H.B. Fuller standards. If a product is proven to be defective when tested according to H.B. Fuller standards, H.B. Fuller will, at its option, refund the purchase price or replace or repair the defective product. THIS LIMITED WARRANTY IS THE BUYER'S SOLE AND EXCLUSIVE REMEDY AGAINST H.B. FULLER AND IS IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event shall H.B. Fuller be liable for any special, incidental, consequential, or punitive damages arising out of any claims whether based on negligence, contract, warranty, strict liability or otherwise.